

### Features


- Halogen Free. "Green" Device (Note 1)
- AEC-Q101 Qualified
- High Surge Capability with Low Forward Voltage
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Lead Free Finish/RoHS Compliant (Note 2) ("P" Suffix Designates RoHS Compliant. See Ordering Information)

### Maximum Ratings @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Value					Unit
		SK34A HE3-L	SK36A HE3-L	SK310A HE3-L	SK3150A HE3-L	SK3200A HE3-L	
Peak Repetitive Reverse Voltage	$V_{RRM}$						V
Working Peak Reverse Voltage	$V_{RWM}$	40	60	100	150	200	
DC Blocking Voltage	$V_R$						
RMS Reverse Voltage	$V_{RMS}$	28	42	70	105	140	V
Average Rectified Forward Current	$I_{F(AV)}$	3					A
Non-Repetitive Peak Surge Current @ 8.3ms Half Sine Wave	$I_{FSM}$	80					A
Current Squared Time @ $1ms \leq t \leq 8.3ms$	$I^2t$	26.56					A <sup>2</sup> s

# 3 Amp Surface Mount Schottky Rectifier 40 to 200 Volts

### SMA (DO-214AC)





DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.075	0.096	1.90	2.44	
B	0.050	0.064	1.27	1.63	
C	0.002	0.008	0.051	0.203	
D	---	0.020	---	0.51	
E	0.030	0.060	0.76	1.52	
F	0.065	0.091	1.65	2.32	
G	0.189	0.220	4.80	5.59	
H	0.157	0.187	4.00	4.75	
J	0.090	0.115	2.25	2.92	


### Marking Code

Part Number	Marking Code
SK34AHE3-L	SK34A
SK36AHE3-L	SK36A
SK310AHE3-L	SK310A
SK3150AHE3-L	SK3150A
SK3200AHE3-L	SK3200A

### Internal Structure

Pin	Description	Simplified Outline	Graphic Symbol
1	Cathode	 <p>XXXX = Marking Code YYWW = Date Code</p>	
2	Anode		

### SUGGESTED SOLDER PAD LAYOUT



Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

2. High temperature solder exemption applied, see EU directive annex 7a.

## Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$T_J$	Operating Junction Temperature Range	SK34AHE3-L ~ SK36AHE3-L	-55		150	°C
$T_{stg}$	Storage Temperature Range		-55		150	°C
$T_J$	Operating Junction Temperature Range	SK310AHE3-L ~ SK3200AHE3-L	-55		175	°C
$T_{stg}$	Storage Temperature Range		-55		175	°C
$R_{th(J-L)}$	Thermal Resistance from Junction to Lead	Note 1		25		°C/W
$R_{th(J-A)}$	Thermal Resistance from Junction to Ambient	Note 1		80		°C/W

Note:

1. Mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper.

## Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage SK34AHE3-L SK36AHE3-L SK310AHE3-L SK3150AHE3-L ~ SK3200AHE3-L	$V_F$	$I_F=3A; T_J=25^\circ C$			0.50 0.70 0.80 0.90	V
Reverse Current SK34AHE3-L ~ SK36AHE3-L SK310AHE3-L ~ SK3200AHE3-L	$I_R$	at Rated $V_R; T_J=25^\circ C$ at Rated $V_R; T_J=100^\circ C$ at Rated $V_R; T_J=25^\circ C$ at Rated $V_R; T_J=125^\circ C$			0.1 10 0.001 0.15	mA
Junction Capacitance SK34AHE3-L SK36AHE3-L SK310AHE3-L SK3150AHE3-L ~ SK3200AHE3-L	$C_J$	$V_R=4V; f=1MHz; T_J=25^\circ C$		150 135 95 65		pF

**Curve Characteristics**

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 - Typical Forward Characteristics




Fig. 4 - Typical Reverse Leakage Characteristics




Fig. 5 - Typical Forward Characteristics





Fig. 6 - Typical Reverse Leakage Characteristics



**Curve Characteristics**

Fig. 7 - Typical Forward Characteristics




Fig. 8 - Typical Reverse Leakage Characteristics




Fig. 9 - Typical Forward Characteristics




Fig. 10 - Typical Reverse Leakage Characteristics





Fig. 11 - Capacitance Characteristics



## Ordering Information

Device	Packing
SK34AHE3-LTP ~ SK3200AHE3-LTP	Tape&Reel:5Kpcs/Reel

**\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp.* products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MCC\(美微科\)](#)