

**Features**

- Halogen Free. "Green" Device (Note 1)
- AEC-Q101 Qualified
- Lead Free Finish/RoHS Compliant(Note 2) ("P" Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Low Forward Voltage
- High Current Capability

**Maximum Ratings**

- Operating Junction Temperature Range: -55°C to +125°C(SK22HE3-L~SK26HE3-L)
- Operating Junction Temperature Range: -55°C to +150°C(SK28HE3-L~SK210HE3-L)
- Storage Temperature Range: -55°C to +150°C
- Maximum Thermal Resistance: 71°C/W Junction to Ambient
- Maximum Thermal Resistance: 15°C/W Junction to Lead

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SK22HE3-L	SK22	20V	14V	20V
SK23HE3-L	SK23	30V	21V	30V
SK24HE3-L	SK24	40V	28V	40V
SK25HE3-L	SK25	50V	35V	50V
SK26HE3-L	SK26	60V	42V	60V
SK28HE3-L	SK28	80V	56V	80V
SK210HE3-L	SK210	100V	70V	100V

**Electrical Characteristics @ 25°C Unless Otherwise Specified**


Average Forward Current	$I_{F(AV)}$	2.0A	$T_L=105^\circ\text{C}$
Peak Forward Surge Current	$I_{FSM}$	50A	8.3ms, half sine
Maximum Instantaneous Forward Voltage	$V_F$	0.50V	$I_{FM}=2.0A;$ $T_J=25^\circ\text{C}$ (Note 3)
SK22HE3-L~SK24HE3-L		0.70V	
SK25HE3-L~SK26HE3-L SK28HE3-L~SK210HE3-L		0.85V	
Maximum DC Reverse Current At Rated DC Blocking Voltage	$I_R$	100µA	$T_J=25^\circ\text{C};$
SK22HE3-L~SK26HE3-L SK28HE3-L~SK210HE3-L		50µA	
Typical Junction Capacitance	$C_J$	230pF	Measured at 1.0MHz $V_R=4.0V$
SK22HE3-L~SK26HE3-L SK28HE3-L~SK210HE3-L		50pF	

- Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.  
 2. High Temperature Solder Exemptions Applied, see EU Directive Annex 7a.  
 3. Pulse test: Pulse width 300 µsec, Duty cycle 2%

**2 Amp Schottky Rectifier  
20 to 100 Volts**

**DO-214AA**


**(SMB) (LEAD FRAME)**



**DIMENSIONS**

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.079	0.103	2.00	2.62	
B	0.075	0.087	1.91	2.21	
C	0.002	0.008	0.05	0.20	
D	0.006	0.012	0.15	0.31	
E	0.030	0.060	0.76	1.52	
F	0.065	0.091	1.65	2.32	
G	0.200	0.220	5.08	5.59	
H	0.160	0.191	4.06	4.85	
J	0.130	0.155	3.30	3.94	

**Suggested Solder Pad Layout**



**Curve Characteristics**

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 4 - Typical Instantaneous Forward Characteristics





Fig. 5 - Typical Instantaneous Forward Characteristics



**Curve Characteristics**

Fig. 7 - Typical Reverse Leakage Characteristics





Fig. 8 - Typical Reverse Leakage Characteristics



## Ordering Information

Device	Packing
SK22HE3-LTP~SK210HE3-LTP	Tape&Reel: 3Kpcs/Reel

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MCC\(美微科\)](#)