

### **Features**

- Two DTC143T Chip In a Package
- · Reduces Component Count
- Halogen Free. "Green" Device (Note 1)
- · Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant.See Ordering Information)

# Dual NPN Digital Transistor

### Maximum Ratings @ 25°C Unless Otherwise Specified

Parameter	Symbol	Value	Unit
Collector-Emitter Voltage	V <sub>CEO</sub>	50	V
Collector-Base Voltage	V <sub>CBO</sub>	50	V
Emitter-Base Voltage	V <sub>EBO</sub>	5	V
Collector Current	I <sub>C</sub>	100	mA
Collector Dissipation	P <sub>C</sub>	150	mW
Junction Temperature	TJ	150	°C
Storage Temperature Range	T <sub>STG</sub>	-55 to +150	°C
Thermal Resistance	R <sub>θJ-A</sub>	833	°C/W


Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

# SOT-363


DIMENSIONS						
DIM INCHES		M	M	NOTE		
DIIVI	MIN	MAX	MIN	MAX	NOIE	
Α	0.006	0.014	0.15	0.35		
В	0.045	0.053	1.15	1.35		
С	0.079	0.096	2.00	2.45		
D	0.026		0.	65	TYP.	
G	0.047	0.055	1.20	1.40		
Н	0.071	0.087	1.80	2.20		
J		0.004		0.10		
K	0.031	0.043	0.80	1.10		
L	0.010	0.018	0.26	0.46		
М	0.003	0.006	0.08	0.15		

### Device Marking: H3

### Internal Structure



### Suggested Solder Pad Layout





## Electrical Characteristics @ 25°C Unless Otherwise Specified

Parameter	Symbol	Min	Тур	Max	Units	Conditions
Collector-Base Breakdown Voltage	V <sub>(BR)CBO</sub>	50			<b>V</b>	$I_{C} = 50 \mu A, I_{E} = 0$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	50			V	I <sub>C</sub> =1mA, I <sub>B</sub> =0
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	5			٧	$I_{E}=50\mu A, I_{C}=0$
Collector Cut-off Current	I <sub>CBO</sub>			0.5	μA	$V_{CB}=50V,I_{E}=0$
Emitter Cut-off Current	I <sub>EBO</sub>			0.5	μA	$V_{EB}=4V,I_{C}=0$
DC Current Gain	h <sub>FE</sub>	100		600		I <sub>C</sub> =1mA, V <sub>CE</sub> =5V
Collector-Emitter Saturation Voltage	V <sub>CE(sat)</sub>			0.3	<b>V</b>	$I_C=5mA$ , $I_B=0.25mA$
Input Resistance	R <sub>1</sub>	3.29	4.7	6.11	ΚΩ	
Transition Frequency	f <sub>T</sub>		250		MHz	V <sub>CE</sub> =10.0V, I <sub>E</sub> =-5mA, f=100MHz



### **Curve Characteristics**

Fig. 1 - Static Characteristics

12

COMMON EMITTER

T<sub>A</sub>=25°C

10

8

4

45µA

45µA


35µA


25µA


10µA

15µA

10µA









### **Ordering Information**

Device	Packing
Part Number-TP	Tape&Reel:3Kpcs/Reel

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp**. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**, products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# 单击下面可查看定价,库存,交付和生命周期等信息

# >>MCC(美微科)