

Features

- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Epoxy Meets UL 94 V-0 Flammability Rating
- Fast Switching Speed For High Efficiency
- Glass Passivated Junction
- Lead Free Finish/RoHS Compliant(Note 1)("P" Suffix Designates Compliant. See Ordering Information)

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Typical Thermal Resistance: 30 °C/W Junction to Ambient


MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
FR301GP	FR301GP	50V	35V	50V
FR302GP	FR302GP	100V	70V	100V
FR303GP	FR303GP	200V	140V	200V
FR304GP	FR304GP	400V	280V	400V
FR305GP	FR305GP	600V	420V	600V
FR306GP	FR306GP	V008	560V	800V
FR307GP	FR307GP	1000V	700V	1000V

Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward			
Current	I _{F(AV)}	3.0A	T _A =55 °C
Peak Forward Surge Current	I _{FSM}	150A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage	V _F	1.30V	I _{FM} =3.0A; T _J =25°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0μA 100μA	T _J =25°C; T _J =55°C
Maximum Reverse Recovery Time FR301GP-304GP FR305GP FR306GP-307GP	t _{rr}	150ns 250ns 500ns	I _F =0.5A; I _R =1.0A; Irr=0.25A
Typical Junction Capacitance	CJ	50pF	Measured at 1.0MHz V _R =4.0V

Note:1. High Temperature Solder Exemptions Applied, See EU Directive Annex 7a.

3.0 Amp Fast Recovery Rectifier 50 to 1000 Volts



DIMENSIONS							
DIM	INCHES		MM		NOTE		
	MIN	MAX	MIN	MAX	NOTE		
Α	0.287	0.374	7.30	9.50			
В	0.189	0.208	4.80	5.30			
С	0.048	0.052	1.20	1.30			
D	1.000		25.40				



Curve Characteristics




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge
Current

160

(A)
120

80

80


80

8.3 ms Single Half Sine-Wave

100

Number of Cycles at 60 Hz

Fig. 4 - Typical Reverse Characteristics





Ordering Information

Device	Packing	
Part Number-TP	Tape&Reel: 1.2Kpcs/Reel	
Part Number-AP	Ammo Packing: 1.2Kpcs/Ammo Box	
Part Number-BP	Bulk:500pcs/Box,12Kpcs/Carton	

Note: Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)