

#### **Features**


- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates Compliant. See Ordering Information)
- Heat Transfer Through Aluminum Oxide DBC Ceramic Isolated Metal Baseplate
- Blocking voltage:800 to 1800V
- · Glass passivated chip

# **Applications**

- Three phase rectifiers for power supplies
- Rectifiers for DC motor field supplies
- · Battery charger rectifiers


MCC Part Number	$V_{RRM}$	$V_{RSM}$
MD200S08M5	800V	900V
MD200S12M5	1200V	1300V
MD200S16M5	1600V	1700V
MD200S18M5	1800V	1900V





Note:1. High Temperature Solder Exemptions Applied, See EU Directive Annex 7a.

# 200 Amp GLASS PASSIVATED THREE PHASE RECTIFIER BRIDGE 800~1800 Volts



DIMENSIONS					
DIM	INCI	HES	MM		NOTE
DIW	MIN	MAX	MIN	MAX	NOTE
Α	0.650	0.689	16.50	17.50	
В	0.098	0.138	2.50	3.50	
С	0.256	0.295	6.50	7.50	
D	2.028	2.067	51.50	52.50	
E	0.453	0.492	11.50	12.50	
F	2.106	2.146	53.50	54.50	
G	0.236	0.276	6.00	7.00	
Н	1.043	1.083	26.50	27.50	
	0.965	1.004	24.50	25.50	
J	2.579	2.618	65.50	66.50	
K	0.2	256	6.	50	Ф
L	2.815	2.854	71.50	72.50	
M	3.130	3.169	79.50	80.50	
N	3.681	3.720	93.50	94.50	



**Maximum Ratings** 

Symbol	Conditions	Values	Units
ΙD	Three phase, full wave Tc=100°C	200	A
IFSM	t=10mS Tvj =45℃	2240	A
i <sup>2</sup> t	t=10mS Tvj =45℃	25000	A <sup>2</sup> s
Visol	a.c.50HZ;r.m.s.;1min	3000	V
Tvj		-40 to +150	$^{\circ}$
Tstg		-40 to +125	$^{\circ}$
Mt	To terminals(M6)	5±15%	Nm
Ms	To heatsink(M6)	5±15%	Nm
Weight	Module (Approximately)	194	g

# **Thermal Characteristics**

Symbol	Conditions	Values	Units
Rth(j-c)	Per diode	0.45	°C/W
Rth(c-s)	Module (Approximately)	0.025	°C/W

## **Electrical Characteristics**

Symbol	Conditions	Values			Units
Symbol	Conditions	Min.	Тур.	Max.	Ullits
VFM	T=25°C IF =300A	_	1.45	1.70	V
IRD	Tvj=25℃ VRD=VRRM Tvj=150℃ VRD=VRRM	_	_	0.5 6	mA mA



#### **Performance Curves**




Fig1. Forward Characteristics





Fig3. Transient thermal impedance



**Fig5.Forward Current Derating Curve** 




Fig2. Power dissipation




Fig4. Max Non-Repetitive Forward Surge Current



### **Ordering Information**

Device	Packing
Part Number-BP	Bulk: 10PCS/BOX ;100PCS/CTN

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# 单击下面可查看定价,库存,交付和生命周期等信息

# >>MCC(美微科)