

Features

- Halogen Free
- AEC-Q101 Qualified
- · High Current Capability
- · Low Forward Voltage
- For Surface Mount Application
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Typical Thermal Resistance(Note 2) : 50°C/W Junction to Ambient
- Typical Thermal Resistance(Note 2): 18°C/W Junction to Lead

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SK82LHE3	SK82	20V	14V	20V
SK84LHE3	SK84	40V	28V	40V
SK86LHE3	SK86	60V	42V	60V
SK810LHE3	SK810	100V	70V	100V


Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	8.0A	T _L =95°C
Peak Forward Surge Current	I _{FSM}	200A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage			
SK82LHE3-86LHE3 SK810LHE3	V _F	0.65V 0.80V	I _{FM} =8.0A; T _J =25°C
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	0.1mA 10mA	T _J =25°C; T _J =100°C
Typical Junction Capacitance	CJ	400pF	Measured at 1.0MHz, V _R =4.0V

Note: 1. High Temperature Solder Exemptions Applied, See EU Directive Annex 7a. 2.Mounted on P.C.B. With 0.6" x 0.6" (16 mm x 16 mm) Copper Pad Areas


8.0 Amp Schottky Rectifier 20 to 100 Volts

SMC (DO-214AB)



DIMENSIONS						
DIM	INCHES		MM		NOTE	
	MIN	MAX	MIN	MAX	NOTE	
Α	0.079	0.103	2.00	2.62		
В	0.108	0.128	2.75	3.25		
С	0.002	0.008	0.051	0.203		
D	0.006	0.012	0.152	0.305		
Е	0.030	0.060	0.76	1.52		
F	0.305	0.320	7.75	8.13		
G	0.260	0.280	6.60	7.11		
Н	0.220	0.245	5.59	6.22		

Suggested Solder Pad Layout





Curve Characteristics




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Reverse Leakage Characteristics




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge

Current

200

(Y)
175
200
100
75
Yeb 50
25
8.3 ms Single Half Sine-Wave

Fig. 4 - Typical Instantaneous Forward Characteristics

Number of Cycles at 60 Hz

100





Fig. 6 - Typical Reverse Leakage Characteristics





Ordering Information

Device	Packing	
Part Number-TP	Tape&Reel: 3Kpcs/Reel	

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Rev.3-2-12132019 _____ MCCSEMI.COM

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)