

Features


- High Density Cell Design for Low $R_{DS(on)}$
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings

- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 62.5°C/W Junction to Case


Parameter	Symbol	Rating	Unit
Total Power Dissipation	P_D	2	W
N-Channel			
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D	4.5	A
P-Channel			
Drain-Source Voltage	V_{DS}	-30	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D	-3.5	A

Internal Structure and Marking Code



Dual N&P-Channel MOSFET

SOT23-6L



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.012	0.020	0.30	0.50	
B	0.051	0.070	1.30	1.80	
C	0.087	0.126	2.20	3.20	
D	0.037		0.95		TYP.
G	0.074		1.90		TYP.
H	0.106	0.122	2.70	3.10	
J	0.002	0.006	0.05	0.15	
K	0.030	0.051	0.75	1.30	
L	0.012	0.024	0.30	0.60	
M	0.003	0.008	0.08	0.22	

Electrical Characteristics @ 25°C (Unless Otherwise Specified)
N-Channel

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	30			V
Gate-Source Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V, V_{GS}=0V$			1	μA
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1.0	1.5	2.5	V
Drain-Source On-Resistance ^(Note1)	$R_{DS(on)}$	$V_{GS}=10V, I_D=3A$			35	m Ω
		$V_{GS}=4.5V, I_D=2A$			50	m Ω
Diode Characteristics						
Diode Forward Voltage ^(Note1)	V_{SD}	$V_{GS}=0V, I_S=1A$			1.2	V
Reverse Recovery Time	t_{rr}	$I_{SD}=3.6 A, dI_{SD}/dt=100A/\mu s$		17.3		nS
Reverse Recovery Charge	Q_{rr}			1.66		nC
Dynamic Characteristics^(Note2)						
Input Capacitance	C_{iss}	$V_{DS}=10V, V_{GS}=0V, f=1MHz$		315		pF
Output Capacitance	C_{oss}			59		
Reverse Transfer Capacitance	C_{rss}			48		
Total Gate Charge	Q_g	$V_{DS}=10V, V_{GS}=15V, I_D=3.6A$		6.08		nC
Gate-Source Charge	Q_{gs}			1.26		
Gate-Drain Charge	Q_{gd}			1.32		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V, V_{DS}=15V, R_{GEN}=3\Omega, R_L=4.1\Omega$		3.8		ns
Turn-On Rise Time	t_r			23.2		
Turn-Off Delay Time	$t_{d(off)}$			7		
Turn-Off Fall Time	t_f			18.6		

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

P-Channel

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-30			V
Gate-Source Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-30V, V_{GS}=0V$			-1	μA
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-1.0	-1.5	-2.5	V
Drain-Source On-Resistance ^(Note1)	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-3A$			90	m Ω
		$V_{GS}=-4.5V, I_D=-2A$			115	m Ω
Diode Characteristics						
Diode Forward Voltage ^(Note1)	V_{SD}	$V_{GS}=0V, I_S=-1A$			-1.2	V
Reverse Recovery Time	t_{rr}	$I_{SD}=-3A, dI_{SD}/dt=100A/\mu s$		25		nS
Reverse Recovery Charge	Q_{rr}			3.8		nC
Dynamic Characteristics^(Note2)						
Input Capacitance	C_{iss}	$V_{DS}=-10V, V_{GS}=0V, f=1MHz$		365		pF
Output Capacitance	C_{oss}			59		
Reverse Transfer Capacitance	C_{rss}			45		
Total Gate Charge	Q_g	$V_{DS}=-10V, V_{GS}=-15V, I_D=-3A$		7.5		nC
Gate-Source Charge	Q_{gs}			1.7		
Gate-Drain Charge	Q_{gd}			1.2		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=-10V, V_{DS}=-15V, R_{GEN}=2.5\Omega, I_{DS}=-1A$		3.2		ns
Turn-On Rise Time	t_r			17.8		
Turn-Off Delay Time	$t_{d(off)}$			18		
Turn-Off Fall Time	t_f			23.5		

Notes:

1. Pulse Test: Pulse Width=300 μs , Duty Cycle $\leq 2\%$.
2. These Parameters Have No Way To Verify.

Curve Characteristics (N-Channel)

Fig. 1 - Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - $R_{DS(ON)} - I_D$




Fig. 4 - Normalized On Resistance Characteristics




Fig. 5 - Gate Charge





Fig. 6 - Capacitance Characteristics



Curve Characteristics (P-Channel)

Fig. 7 - Output Characteristics




Fig. 8 - Transfer Characteristics




Fig. 9 - $R_{DS(ON)} - I_D$




Fig. 10 - Normalized On Resistance Characteristics




Fig. 11 - Gate Charge





Fig. 12 - Capacitance Characteristics



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" Suffix for Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MCC\(美微科\)](#)