

## Features

- Guard Ring Protection
- Low Forward Voltage Drop
- Low Power Loss For High Efficiency
- Reverse Energy Tested
- Lead Free Finish/RoHS Compliant(Note 1)("P" Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating

# 2.0 Amp Schottky Barrier Rectifier 20 to 60 Volts

## **Maximum Ratings**

- Operating Junction Temperature Range: -50°C to +125°C
- Storage Temperature Range: -50°C to +125°C
- Maximum Thermal Resistance: 30°C/W Junction to Lead


MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
SR202	SR202	20V	14V	20V
SR203	SR203	30V	21V	30V
SR204	SR204	40V	28V	40V
SR206	SR206	60V	42V	60V

### Electrical Characteristics @ 25°C Unless Otherwise Specified

I <sub>F(AV)</sub>	2.0A	T <sub>L</sub> = 90°C
I <sub>FSM</sub>	50A	8.3ms,Half Sine
V <sub>FM</sub>	0.55V 0.70V	I <sub>FM</sub> =2.0A; T <sub>J</sub> =25°C*
I <sub>RM</sub>	0.1mA 10mA	V <sub>RRM</sub> , T <sub>J</sub> =25°C; T <sub>J</sub> =100°C
CJ	50pF	V <sub>R</sub> =5.0V,T <sub>J</sub> =25°C
	I <sub>FSM</sub> V <sub>FM</sub>	I <sub>FSM</sub> 50A   V <sub>FM</sub> 0.55V   0.70V   I <sub>RM</sub> 0.1mA   10mA

\*Pulse test: Pulse width 300  $\mu sec,$  Duty cycle 2%

Note : 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7a.



0.90

\_\_\_\_\_

0.71

25.40

Φ

С

D


0.028 0.035


-----

1.000



# **Curve Characteristics**









Fig. 6 - Typical Reverse Leakage Characteristics



Percent of Rated Peak Reverse Voltage (%)



# **Ordering Information**

Device	Packing	
(Part Number)-TP	Tape&Reel: 5Kpcs/Reel	
(Part Number)-AP	Ammo Packing: 5Kpcs/Ammo Box	
(Part Number)-BP	Bulk:1Kpcs/Box,50Kpcs/Carton	

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp*. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)