

Features

- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free Available Upon Request By Adding Suffix "-HF"

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Typical Thermal Resistance: 2.5°C/W Junction to Case

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MUR810F	MUR810F	100V	70V	100V
MUR820F	MUR820F	200V	140V	200V
MUR840F	MUR840F	400V	280V	400V
MUR860F	MUR860F	600V	420V	600V


Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	I _{F(AV)}	8.0A	T _C =100°C
Peak Forward Surge Current	I _{FSM}	125A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage MUR810F-MUR820F MUR840F MUR860F	V _F	0.975V 1.3V 1.5V	I _{FM} =8A TJ=25⁰C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	5.0μA 500μA	TJ=25ºC; TJ=125ºC
Maximum Reverse Recovery Time MUR810F-MUR820F MUR840F-MUR860F	t _{rr}	35ns 50ns	I _F =0.5A; I _R =1.0A; I _{RR} =0.25A

Note :1. High Temperature Solder Exemption Applied, See EU Directive Annex 7a.

Internal Structure

PIN 1 O-








DIMENSIONS						
DIM	INCHES		MM		NOTE	
	MIN	MAX	MIN	MAX	NOTE	
Α	0.567	0.606	14.40	15.40		
В		0.406		10.30		
С	0.100	0.112	2.55	2.85		
D	0.248	0.272	6.30	6.90		
Е		0.161		4.10		
F	0.500	0.543	12.70	13.80		
G	0.2	00	5.′	10		
Н		0.035		0.90		
Ι		0.032		0.80		
J	0.102	0.134	2.60	3.40	Φ	
Κ		0.189		4.80		
L		0.123		3.10		
Μ	0.098	0.114	2.50	2.90		





Curve Characteristics
















Ordering Information

Device	Packing	
Part Number-BP	Bulk:50pcs/Tube,1Kpcs/Box,5Kpcs/Carton	

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp*. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价,库存,交付和生命周期等信息

>>MCC(美微科)