


## Features

- Lead Free Finish/RoHS Compliant (NOTE 1)("P" Suffix designates RoHS Compliant. See ordering information)
- International standard package
- Heat transfer through aluminum oxide DBC ceramic isolated metal baseplate
- Glass passivated chip
- Simple Mounting

## Applications


- Power Converters
- Lighting Control
- DC Motor Control and Drives
- Heat and temperature control

MCC Part Number	$V_{RRM}$	$V_{RSM}$
MT200C08T2	800V	900V
MT200C12T2	1200V	1300V
MT200C16T2	1600V	1700V
MT200C18T2	1800V	1900V



Note:1. High Temperature Solder Exemptions Applied, See EU Directive Annex 7a.

# 200 Amp THYRISTOR MODULE 800~1800 Volts



### Maximum Ratings


Symbol	Conditions	Values	Units
$I_{TAV}$	Sine 180°; $T_c=85^\circ\text{C}$	200	A
$I_{TSM}$	$T_{VJ}=45^\circ\text{C}$ $t=10\text{ms}$ , sine $T_{VJ}=125^\circ\text{C}$ $t=10\text{ms}$ , sine	5500 5000	A
$i^2t$	$T_{VJ}=45^\circ\text{C}$ $t=10\text{ms}$ , sine $T_{VJ}=125^\circ\text{C}$ $t=10\text{ms}$ , sine	151000 125000	A <sup>2</sup> s
Visol	a.c.50HZ;r.m.s.;1min	3000	V
$T_{vj}$		-40 to 130	°C
$T_{stg}$		-40 to 125	°C
$M_t$	To terminals(M6)	$3 \pm 15\%$	Nm
$M_s$	To heatsink(M6)	$5 \pm 15\%$	Nm
$di/dt$	$T_{VJ}=T_{VJM}$ , $2/3V_{DRM}$ , $I_G=500\text{mA}$ $Tr<0.5\mu\text{s}$ , $tp>6\mu\text{s}$	200	A/us
$dv/dt$	$T_J=T_{VJM}$ , $2/3V_{DRM}$ , linear voltage rise	1000	V/us
a	Maximum allowable acceleration	50	m/s <sup>2</sup>
Weight	Module(Approximately)	165	g

### Thermal Characteristics


Symbol	Conditions	Values	Units
$R_{th(j-c)}$	Cont.; thyristor / per module	0.16/0.08	°C/W
$R_{th(c-s)}$	per thyristor / per module	0.1/0.05	°C/W

Symbol	Conditions	Values			Units
$V_{TM}$	$T=25^\circ\text{C}$ $I_{TM}=620\text{A}$			1.7	V
$I_{RRM}/I_{DRM}$	$T_{VJ}=T_{VJM}$ , $V_R=V_{RRM}$ , $V_D=V_{DRM}$			40	mA
$V_{TO}$	For power-loss calculations only ( $T_{VJ}=125^\circ\text{C}$ )			0.85	V
$r_T$	$T_{VJ}=T_{VJM}$			1.5	mΩ
$V_{GT}$	$T_{VJ}=25^\circ\text{C}$ , $V_D=6\text{V}$			3	V
$I_{GT}$	$T_{VJ}=25^\circ\text{C}$ , $V_D=6\text{V}$			200	mA
$V_{GD}$	$T_{VJ}=125^\circ\text{C}$ , $V_D=2/3V_{DRM}$			0.25	V
$I_{GD}$	$T_{VJ}=125^\circ\text{C}$ , $V_D=2/3V_{DRM}$			10	mA
$I_L$	$T_{VJ}=25^\circ\text{C}$ , $R_G=33\ \Omega$	300	1000		mA
$I_H$	$T_{VJ}=25^\circ\text{C}$ , $V_D=6\text{V}$	150	400		mA
tgd	$T_{VJ}=25^\circ\text{C}$ , $I_G=1\text{A}$ , $di_G/dt=1\text{A/us}$	1			us
tq	$v_J=T_{VJM}$	100			us


**Performance Curves**




**Fig1. Power dissipation**



**Fig2. Forward Current Derating Curve**




**Fig3. Transient thermal impedance**




**Fig4. Max Non-Repetitive Forward Surge Current**

**Performance Curves**



**Fig5. Forward Characteristics**



**Fig6. Gate trigger Characteristics**

## Ordering Information

Device	Packing
Part Number-BP	Bulk: 8PCS/BOX ;80PCS/CTN

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MCC\(美微科\)](#)