

Features

- High Current Rating
- Lower $R_{DS(ON)}$
- Lower Capacitance
- Lower Total Gate Charge
- Tighter V_{SD} Specifications
- Avalanche Energy Specified
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free. "Green" Device (Note 1)
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings


- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 40°C/W Junction to Ambient
- Thermal Resistance: 0.6°C/W Junction to Case

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	85	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D	$T_C=25^\circ\text{C}$	118
		$T_C=100^\circ\text{C}$	74
Pulsed Drain Current	I_{DM}	472	A
Single Pulse Avalanche Energy (Note2)	E_{AS}	351	mJ
Total Power Dissipation	P_D	200	W

1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.


2. $L=0.5\text{mH}$, $I_{AS}=37.5\text{A}$, $V_{DD}=50\text{V}$, $V_{GS}=10\text{V}$, $R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$

Internal Structure and Marking Code



N-CHANNEL MOSFET

TO-220AB(H)



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	0.172	0.188	4.37	4.77	
B	0.049	0.057	1.25	1.45	
C	0.246	0.270	6.25	6.85	
D	0.594	0.634	15.10	16.10	
E	0.382	0.406	9.70	10.30	
F	0.346	0.370	8.80	9.40	
G	0.102	0.118	2.60	3.00	
H	0.087	0.102	2.20	2.60	
J	----	0.134	----	3.40	
K	0.046	0.058	1.17	1.47	
L	0.028	0.037	0.70	0.95	
M	0.200		5.08		TYP.
N	0.100		2.54		TYP.
O	0.502	0.543	12.75	13.80	
P	0.134	0.150	3.40	3.80	Φ
Q	0.016	0.026	0.40	0.65	
R	0.276	----	7.00	----	
S	0.217	----	5.50	----	

ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	85			V
Gate-Threshold Voltage ^(Note3)	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0	3.0	4.0	V
Gate-Body Leakage Current ^(Note3)	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 85V, V_{GS} = 0V$			1	μA
Drain-Source On-Resistance ^(Note3)	$R_{DS(on)}$	$V_{GS}=10V, I_D=59A$		5	6.5	m Ω
		$V_{GS}=6V, I_D=20A$		7.5	10	
Gate resistance	R_G	f=1MHz, Open drain		1.6		Ω
Drain- Source Diode Forward Voltage ^(Note3)	V_{SD}	$V_{GS} = 0V, I_S = 59A$		0.9	1.2	V
Dynamic Characteristics						
Input Capacitance ^(Note4)	C_{iss}	$V_{DS}=40V, V_{GS}=0V, f=1MHz$		4300		pF
Output Capacitance ^(Note4)	C_{oss}			900		
Reverse Transfer Capacitance ^(Note4)	C_{riss}			250		
Switching Characteristics						
Total Gate Charge	Q_g	$V_{DS}=40V, V_{GS}=10V, I_D=59A$		62		nC
Gate-Source Charge	Q_{gs}			20		
Gate-Drain Charge	Q_{gd}			17		
Reverse Recovery Time	t_{rr}	$I_F=59A, di/dt=870A/\mu s$		26		ns
Reverse Recovery Charge	Q_{rr}			157		nC
Turn-on Delay Time ^(Note4)	$t_{d(on)}$	$V_{DD}=40V, V_{GS}=10V, R_G=2.2\Omega, I_D=59A$		18		ns
Turn-on Rise Time ^(Note4)	t_r			86		
Turn-off Delay Time ^(Note4)	$t_{d(off)}$			30		
Turn-off Fall Time ^(Note4)	t_f			9		

Note: 3. Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$
 4. These Parameters Have No Way to Verify

Curve Characteristics

Fig. 1 - Typical Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - $R_{DS(ON)} - I_D$




Fig. 4 - $R_{DS(ON)} - V_{GS}$




Fig. 5 - $I_S - V_{SD}$





Fig. 6 - Gate Charge



Curve Characteristics

Fig. 7 - Normalized On Resistance Characteristics




Fig. 8 - Capacitance Characteristics




Fig. 9 - Powe Dissipation




Fig. 10 - Safe Operation Area





Fig. 11 - Maximum Transient Thermal Impedance



Ordering Information

Device	Packing
Part Number-BP	Bulk:50pcs/Tube, 1Kpcs/Box, 5Kpcs/Carton

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MCC\(美微科\)](#)