




苏州敏芯微电子技术股份有限公司
MEMSensing Microsystems (Suzhou, China) Co., Ltd.

Data Sheet

V 1.0 / Jun. 2018

MSM381A3729H9BP

Analog output MEMS microphone



MSM381A3729H9BP

Analog output MEMS microphone



苏州敏芯微电子技术股份有限公司
MEMSensing Microsystems (Suzhou, China) Co., Ltd.



GENERAL DESCRIPTION

MSM381A3729H9BP is an omnidirectional, Top-ported, analog output MEMS microphone. It has high performance and reliability. It is with excellent RF immunity performance.

MSM381A3729H9BP is available in a thin 3.76 mm × 2.95 mm × 1.1 mm proprietary OCLGA package. It is SMT compatible with no sensitivity degradation.


APPLICATIONS

- ✧ Sound Box
- ✧ Laptop
- ✧ Tablet computer
- ✧ Bluetooth headset
- ✧ Earphone
- ✧ Wearable intelligent equipment

FEATURES

- ✧ Low Noise
- ✧ Omnidirectional
- ✧ Excellent RF immunity
- ✧ Standard SMD Reflow
- ✧ Compatible with Sn/Pb and Pb-free solder processes
- ✧ RoHS/Halogen free compliant
- ✧ Sensitivity Matching within +/-1dB

PRODUCT VIEW



MSM381A3729H9BP

Analog output MEMS microphone



苏州敏芯微电子技术股份有限公司
MEMSensing Microsystems (Suzhou, China) Co., Ltd.



ABSOLUTE MAXIMUM RATINGS

| Parameter | Maximum value | Unit |
|----------------------|---------------|--------|
| Supply Voltage | -0.3 to 4.0 | V |
| Sound Pressure Level | 140 | dB SPL |
| Storage temperature | -40 to 100 | °C |

Stresses exceeding these “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only. Functional operation at these or any other conditions beyond those indicated under “Acoustic & Electrical Specifications” is not implied. Exposure beyond those indicated under “Acoustic & Electrical Specifications” for extended periods may affect device reliability.


ACOUSTIC & ELECTRICAL SPECIFICATIONS

All data taken at 25°C, Relative Humidity 45±5% unless otherwise specified

| | Limits | | | unit | condition |
|--|---|------|------|--------|--|
| | Min. | Nom. | Max. | | |
| Directivity | Omni directional | | | | |
| Sensitivity | -39 | -38 | -37 | dB | @1kHz ref 1V/Pa |
| Operation voltage | 1.5 | - | 3.6 | V | |
| Freq. range | Refer to the frequency response graphic | | | Hz | Refer to sensitivity@1kHz |
| Sensitivity loss across supply voltage | No change across the voltage range | | | dB | |
| Signal to noise ratio | - | 64 | - | dB | 20 kHz bandwidth, A-weighted |
| THD | - | 0.15 | - | % | 94dB SPL @1kHz S =Nom, Rload > 2 k |
| AOP | - | 123 | - | dB SPL | 10% THD @1kHz S =Nom, Rload > 2 k |
| Polarity | Increasing output voltage | | | | Increasing sound pressure |
| Out impedance | - | 200 | - | Ω | @1kHz |
| DC Output | | 0.7 | | V | |
| PSRR | - | 70 | - | dB | 200mVpp sine wave @ 1 kHz, VDD = 1.8V |
| PSR | - | -100 | - | dBV(A) | 100 mVpp square wave@ 217 Hz, VDD = 1.8V, A-weighted |
| Current consumption | - | 150 | 170 | μA | |




TYPICAL FREQUENCY RESPONSE




SMT Parameters:

1. Recommend PCB land pattern layout: (unit: mm)





2. Recommend reflow profile:



| Description | Parameter | Pb-free |
|--|---------------------|-------------------|
| Average ramp-up rate | T_{smax} to T_P | 3°C/sec max |
| Preheat | | |
| Minimum temperature | T_{SMIN} | 150 °C |
| Maximum temperature | T_{SMAX} | 200 °C |
| Time(T_{SMIN} to T_{SMAX}) | t_s | 60 sec to 180 sec |
| Ramp-up rate | T_{SMAX} to T_L | 1.25 °C/sec |
| Time maintained above liquidus temperature | t_L | 60 sec to 150 sec |
| Liquidus temperature | T_L | 217 °C |
| Peak temperature | T_P | 260 °C |
| Time within 5°C of actual peak temperature | t_p | 20 sec to 40 sec |
| Ramp-down rate | T_P to T_{smax} | 6 °C/sec max |
| Time 25 °C ($t_{25 °C}$) to peak temperature | t | 8 minutes max |

MSM381A3729H9BP

Analog output MEMS microphone





苏州敏芯微电子技术股份有限公司


MEMSensing Microsystems (Suzhou, China) Co., Ltd.




OUTLINE DIMENSIONS AND PIN DEFINITION:



TOP VIEW



SIDE VIEW



BOTTOM VIEW

PIN function description

| PIN# | Function |
|------|----------|
| 1 | VDD |
| 2 | GND |
| 3 | GND |
| 4 | OUT |

| Item | Dimension | Tolerance |
|--------------------|-----------|-----------|
| Length (L) | 3.76 | ±0.10 |
| Width (W) | 2.95 | ±0.10 |
| Height (H) | 1.10 | ±0.10 |
| Acoustic Port (AP) | ∅0.325 | ±0.05 |

Dimensions are in millimeters, tolerance is ±0.15mm unless otherwise specified.

| | | |
|---|---|---------------|
| MYWW X ₁ X ₂ X ₃ X ₄ | M | Memsensing |
| | Y | Year(A~Z) |
| | WW | Week |
| | X ₁ X ₂ X ₃ X ₄ | Serial Number |

MSM381A3729H9BP

Analog output MEMS microphone




苏州敏芯微电子技术股份有限公司

MEMSensing Microsystems (Suzhou, China) Co., Ltd.



RECOMMENDED INTERFACE CIRCUIT:

- Recommended Application Example (differential amplification circuit)



NOTE: It is recommended that the components on the left side of red line be placed close to MIC, and components on the right side of red line be placed close to codec.

MSM381A3729H9BP

Analog output MEMS microphone



苏州敏芯微电子技术股份有限公司
MEMSensing Microsystems (Suzhou, China) Co., Ltd.



ADDITIONAL NOTES

- (A) MSL (moisture sensitivity level) Class 1.
- (B) Maximum of 3 reflow cycles is recommended.
- (C) In order to minimize device damage:
 - Do not board wash or clean after the reflow process.
 - Do not brush board with or without solvents after the reflow process.
 - Do not directly expose to ultrasonic processing, welding, or cleaning.
 - Do not insert any object in port hole of device at any time.
 - Do not apply air pressure into the port hole.
 - Do not pull a vacuum over port hole of the microphone.

STORAGE AND TRANSPORTATION

- (A) Keep MEMS MIC in warehouse with less than 75% humidity and without sudden temperature change, acid air, any other harmful air or strong magnetic field.
 - Recommend floor life (out of bag) at factory no more than 4 weeks.
- (B) The MEMS MIC with normal pack can be transported by ordinary conveyances. Please protect products against moist, shock, sunburn and pressure during transportation.

MATERIALS STATEMENT

Meets the requirements of the European RoHS and Halogen-Free.

MSM381A3729H9BP

Analog output MEMS microphone








苏州敏芯微电子技术股份有限公司

MEMSensing Microsystems (Suzhou, China) Co., Ltd.



PACKAGING & MARKING DETAIL:



| | | | | | |
|---------|------------|------------|-----------|------------------------------------|-----------|
| ITEM | W | E | F | ØD0 | K0 |
| DIM(mm) | 12.00±0.30 | 1.75±0.10 | 5.50±0.10 | 1.50 ^{+0.10} ₀ | 1.30±0.10 |
| ITEM | P0 | 10P0 | P1 | A0 | B0 |
| DIM(mm) | 4.00±0.10 | 40.00±0.20 | 8.00±0.10 | 4.06±0.05 | 3.30±0.10 |
| ITEM | P2 | T | | | |
| DIM(mm) | 2.00±0.10 | 0.25±0.05 | | | |

Note:

- 1) Dimensions are in mm;
- 2) Don't put the vacuum suction nozzle alignment the port hole;
- 3) Tape & Reel Per EIA-481 standard;
- 4) Label applied to external package and direct to reel;
- 5) Static voltage <100V;

| Model Number | Reel Diameter | Quantity Per Reel |
|-----------------|---------------|-------------------|
| MSM381A3729H9BP | 13 inch | 5700 |



RELIABILITY SPECIFICATIONS

| Test | Description |
|---------------------------|--|
| Thermal Shock | 100 cycles air-to-air thermal shock from -40°C to +125°C with 15 minute soaks. |
| High Temperature Storage | 1,000 hours at +105°C environment |
| Low Temperature Storage | 1,000 hours at -40°C environment |
| Reflow | 5 reflow cycles with peak temperature of +260°C |
| ESD-HBM | 3 discharges of ±2 kV direct contact to I/O pins. |
| ESD- LID-GND | 3 discharges of ±8 kV direct contact to lid while unit is grounded. |
| ESD-MM | 3 discharges of ±200V direct contact to I/O pins. |
| Vibration | 4 cycles of 20 to 2,000 Hz sinusoidal sweep with 20 G peak acceleration lasting 12 minutes in X, Y and Z directions. |
| Mechanical Shock | 3 pulses of 10,000 G in the X, Y and Z direction |
| High Temperature Bias | 1,000 hours at +105°C under bias |
| Low Temperature Bias | 1,000 hours at -40°C under bias |
| Temperature/Humidity Bias | 1,000 hours at +85°C/85% R.H. under bias. |
| Drop Test | To be no interference in operation after dropped to 1.0cm steel plate 18 times from 1.5 meter height |

NOTE: Sensitivity should vary within ±3dB from initial sensitivity. (The measurement to be done after 2 hours of conditioning at 20±2 °C, R.H 60%~70%)

MSM381A3729H9BP

Analog output MEMS microphone



苏州敏芯微电子技术股份有限公司

MEMSensing Microsystems (Suzhou, China) Co., Ltd.



REVISION HISTORY:

| Revision | Subjects (major changes since last revision) | Date |
|----------|--|------------|
| 1.0 | Initial Release | 2018-06-19 |

公司销售、技术支持联系方式

(<http://www.memsensing.com>)

For English:

MEMSensing Microsystems(Suzhou,China)
Co. Ltd.

No. 99 Jinji Lake Avenue, Bldg. NW-09, Suite 501
Suzhou Industrial Park, China 215123

Phone: +86 512 62956055

Fax: +86 512 62956056

中文用户:

苏州敏芯微电子技术股份有限公司

苏州工业园区金鸡湖大道 99 号, NW-09 楼, 501 室
中国 215123

电话: +86 512 62956055

传真: +86 512 62956056

Disclaimer: specifications and characteristics are subject to change without notice. MEMSensing Microsystems Co. Ltd. assumes no liability to any customer, licensee or any third party for any damages or any kind of nature whatsoever related to using this technical data.

单击下面可查看定价，库存，交付和生命周期等信息

[>>MEMSensing\(敏芯微\)](#)