



Part Number : [529010474](#)

Product Description : SlimStack Board-to-Board Connector, 0.635mm Pitch, 0.635 Series, Receptacle, 12.00 to 16.00mm Mated Height, 6.40mm Mated Width, 40 Circuits

Series Number : 52901

Status : Active

Product Category : Board-to-Board Connectors

Documents & Resources

Drawings

[Drawing 529010474_sd.pdf](#)

3D Models and Design Files

[3D Model 529010474_stp.zip](#)


Specifications

[Packaging Specification SPK-52901-001-001.pdf](#)

[Product Specification 527600000-000.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Compliant with Exemption 44; 33 |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|---|
| Status | Active |
| Category | Board-to-Board Connectors |
| Series | 52901 |
| Description | SlimStack Board-to-Board Connector, 0.635mm Pitch, 0.635 Series, Receptacle, 12.00 to 16.00mm Mated Height, 6.40mm Mated Width, 40 Circuits |
| Series Name | 0.635, Rigid |
| Application | Board-to-Board, Signal |
| Comments | Stacking-Type |
| Component Type | PCB Receptacle |
| Product Family | SlimStack Board-to-Board/Board-to-FPC Connectors |
| Product Name | SlimStack |
| UPC | 822348176526 |

Agency

| | |
|----|--------|
| UL | E29179 |
|----|--------|

Electrical

| | |
|-------------------------------|------|
| Current - Maximum per Contact | 0.5A |
| Voltage - Maximum | 100V |

Physical

| | |
|--------------------------------|-------|
| Circuits (Loaded) | 40 |
| Circuits (maximum) | 40 |
| Color - Resin | White |
| Durability (mating cycles max) | 50 |
| Flammability | 94V-0 |
| Glow-Wire Capable | No |

| | |
|--------------------------------|---|
| Lock to Mating Part | Yes |
| Mated Height | 12.00mm, 13.00mm, 14.00mm, 15.00mm, 16.00mm |
| Mated Width | 6.40mm |
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 1137.663/mg |
| Number of Rows | 2 |
| Orientation | Vertical |
| Packaging Type | Embossed Tape on Reel |
| PCB Locator | Yes |
| PCB Retention | Yes |
| PCB Thickness - Recommended | 1.60mm |
| Pitch - Mating Interface | 0.635mm |
| Polarized to PCB | Yes |
| Robotic Placement | Pick and Place Cap |
| Temperature Range - Operating | -55° to +105°C |
| Termination Interface Style | Surface Mount |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|--|--------------|
| 0.635mm Pitch Vertical SlimStack Plugs | <u>53625</u> |
| 0.635mm Pitch Vertical SlimStack Plugs | <u>53627</u> |
| 0.635mm Pitch Vertical SlimStack Plugs | <u>53647</u> |
| 0.635mm Pitch Vertical SlimStack Plugs | <u>53649</u> |
| 0.635mm Vertical SlimStack Plugs | <u>55091</u> |

单击下面可查看定价，库存，交付和生命周期等信息

[>>MOLEX](#)