



- NOTES:
- MATERIALS:
HOUSING: POLYESTER (PBT), GLASS FILLED, UL94 V-0,
COLOR: BLACK
TERMINALS: COPPER ALLOY
 - FINISHES: 1. TIN ONLY: 100MIN TIN OVER 50MIN NICKEL
2. TIN/GOLD: 30MIN SELECT GOLD (CONTACT MATING AREA),
100MIN SELECT TIN (PCB TAIL AREA) OVER 50MIN NICKEL OVERALL.
 - PRODUCT SPECIFICATION: PS-19427-001.
 - PACKAGING SPECIFICATION: PK-19427-001.
 - MATES WITH: 19418 SERIES RECEPTACLE ASSEMBLIES.
 - RECOMMENDED MOUNTING HARDWARE: (2) #10 X .62/18.9 LONG PLASTIC
THREAD CUTTING SCREWS. RECOMMENDED TORQUE 15-17 IN.-LBS.
SUGGESTED SOURCE: ITW SHAKEPROOF INDUSTRIAL BOSSCREW OR EQUIVALENT.

REVISED REV	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	TERMINAL PLATING	
			mm	INCH	IN/MM	DATE	TITLE	INCH	INCH	INCH
4 PLACES	± .015	± .015	± .015	± .015	DRAWN BY	BRUPERT	04/07/28	8 WAY RIGHT ANGLE HEADER ASSEMBLY		
3 PLACES	± .015	± .015	± .015	CHECKED BY	JPAWLICK	04/07/28				
2 PLACES	± .038	± .038	± .038	APPROVED BY	RDEROSS	04/07/28				
1 PLACE	± .038	± .038	± .038	MATERIAL NO.	SD-19427-022	DOCUMENT NO.	SD-19427-022			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SEE CHART			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

单击下面可查看定价，库存，交付和生命周期等信息

[>>MOLEX](#)