

Part Number : [477450100](#)

Product Description : 2.50mm, 3.50mm CMC Header, Right-Angle, 28 Position, 1 Port, Black, Peg, Lead-Free

Series Number : 47745

Status : Active

Product Category : PCB Headers and Receptacles

Documents & Resources

Drawings

[Drawing 477450100_sd.pdf](#)


[Packaging Design Drawing PK-47745-001-001.pdf](#)

3D Models and Design Files

[3D Model 477450100_stp.zip](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Duty-To-Declare
China RoHS	
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	47745
Description	2.50mm, 3.50mm CMC Header, Right-Angle, 28 Position, 1 Port, Black, Peg, Lead-Free
Application	Automotive, Power, Wire-to-Board
Comments	Coding: Black
Component Type	PCB Header
Product Family	CMC and CMX Sealed, Hybrid, Modular Connectors
Product Name	CMC
UPC	887191161006

Electrical

Current - Maximum per Contact	12.0A, 2.5A, 21.0A
Voltage - Maximum	14V DC

Physical

Breakaway	No
Circuits Detail	5x 2.8mm, 5 x 1.5mm, 18 x 0.635mm terminals
Circuits (Loaded)	28
Circuits (maximum)	28
Color - Resin	Black
Durability (mating cycles max)	20
First Mate / Last Break	Yes
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin

Material - Resin	Polyester
Net Weight	36.292/g
Number of Rows	3
Orientation	Right Angle
Packaging Type	Carton
PC Tail Length	2.90mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	2.50mm, 3.50mm, 3.70mm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Closed Ends
Stackable	No
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Solder or Weld

Solder Process Data

Max-Duration	10
Lead-Free Process Capability	WAVE
Max-Cycle	1
Max-Temp	260

Mates With / Use With

Mates with Part(s)

Description	Part Number
Power CMC Receptacles	<u>64318</u>

Use with Part(s)

Description	Part Number
CMC Wire Cap for 48 Circuits and 28 Circuits, CMC Receptacle Mat Sealed	/content/molex/molex-dot-com/us/en/products/product-page.html/643201301.html
Power CMC Receptacles	<u>64318</u>

CMC CP Female Terminals	<u>64322</u>
1.50mm CMC CP Female Terminals	<u>64323</u>
2.80mm CMC CP Female Terminals	<u>64324</u>
CMC Blind Cavity Plugs and Single Wire Seals	<u>64325</u>

This document was generated on May 07, 2024

单击下面可查看定价，库存，交付和生命周期等信息

[>>MOLEX](#)