Please download the latest datasheet of NTPAA100LDNB0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NTPAA100LDNB0

Note: This datasheet may be out of date.

# NTPAA100LDNB0










## Appearance & Shape





(in mm)



#### **Features**

- 1. Lead is not contained in the ceramic element, the terminations, the solder for inner connection and the coating resin.
- 2. Most suitable for power supplies of less than 100W
- 3. Excellent recovery characteristics due to resin coating with excellent heat characteristics



## **Applications**

Limited Usage	Consumer Grade		
Other Usage	Switching power supplies, CRT		
	monitors, Color televisions, VCR-Power		
	supplies, Other power circuits		



## Packaging Information

	Packaging		Standard
			Packing
			Quantity
	В0	Bulk(Bag)	300

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL : https://www.murata.com/



# NTPAA100LDNB0

Note: This datasheet may be out of date.

 $\label{thm:please} Please \ download \ the \ latest \ data sheet \ of \ NTPAA100LDNB0 \ from \ the \ official \ website \ of \ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NTPAA100LDNB0



# **Specifications**

Resistance (25°C)	10Ω	
Resistance Value Tolerance	±15%	
(at 25°C)		
Permissible Max. Current	1.7A	
(25°C)	1.78	
Permissible Max. Current	1.5A	
(55°C)		
Thermal Time Constant	70s	
Typical Dissipation Constant	13.5mW/°C	
(25°C)	13.511100/ C	
Permissible Electrolytic	1400µF	
Capacitor	Ι4ουμι	
Measure Condition of		
Permissible Electrolytic	at 100V	
Capacitor		
Operating Temperature	-20°C to 160°C	
Range	-20 € 10 100 €	
Lead Shape	Lead Wire type	
Shape	Lead	
Mass	1.1g	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL: https://www.murata.com/


Note: This datasheet may be out of date.


Please download the latest datasheet of NTPAA100LDNB0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NTPAA100LDNB0


# NTPAA100LDNB0







#### Permissible Maximum Current Derating Curve



### Permissible Electrolytic Capacitor

Current-R ratio(Rt/R25), Current-Temperature Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



URL: https://www.murata.com/

# 单击下面可查看定价,库存,交付和生命周期等信息

>>Murata(村田)