

# PESDxUSB3S series

## ESD protection for differential data lines

Rev. 4 — 30 January 2019

Product data sheet

## 1. Product profile

### 1.1. General description

The devices are ElectroStatic Discharge (ESD) protection for one, two and three differential channels.

The devices are footprint compatible to PCMFxUSB3S common mode filters with ESD protection.

Diodes provide protection to downstream components from ESD voltages up to  $\pm 15$  kV on each signal line.

**Table 1. Product overview**

| Type number | Number of channels | Package Name |
|-------------|--------------------|--------------|
| PESD1USB3S  | 1                  | WLCSP5       |
| PESD2USB3S  | 2                  | WLCSP10      |
| PESD3USB3S  | 3                  | WLCSP15      |

### 1.2. Features and benefits

- Allows switching between PCMFxUSB3S common mode filters with ESD protection and PESDxUSB3S ESD protection in the same footprint
- TrEOS protection process for very high system-level ESD robustness: superior protection of sensitive Systems on Chips (SoCs)
- ESD protection for one, two and three differential channels up to  $\pm 15$  kV contact discharge according to IEC 61000-4-2
- Industry-standard WLCSP5, 10 and 15 packages for smallest footprint







### 1.3. Applications

- Smartphone, cellular and cordless phone
- USB3.1, USB2.0, HDMI2.0, HDMI1.4
- General-purpose downstream ESD protection for differential data lines
- Tablet PC and Mobile Internet Device (MID)
- MIPI D-PHY as used in Camera Serial Interface (CSI) and Display Serial Interface (DSI)

nexperia

## 2. Pinning information

Table 2. Pinning

| Pin                        | Symbol   | Description          | Simplified outline                                                                                                                       | Graphic symbol                                                                                                                                 |
|----------------------------|----------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| PESD1USB3S (WLCSP5_2-1-2)  |          |                      |                                                                                                                                          |                                                                                                                                                |
| A1                         | CH1_IN+  | channel 1+, external |  <p>Transparent top view<br/><b>WLCSP5_2-1-2</b></p>    |  <p>aaa-021381</p>                                          |
| A2                         | CH1_IN-  | channel 1-, external |                                                                                                                                          |                                                                                                                                                |
| B1                         | GND_CH1  | ground channel 1     |                                                                                                                                          |                                                                                                                                                |
| C1                         | CH1_OUT+ | channel 1+, internal |                                                                                                                                          |                                                                                                                                                |
| C2                         | CH1_OUT- | channel 1-, internal |                                                                                                                                          |                                                                                                                                                |
| PESD2USB3S (WLCSP10_4-2-4) |          |                      |                                                                                                                                          |                                                                                                                                                |
| A1                         | CH1_IN+  | channel 1+, external |  <p>Transparent top view<br/><b>WLCSP10_4-2-4</b></p>  |  <p>B1, B2 - no internal connection<br/>aaa-021384</p>       |
| A2                         | CH1_IN-  | channel 1-, external |                                                                                                                                          |                                                                                                                                                |
| A3                         | CH2_IN+  | channel 2+, external |                                                                                                                                          |                                                                                                                                                |
| A4                         | CH2_IN-  | channel 2-, external |                                                                                                                                          |                                                                                                                                                |
| B1                         | GND_CH1  | ground channel 1     |                                                                                                                                          |                                                                                                                                                |
| B2                         | GND_CH2  | ground channel 2     |                                                                                                                                          |                                                                                                                                                |
| C1                         | CH1_OUT+ | channel 1+, internal |                                                                                                                                          |                                                                                                                                                |
| C2                         | CH1_OUT- | channel 1-, internal |                                                                                                                                          |                                                                                                                                                |
| C3                         | CH2_OUT+ | channel 2+, internal |  <p>Transparent top view<br/><b>WLCSP15_6-3-6</b></p> |  <p>B1, B2, B3 - no internal connection<br/>aaa-021385</p> |
| C4                         | CH2_OUT- | channel 2-, internal |                                                                                                                                          |                                                                                                                                                |
| C5                         | CH3_OUT+ | channel 3+, internal |                                                                                                                                          |                                                                                                                                                |
| C6                         | CH3_OUT- | channel 3-, internal |                                                                                                                                          |                                                                                                                                                |

### 3. Ordering information

**Table 3. Ordering information**

| Type number | Package |                                                 |
|-------------|---------|-------------------------------------------------|
|             | Name    | Description                                     |
| PESD1USB3S  | WLCSP5  | wafer level chip-size package; 5 bumps (2-1-2)  |
| PESD2USB3S  | WLCSP10 | wafer level chip-size package; 10 bumps (4-2-4) |
| PESD3USB3S  | WLCSP15 | wafer level chip-size package; 15 bumps (6-3-6) |

### 4. Marking

**Table 4. Marking codes**

| Type number | Marking code |
|-------------|--------------|
| PESD1USB3S  | PD1S         |
| PESD2USB3S  | PD2S         |
| PESD3USB3S  | PD3S         |

### 5. Limiting values

**Table 5. Limiting values**

*In accordance with the Absolute Maximum Rating System (IEC 60134).*

| Symbol    | Parameter                       | Conditions                                        | Min  | Max  | Unit |
|-----------|---------------------------------|---------------------------------------------------|------|------|------|
| $V_I$     | input voltage                   |                                                   | -0.5 | 5    | V    |
| $V_{ESD}$ | electrostatic discharge voltage | IEC 61000-4-2, level 4; all input pins to ground  |      |      |      |
|           |                                 | • contact discharge                               | -15  | 15   | kV   |
|           |                                 | • air discharge                                   | -15  | 15   | kV   |
|           |                                 | IEC 61000-4-2, level 4; all output pins to ground |      |      |      |
|           |                                 | • contact discharge                               | -2   | 2    | kV   |
|           |                                 | • air discharge                                   | -2   | 2    | kV   |
| $I_{PPM}$ | rated peak-pulse current        | $t_p = 8/20 \mu s$                                | -8   | 8    | A    |
| $T_{stg}$ | storage temperature             |                                                   | -40  | +125 | °C   |
| $T_{amb}$ | ambient temperature             |                                                   | -40  | +125 | °C   |

6. Characteristics

6.1. Channel characteristics

Table 6. Channel characteristics

T<sub>amb</sub> = 25 °C unless otherwise specified.

| Symbol           | Parameter               | Conditions                        |     | Min | Typ  | Max | Unit |
|------------------|-------------------------|-----------------------------------|-----|-----|------|-----|------|
| C <sub>d</sub>   | diode capacitance       | f = 1 MHz; V <sub>I</sub> = 2.5 V | [1] | -   | 0.45 | -   | pF   |
| I <sub>RM</sub>  | reverse leakage current | per line; V <sub>I</sub> = 5 V    |     | -   | 1    | 100 | nA   |
| V <sub>BR</sub>  | breakdown voltage       | I <sub>R</sub> = 1 mA             |     | 6   | 9    | -   | V    |
| V <sub>F</sub>   | forward voltage         | I <sub>F</sub> = 10 mA            |     | -   | 0.8  | -   | V    |
| R <sub>dyn</sub> | dynamic resistance      | TLP                               | [2] |     |      |     |      |
|                  |                         | • positive transient              |     | -   | 0.16 | -   | Ω    |
|                  |                         | • negative transient              |     | -   | 0.16 | -   | Ω    |
|                  |                         | surge                             | [3] |     |      |     |      |
|                  |                         | • positive transient              |     | -   | 0.25 | -   | Ω    |
|                  |                         | • negative transient              |     | -   | 0.25 | -   | Ω    |

[1] This parameter is guaranteed by design.  
[2] 100 ns Transmission Line Pulse (TLP); 50 Ω; pulser at 70 to 90 ns.  
[3] According to IEC 61000-4-5 (8/20 μs).

6.2. Frequency characteristics

Table 7. Frequency characteristics

T<sub>amb</sub> = 25 °C unless otherwise specified.

| Symbol                               | Parameter         | Conditions |     | Min | Typ | Max | Unit |
|--------------------------------------|-------------------|------------|-----|-----|-----|-----|------|
| Differential mode: S <sub>dd21</sub> |                   |            |     |     |     |     |      |
| f <sub>-3dB</sub>                    | cut-off frequency |            | [1] | -   | 17  | -   | GHz  |

[1] Normalized to attenuation at 1 MHz.




Fig. 1. Differential mode insertion loss; typical values







Fig. 2. Differential cross-talk; typical values






Fig. 6. HDMI 2.0 eye diagram TP1, test board with PESD3USB3S; typical values




Fig. 7. HDMI 2.0 eye diagram TP1, test board without device; typical values




Fig. 8. Dynamic resistance with positive clamping; typical values






Fig. 9. Dynamic resistance with negative; typical values



Transmission Line Pulse (TLP) = 5 ns


Fig. 10. Dynamic resistance with positive clamping; typical values



Transmission Line Pulse (TLP) = 5 ns


Fig. 11. Dynamic resistance with negative clamping; typical values

The device uses an advanced clamping structure showing a negative dynamic resistance. This snap-back behavior strongly reduces the clamping voltage to the system behind the ESD protection during an ESD event. Do not connect unlimited DC current sources to the data lines to avoid keeping the ESD protection device in snap-back state after exceeding breakdown voltage (due to an ESD pulse for instance).



IEC61000-4-5;  $t_p = 8/20 \mu s$ ; positive pulse

Fig. 12. Dynamic resistance with positive clamping; typical values



IEC61000-4-5;  $t_p = 8/20 \mu s$ ; negative pulse


Fig. 13. Dynamic resistance with negative clamping; typical values

## 7. Application information

The device is designed to provide high-level ESD protection for differential high-speed data line pairs such as:

- USB 3.2
- HDMI 2.0
- Transition-Minimized Differential Signaling (TMDS)
- DisplayPort
- external Serial Advanced Technology Attachment (eSATA)
- Low Voltage Differential Signaling (LVDS)


When designing the Printed-Circuit Board (PCB), give careful consideration to impedance matching and signal coupling. Do not connect the protected signal lines to unlimited current sources like, for example, a battery.





Since the SuperSpeed TX/RX lines are separated by GND or VBUS from the Hi-Speed lines, PESD1USB3S makes it easy to achieve same signal lengths, straight routing, and optimal positioning for ESD protection directly at the connector.




8. Package outline








9. Soldering





## 10. Revision history

Table 8. Revision history

| Document ID        | Release date                                                                                                                                                                                                                   | Data sheet status  | Change notice | Supersedes         |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------|--------------------|
| PESDXUSB3S_SER v.4 | 20190130                                                                                                                                                                                                                       | Product data sheet | -             | PESDXUSB3S_SER v.3 |
| Modifications:     | <ul style="list-style-type: none"><li>Limiting values: maximum value for <math>T_{amb}</math> updated</li><li>Frequency characteristics: table and Fig 2 + 3: <math>S_{21dd}</math> changed to <math>S_{dd21}</math></li></ul> |                    |               |                    |
| PESDXUSB3S_SER v.3 | 20160426                                                                                                                                                                                                                       | Product data sheet | -             | PESDXUSB3S_SER v.2 |
| PESDXUSB3S_SER v.2 | 20160127                                                                                                                                                                                                                       | Product data sheet | -             | PESDXUSB3S_SER v.1 |
| PESDXUSB3S_SER v.1 | 20151216                                                                                                                                                                                                                       |                    |               |                    |

## 11. Legal information

### Data sheet status

| Document status<br>[1][2]      | Product status [3] | Definition                                                                            |
|--------------------------------|--------------------|---------------------------------------------------------------------------------------|
| Objective [short] data sheet   | Development        | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification      | This document contains data from the preliminary specification.                       |
| Product [short] data sheet     | Production         | This document contains the product specification.                                     |

- [1] Please consult the most recently issued document before initiating or completing a design.
- [2] The term 'short data sheet' is explained in section "Definitions".
- [3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the internet at <https://www.nexperia.com>.

### Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of Nexperia.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use in automotive applications** — This Nexperia product has been qualified for use in automotive applications. Unless otherwise agreed in writing, the product is not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or

equipment, nor in applications where failure or malfunction of an Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Translations** — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

### Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## Contents

|                                   |           |
|-----------------------------------|-----------|
| <b>1. Product profile</b>         | <b>1</b>  |
| 1.1. General description          | 1         |
| 1.2. Features and benefits        | 1         |
| 1.3. Applications                 | 1         |
| <b>2. Pinning information</b>     | <b>2</b>  |
| <b>3. Ordering information</b>    | <b>3</b>  |
| <b>4. Marking</b>                 | <b>3</b>  |
| <b>5. Limiting values</b>         | <b>3</b>  |
| <b>6. Characteristics</b>         | <b>4</b>  |
| 6.1. Channel characteristics      | 4         |
| 6.2. Frequency characteristics    | 4         |
| <b>7. Application information</b> | <b>8</b>  |
| <b>8. Package outline</b>         | <b>9</b>  |
| <b>9. Soldering</b>               | <b>12</b> |
| <b>10. Revision history</b>       | <b>14</b> |
| <b>11. Legal information</b>      | <b>15</b> |

© Nexperia B.V. 2019. All rights reserved

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)

Date of release: 30 January 2019



单击下面可查看定价，库存，交付和生命周期等信息

[>>Nexperia\(安世\)](#)