BAS21SW

High-voltage switching diode

5 January 2023 **Product data sheet**

1. General description

High-voltage switching diode encapsulated in a very small SOT323 (SC-70) Surface-Mounted Device (SMD) plastic package.

2. Features and benefits

- High switching speed: t_{rr} ≤ 50 ns
- Low leakage current
- High reverse voltage V_R ≤ 250 V
- Low capacitance: C_d ≤ 2 pF
- Very small SMD plastic package
- AEC-Q101 qualified

3. Applications

- High-speed switching at high voltage
- High-voltage general-purpose switching
- Voltage clamping
- Reverse polarity protection

4. Quick reference data

Table 1. Quick reference data

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
Per diode							
I_F	forward current		[1]	-	-	225	mA
I_R	reverse current	V_R = 200 V; T_{amb} = 25 °C		-	-	100	nA
V_R	reverse voltage			-	-	250	V
t_{rr}	reverse recovery time	I_F = 10 mA; I_R = 10 mA; R_L = 100 Ω; $I_{R(meas)}$ = 1 mA; T_{amb} = 25 °C		-	-	50	ns

[1] Single diode loaded.

nexperia

Downloaded From Oneyac.com

5. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	A1	anode (diode 1)	 SC-70 (SOT323)	
2	K2	cathode (diode 2)		
3	K1, A2	cathode (diode 1) and anode (diode 2)		

6. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BAS21SW	SC-70	plastic, surface-mounted package; 3 leads; 1.3 mm pitch; 2 mm x 1.25 mm x 0.95 mm body	SOT323

7. Marking

Table 4. Marking codes

Type number	Marking code[1]
BAS21SW	X5%

[1] % = placeholder for manufacturing site code

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2023. All rights reserved

Downloaded From Oneyac.com

8. Limiting values

Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
Per diode						
V_R	reverse voltage			-	250	V
I_F	forward current		[1]	-	225	mA
I_{FSM}	non-repetitive peak forward current	t_p = 1 µs; square wave; $T_{j(init)}$ = 25 °C		-	9	A
		t_p = 100 µs; square wave; $T_{j(init)}$ = 25 °C		-	3	A
		t_p = 10 ms; square wave; $T_{j(init)}$ = 25 °C		-	1.7	A
I_{FRM}	repetitive peak forward current			-	625	mA
Per device						
P_{tot}	total power dissipation	$T_{amb} \leq$ 25 °C	[2]	-	200	mW
T_j	junction temperature			-	150	°C
T_{amb}	ambient temperature			-55	150	°C
T_{stg}	storage temperature			-65	150	°C

[1] Single diode loaded.
[2] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.

9. Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	-	625	K/W
$R_{th(j-sp)}$	thermal resistance from junction to solder point			-	-	300	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

10. Characteristics

Table 7. Characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
Per diode							
V_F	forward voltage	I_F = 100 mA; T_{amb} = 25 °C		-	-	1	V
		I_F = 200 mA; T_{amb} = 25 °C		-	-	1.25	V
I_R	reverse current	V_R = 200 V; T_{amb} = 25 °C		-	-	100	nA
		V_R = 200 V; T_j = 150 °C		-	-	100	µA
C_d	diode capacitance	V_R = 0 V; f = 1 MHz; T_{amb} = 25 °C		-	-	2	pF
t_{rr}	reverse recovery time	I_F = 10 mA; I_R = 10 mA; R_L = 100 Ω; $I_{R(meas)}$ = 1 mA; T_{amb} = 25 °C		-	-	50	ns

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2023. All rights reserved

Downloaded From Oneyac.com



(1) T_{amb} = 150° C
(2) T_{amb} = 85° C
(3) T_{amb} = 25° C
(4) T_{amb} = -40° C

Fig. 1. Forward current as a function of forward voltage; typical values



Based on square wave currents
T_j = 25 °C prior to surge

Fig. 2. Maximum permissible non-repetitive peak forward current as a function of pulse duration



(1) T_{amb} = 150° C
(2) T_{amb} = 85° C
(3) T_{amb} = 25° C
(4) T_{amb} = -40° C

Fig. 3. Reverse current as a function of reverse voltage; typical values



f = 1 MHz
T_j = 25 °C.

Fig. 4. Diode capacitance as a function of reverse voltage; typical values.

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2023. All rights reserved

Downloaded From Oneyac.com



FR4 PCB, standard footprint
(1) Single diode loaded
(2) Double diode loaded

Fig. 5. Forward current as a function of ambient temperature; derating curves

11. Test information



(1) I_R = 1 mA

Fig. 6. Reverse recovery time test circuit and waveforms

Quality information

This product has been qualified in accordance with the Automotive Electronics Council (AEC) standard *Q101 - Stress test qualification for discrete semiconductors*, and is suitable for use in automotive applications.

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2023. All rights reserved

Downloaded From Oneyac.com

12. Package outline



Fig. 7. Package outline SC-70 (SOT323)

13. Soldering



Fig. 8. Reflow soldering footprint for SC-70 (SOT323)



Fig. 9. Wave soldering footprint for SC-70 (SOT323)

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2023. All rights reserved

Downloaded From Oneyac.com

14. Revision history

Table 8. Revision history

Data sheet ID	Release date	Data sheet status	Change notice	Supersedes
BAS21SW v.2	20230105	Product data sheet	-	BAS21W_SER_1
Modifications:	• Family data sheet is transferred to single data sheets. • Section packing information removed.			
BAS21W_SER_1	20091009	Product data sheet	-	-

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2023. All rights reserved

Downloaded From Oneyac.com

15. Legal information

Data sheet status

Document status [1][2]	Product status [3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.
[2] The term 'short data sheet' is explained in section "Definitions".
[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the internet at https://www.nexperia.com.

Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use in automotive applications — This Nexperia product has been qualified for use in automotive applications. Unless otherwise agreed in writing, the product is not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

All information provided in this document is subject to legal disclaimers.

© Nexperia B.V. 2023. All rights reserved

Downloaded From Oneyac.com

Contents

1. General description....1
2. Features and benefits....1
3. Applications....1
4. Quick reference data....1
5. Pinning information....2
6. Ordering information....2
7. Marking....2
8. Limiting values....3
9. Thermal characteristics....3
10. Characteristics....3
11. Test information....5
12. Package outline....6
13. Soldering....6
14. Revision history....7
15. Legal information....8

© Nexperia B.V. 2023. All rights reserved

For more information, please visit: http://www.nexperia.com
For sales office addresses, please send an email to: salesaddresses@nexperia.com
Date of release: 5 January 2023

Downloaded From Oneyac.com

单击下面可查看定价，库存，交付和生命周期等信息

>>Nexperia(安世)

Downloaded From Oneyac.com