



# PSMN130-200D

N-channel TrenchMOS SiliconMAX standard level FET

Rev. 04 — 20 December 2010

Product data sheet

## 1. Product profile

### 1.1 General description

SiliconMAX standard level N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS technology. This product is designed and qualified for use in computing, communications, consumer and industrial applications only.

### 1.2 Features and benefits

- Higher operating power due to low thermal resistance
- Low conduction losses due to low on-state resistance
- Suitable for high frequency applications due to fast switching characteristics

### 1.3 Applications

- DC-to-DC converters
- Switched-mode power supplies

### 1.4 Quick reference data



Table 1. Quick reference data

| Symbol                         | Parameter                        | Conditions                                                                                    | Min | Typ | Max | Unit |
|--------------------------------|----------------------------------|-----------------------------------------------------------------------------------------------|-----|-----|-----|------|
| $V_{DS}$                       | drain-source voltage             | $T_j \geq 25\text{ °C}$ ; $T_j \leq 175\text{ °C}$                                            | -   | -   | 200 | V    |
| $I_D$                          | drain current                    | $T_{mb} = 25\text{ °C}$ ; $V_{GS} = 10\text{ V}$                                              | -   | -   | 20  | A    |
| $P_{tot}$                      | total power dissipation          | $T_{mb} = 25\text{ °C}$                                                                       | -   | -   | 150 | W    |
| <b>Static characteristics</b>  |                                  |                                                                                               |     |     |     |      |
| $R_{DS(on)}$                   | drain-source on-state resistance | $V_{GS} = 10\text{ V}$ ; $I_D = 25\text{ A}$ ; $T_j = 25\text{ °C}$                           | -   | 120 | 130 | mΩ   |
| <b>Dynamic characteristics</b> |                                  |                                                                                               |     |     |     |      |
| $Q_{GD}$                       | gate-drain charge                | $V_{GS} = 10\text{ V}$ ; $I_D = 20\text{ A}$ ; $V_{DS} = 160\text{ V}$ ; $T_j = 25\text{ °C}$ | -   | 22  | -   | nC   |

nexperia

2. Pinning information

Table 2. Pinning information

| Pin | Symbol | Description                       | Simplified outline                                                                | Graphic symbol                                                                      |
|-----|--------|-----------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 1   | G      | gate                              |  |  |
| 2   | D      | drain <sup>[1]</sup>              |                                                                                   |                                                                                     |
| 3   | S      | source                            |                                                                                   |                                                                                     |
| mb  | D      | mounting base; connected to drain |                                                                                   |                                                                                     |

SOT428 (DPAK)

[1] It is not possible to make a connection to pin 2.

3. Ordering information

Table 3. Ordering information


| Type number  | Package |                                                                                 |         |
|--------------|---------|---------------------------------------------------------------------------------|---------|
|              | Name    | Description                                                                     | Version |
| PSMN130-200D | DPAK    | plastic single-ended surface-mounted package (DPAK); 3 leads (one lead cropped) | SOT428  |

## 4. Limiting values

**Table 4. Limiting values**


In accordance with the Absolute Maximum Rating System (IEC 60134).

| Symbol                      | Parameter                                    | Conditions                                                                                                                                                                                      | Min | Max | Unit |
|-----------------------------|----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----|------|
| $V_{DS}$                    | drain-source voltage                         | $T_j \geq 25\text{ °C}$ ; $T_j \leq 175\text{ °C}$                                                                                                                                              | -   | 200 | V    |
| $V_{DGR}$                   | drain-gate voltage                           | $T_j \geq 25\text{ °C}$ ; $T_j \leq 175\text{ °C}$ ; $R_{GS} = 20\text{ k}\Omega$                                                                                                               | -   | 200 | V    |
| $V_{GS}$                    | gate-source voltage                          |                                                                                                                                                                                                 | -20 | 20  | V    |
| $I_D$                       | drain current                                | $V_{GS} = 10\text{ V}$ ; $T_{mb} = 100\text{ °C}$                                                                                                                                               | -   | 14  | A    |
|                             |                                              | $V_{GS} = 10\text{ V}$ ; $T_{mb} = 25\text{ °C}$                                                                                                                                                | -   | 20  | A    |
| $I_{DM}$                    | peak drain current                           | pulsed; $T_{mb} = 25\text{ °C}$                                                                                                                                                                 | -   | 80  | A    |
| $P_{tot}$                   | total power dissipation                      | $T_{mb} = 25\text{ °C}$                                                                                                                                                                         | -   | 150 | W    |
| $T_{stg}$                   | storage temperature                          |                                                                                                                                                                                                 | -55 | 175 | °C   |
| $T_j$                       | junction temperature                         |                                                                                                                                                                                                 | -55 | 175 | °C   |
| <b>Source-drain diode</b>   |                                              |                                                                                                                                                                                                 |     |     |      |
| $I_S$                       | source current                               | $T_{mb} = 25\text{ °C}$                                                                                                                                                                         | -   | 20  | A    |
| $I_{SM}$                    | peak source current                          | pulsed; $T_{mb} = 25\text{ °C}$                                                                                                                                                                 | -   | 80  | A    |
| <b>Avalanche ruggedness</b> |                                              |                                                                                                                                                                                                 |     |     |      |
| $E_{DS(AL)S}$               | non-repetitive drain-source avalanche energy | $V_{GS} = 10\text{ V}$ ; $T_{j(\text{init})} = 25\text{ °C}$ ; $I_D = 19\text{ A}$ ;<br>$V_{sup} \leq 25\text{ V}$ ; unclamped; $t_p = 100\text{ }\mu\text{s}$ ;<br>$R_{GS} = 50\text{ }\Omega$ | -   | 252 | mJ   |
| $I_{AS}$                    | non-repetitive avalanche current             | $V_{sup} \leq 25\text{ V}$ ; $V_{GS} = 10\text{ V}$ ; $T_{j(\text{init})} = 25\text{ °C}$ ;<br>$R_{GS} = 50\text{ }\Omega$ ; unclamped                                                          | -   | 20  | A    |



$$P_{der} = \frac{P_{tot}}{P_{tot(25^\circ\text{C})}} \times 100\%$$

**Fig 1. Normalized total power dissipation as a function of mounting base temperature**



$$I_{der} = \frac{I_D}{I_{D(25^\circ\text{C})}} \times 100\%$$

**Fig 2. Normalized continuous drain current as a function of mounting base temperature**




Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage




Fig 4. Single-shot avalanche rating; avalanche current as a function of avalanche period

5. Thermal characteristics

Table 5. Thermal characteristics

| Symbol         | Parameter                                         | Conditions                                            | Min | Typ | Max | Unit |
|----------------|---------------------------------------------------|-------------------------------------------------------|-----|-----|-----|------|
| $R_{th(j-mb)}$ | thermal resistance from junction to mounting base |                                                       | -   | -   | 1   | K/W  |
| $R_{th(j-a)}$  | thermal resistance from junction to ambient       | mounted on a printed-circuit board; minimum footprint | -   | 50  | -   | K/W  |





Fig 5. Transient thermal impedance from junction to mounting base as a function of pulse duration


## 6. Characteristics

Table 6. Characteristics


| Symbol                  | Parameter                        | Conditions                                                                                                                      | Min | Typ  | Max | Unit |
|-------------------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----|------|-----|------|
| Static characteristics  |                                  |                                                                                                                                 |     |      |     |      |
| V <sub>(BR)DSS</sub>    | drain-source breakdown voltage   | I <sub>D</sub> = 0.25 mA; V <sub>GS</sub> = 0 V; T <sub>J</sub> = -55 °C                                                        | 178 | -    | -   | V    |
|                         |                                  | I <sub>D</sub> = 0.25 mA; V <sub>GS</sub> = 0 V; T <sub>J</sub> = 25 °C                                                         | 200 | -    | -   | V    |
| V <sub>GS(th)</sub>     | gate-source threshold voltage    | I <sub>D</sub> = 1 mA; V <sub>DS</sub> = V <sub>GS</sub> ; T <sub>J</sub> = -55 °C                                              | -   | -    | 6   | V    |
|                         |                                  | I <sub>D</sub> = 1 mA; V <sub>DS</sub> = V <sub>GS</sub> ; T <sub>J</sub> = 25 °C                                               | 2   | 3    | 4   | V    |
|                         |                                  | I <sub>D</sub> = 1 mA; V <sub>DS</sub> = V <sub>GS</sub> ; T <sub>J</sub> = 175 °C                                              | 1   | -    | -   | V    |
| I <sub>DSS</sub>        | drain leakage current            | V <sub>DS</sub> = 150 V; V <sub>GS</sub> = 0 V; T <sub>J</sub> = 25 °C                                                          | -   | 0.05 | 10  | µA   |
|                         |                                  | V <sub>DS</sub> = 150 V; V <sub>GS</sub> = 0 V; T <sub>J</sub> = 175 °C                                                         | -   | -    | 500 | µA   |
| I <sub>GSS</sub>        | gate leakage current             | V <sub>GS</sub> = 10 V; V <sub>DS</sub> = 0 V; T <sub>J</sub> = 25 °C                                                           | -   | 0.02 | 100 | nA   |
|                         |                                  | V <sub>GS</sub> = -10 V; V <sub>DS</sub> = 0 V; T <sub>J</sub> = 25 °C                                                          | -   | 0.02 | 100 | nA   |
| R <sub>DSon</sub>       | drain-source on-state resistance | V <sub>GS</sub> = 10 V; I <sub>D</sub> = 25 A; T <sub>J</sub> = 175 °C                                                          | -   | -    | 377 | mΩ   |
|                         |                                  | V <sub>GS</sub> = 10 V; I <sub>D</sub> = 25 A; T <sub>J</sub> = 25 °C                                                           | -   | 120  | 130 | mΩ   |
| Dynamic characteristics |                                  |                                                                                                                                 |     |      |     |      |
| Q <sub>G(tot)</sub>     | total gate charge                | I <sub>D</sub> = 20 A; V <sub>DS</sub> = 160 V; V <sub>GS</sub> = 10 V; T <sub>J</sub> = 25 °C                                  | -   | 65   | -   | nC   |
| Q <sub>GS</sub>         | gate-source charge               |                                                                                                                                 | -   | 10   | -   | nC   |
| Q <sub>GD</sub>         | gate-drain charge                |                                                                                                                                 | -   | 22   | -   | nC   |
| C <sub>iss</sub>        | input capacitance                | V <sub>DS</sub> = 25 V; V <sub>GS</sub> = 0 V; f = 1 MHz; T <sub>J</sub> = 25 °C                                                | -   | 2470 | -   | pF   |
| C <sub>oss</sub>        | output capacitance               |                                                                                                                                 | -   | 207  | -   | pF   |
| C <sub>rss</sub>        | reverse transfer capacitance     |                                                                                                                                 | -   | 90   | -   | pF   |
| t <sub>d(on)</sub>      | turn-on delay time               | V <sub>DS</sub> = 100 V; R <sub>L</sub> = 4.7 Ω; V <sub>GS</sub> = 10 V; R <sub>G(ext)</sub> = 5.6 Ω; T <sub>J</sub> = 25 °C    | -   | 15   | -   | ns   |
| t <sub>r</sub>          | rise time                        |                                                                                                                                 | -   | 46   | -   | ns   |
| t <sub>d(off)</sub>     | turn-off delay time              |                                                                                                                                 | -   | 50   | -   | ns   |
| t <sub>f</sub>          | fall time                        |                                                                                                                                 | -   | 38   | -   | ns   |
| L <sub>D</sub>          | internal drain inductance        | from tab to centre of die; T <sub>J</sub> = 25 °C                                                                               | -   | 3.5  | -   | nH   |
| L <sub>S</sub>          | internal source inductance       | from source lead to source bond pad; T <sub>J</sub> = 25 °C                                                                     | -   | 7.5  | -   | nH   |
| Source-drain diode      |                                  |                                                                                                                                 |     |      |     |      |
| V <sub>SD</sub>         | source-drain voltage             | I <sub>S</sub> = 25 A; V <sub>GS</sub> = 0 V; T <sub>J</sub> = 25 °C                                                            | -   | 0.95 | 1.2 | V    |
| t <sub>rr</sub>         | reverse recovery time            | I <sub>S</sub> = 20 A; dI <sub>S</sub> /dt = -100 A/µs; V <sub>GS</sub> = -10 V; V <sub>DS</sub> = 25 V; T <sub>J</sub> = 25 °C | -   | 124  | -   | ns   |
| Q <sub>r</sub>          | recovered charge                 |                                                                                                                                 | -   | 0.74 | -   | µC   |




**Fig 6. Output characteristics: drain current as a function of drain-source voltage; typical values**




**Fig 7. Drain-source on-state resistance as a function of drain current; typical values**



**Fig 8. Transfer characteristics: drain current as a function of gate-source voltage; typical values**




**Fig 9. Forward transconductance as a function of drain current; typical values**



$$a = \frac{R_{DS(on)}}{R_{DS(on)25^{\circ}\text{C}}}$$

**Fig 10. Normalized drain-source on-state resistance factor as a function of junction temperature**



**Fig 11. Gate-source threshold voltage as a function of junction temperature**




Fig 12. Sub-threshold drain current as a function of gate-source voltage




Fig 13. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values




Fig 14. Gate-source voltage as a function of gate charge; typical values




Fig 15. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values

7. Package outline

Plastic single-ended surface-mounted package (DPAK); 3 leads (one lead cropped)

SOT428




Fig 16. Package outline SOT428 (DPAK)



8. Revision history

Table 7. Revision history

| Document ID         | Release date                                                                                                                                                                                                                                                                             | Data sheet status     | Change notice | Supersedes          |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|---------------|---------------------|
| PSMN130-200D v.4    | 20101220                                                                                                                                                                                                                                                                                 | Product data sheet    | -             | PSMN130-200D_HG v.3 |
| Modifications:      | <ul style="list-style-type: none"><li>The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.</li><li>Legal texts have been adapted to the new company name where appropriate.</li><li>Various changes to content.</li></ul> |                       |               |                     |
| PSMN130-200D_HG v.3 | 19990801                                                                                                                                                                                                                                                                                 | Product specification | -             | -                   |

## 9. Legal information

### 9.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition                                                                            |
|-----------------------------------|-------------------------------|---------------------------------------------------------------------------------------|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

### 9.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

**Suitability for use** — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

### 9.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective

agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the

product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

## 9.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 10. Contact information

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)

## 11. Contents

---

|           |                                          |           |
|-----------|------------------------------------------|-----------|
| <b>1</b>  | <b>Product profile</b> . . . . .         | <b>1</b>  |
| 1.1       | General description . . . . .            | 1         |
| 1.2       | Features and benefits . . . . .          | 1         |
| 1.3       | Applications . . . . .                   | 1         |
| 1.4       | Quick reference data . . . . .           | 1         |
| <b>2</b>  | <b>Pinning information</b> . . . . .     | <b>2</b>  |
| <b>3</b>  | <b>Ordering information</b> . . . . .    | <b>2</b>  |
| <b>4</b>  | <b>Limiting values</b> . . . . .         | <b>3</b>  |
| <b>5</b>  | <b>Thermal characteristics</b> . . . . . | <b>4</b>  |
| <b>6</b>  | <b>Characteristics</b> . . . . .         | <b>5</b>  |
| <b>7</b>  | <b>Package outline</b> . . . . .         | <b>8</b>  |
| <b>8</b>  | <b>Revision history</b> . . . . .        | <b>9</b>  |
| <b>9</b>  | <b>Legal information</b> . . . . .       | <b>10</b> |
| 9.1       | Data sheet status . . . . .              | 10        |
| 9.2       | Definitions . . . . .                    | 10        |
| 9.3       | Disclaimers . . . . .                    | 10        |
| 9.4       | Trademarks . . . . .                     | 11        |
| <b>10</b> | <b>Contact information</b> . . . . .     | <b>11</b> |

单击下面可查看定价，库存，交付和生命周期等信息

[>>Nexperia\(安世\)](#)