





## ■ Dimensions

Cap. (μF)	V (Code)		10		16		25		35	
	Code		1A		1C		1E		1V	
2.2	2R2								10 × 12.5	50
3.3	3R3								10 × 12.5	60
4.7	4R7								10 × 12.5	85
10	100								10 × 12.5	175
22	220								10 × 12.5	200
33	330								10 × 12.5	225
47	470								10 × 12.5	250
100	101						10 × 12.5	250	10 × 20	400
220	221				10 × 16	300	12.5 × 20	500	12.5 × 25	600
330	331	10 × 16	300	10 × 20	400	12.5 × 25	600	16 × 25	800	800
470	471	10 × 20	400	12.5 × 20	600	16 × 25	800	16 × 31.5	1000	1000
1000	102	12.5 × 25	600	16 × 25	800	16 × 31.5	1000	18 × 40	1300	1300
2200	222	16 × 31.5	1000	18 × 35.5	1200					
3300	332	18 × 35.5	1200	18 × 40	1300					
4700	472	18 × 40	1300						Case size φ D × L (mm)	Rated ripple

Cap. (μF)	V (Code)		50		63		80		100	
	Code		1H		1J		1K		2A	
22	220								10 × 12.5	390
33	330						10 × 12.5	420	10 × 16	510
47	470						10 × 16	550	10 × 20	640
56	560				10 × 12.5	430	10 × 20	690	10 × 20	640
68	680				10 × 16	560	10 × 20	690	12.5 × 20	760
100	101	10 × 12.5	380	10 × 20	710	12.5 × 20	820	12.5 × 25	950	950
220	221	10 × 20	640	12.5 × 25	1040	16 × 25	1250	16 × 31.5	1380	1380
330	331	12.5 × 20	770	12.5 × 31.5	1170	16 × 31.5	1480	18 × 31.5	1430	1430
470	471	12.5 × 25	960	16 × 25	1280	18 × 31.5	1530			
560	561	12.5 × 31.5	1080	16 × 31.5	1520					
680	681	16 × 25	1190	16 × 35.5	1520					
1000	102	16 × 31.5	1420						Case size φ D × L (mm)	Rated ripple

Rated ripple current (mA rms) at 150°C 100kHz

### ● Frequency coefficient of rated ripple current

V	CV	Frequency			
		120Hz	300Hz	1kHz	10kHz or more
10 to 100	1000 > CV	0.50	0.64	0.83	1.00
	1000 ≤ CV	0.67	0.79	0.91	1.00

Cap. (μF)	V (Code)		160		200		350		400	
	Code		2C		2D		2V		2G	
4.7	4R7						10 × 16	77	10 × 20	83
6.8	6R8				10 × 12.5	83	10 × 20	110	12.5 × 20	88
10	100	10 × 12.5	110	10 × 12.5	83	12.5 × 20	120	12.5 × 25	105	105
15	150	10 × 12.5	110	10 × 16	130	12.5 × 25	130	12.5 × 25	105	105
22	220	10 × 16	160	10 × 20	170					
33	330	12.5 × 20	230	12.5 × 20	210					
47	470	12.5 × 20	250	12.5 × 25	250					
56	560	12.5 × 25	270	16 × 20	270					
68	680	16 × 20	290	16 × 25	290					
100	101	16 × 25	300						Case size φ D × L (mm)	Rated ripple

Rated ripple current (mA rms) at 150°C 120Hz

### ● Frequency coefficient of rated ripple current

V	Cap. (μF)	Frequency					
		50Hz	120Hz	300Hz	1kHz	10kHz	100kHz or more
160 to 400	4.7 to 33	0.75	1.00	1.25	1.50	1.75	1.80
	47 to 100	0.80	1.00	1.15	1.30	1.40	1.50

单击下面可查看定价，库存，交付和生命周期等信息

[>>Nichicon\(尼吉康\)](#)