

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

UPM

Low Impedance, High Reliability




Low Impedance

Long Life

Anti-Solvent Feature
(Through 100V only)

UPM




- High reliability withstanding 5000 hour load life at +105°C (3000/2000 hours for smaller case sizes as specified below).
- Capacitance ranges available based on the numerical values in E12 series under JIS.
- Compliant to the RoHS directive (2011/65/EU, (EU)2015/863).
- AEC-Q200 compliant. Please contact us for details.

■ Specifications

Item	Performance Characteristics									
Category Temperature Range	-55 to +105°C (6.3 to 100V), -40 to +105°C (160 to 400V), -25 to +105°C (450V)									
Rated Voltage Range	6.3 to 450V									
Rated Capacitance Range	1 to 15000μF									
Capacitance Tolerance	±20% at 120Hz, 20°C									
Leakage Current	Rated Voltage (V)	6.3 to 100								
	Leakage current	After 1 minute's application of rated voltage at 20°C, leakage current is not more than 0.03CV or 4 μA, whichever is greater.								
Tangent of loss angle (tan δ)	For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF.									
	Rated Voltage (V)	6.3	10	16	25	35	50	63 to 100	160 to 350	400 · 450
	tan δ (MAX.)	0.22	0.19	0.16	0.14	0.12	0.10	0.08	0.20	0.25
Stability at Low Temperature	Rated voltage (V)	6.3 · 10	16	25 · 35	50 to 100	160 · 200	250	315 · 350	400	450
	Impedance ratio (MAX.)	Z-25°C / Z+20°C	—	—	—	—	—	—	—	120Hz
		Z-40°C / Z+20°C	—	—	—	—	4	6	8	10
		Z-55°C / Z+20°C	4	3	3	2	—	—	—	—
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after D.C. bias plus rated ripple current is applied for 5000 hours (2000 hours for φD=5 and 6.3, 3000 hours for φD=8) at 105°C, the peak voltage shall not exceed the rated voltage.									
	Capacitance change	Within ±20% of the initial capacitance value								
	tan δ	200% or less than the initial specified value								
	Leakage current	Less than or equal to the initial specified value								
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the characteristic requirements listed at right.									
	Capacitance change	Within ±20% of the initial capacitance value								
	tan δ	150% or less than the initial specified value								
	Leakage current	Less than or equal to the initial specified value								
Marking	Printed with white color letter on dark brown sleeve.									

■ Radial Lead Type



α	($\phi D < 10$) 1.5
	($\phi D \geq 10$) 2.0


(mm)						
ϕD	5	6.3	8	10	12.5	16
P	2.0	2.5	3.5	5.0	5.0	7.5

ϕD	5	6.3	8	10	12.5	16	18
ϕd	0.5	0.5	0.6	0.6	0.6*	0.8	0.8

*In case L > 25 for the φ12.5 dia. unit, lead dia. φ d = 0.8mm.

- Please refer to page 20 about the end seal configuration.


Type numbering system (Example : 25V 470μF)



※ Configuration

φ D	Pb-free leadwire Pb-free PET sleeve
5	DD
6.3	ED
8 · 10	PD
12.5 to 18	HD

● Frequency coefficient of rated ripple current



Please refer to page 20, 21, 22 about the formed or taped product spec.
Please refer to page 4 for the minimum order quantity.

- Dimension table in next page.

UPM

Dimensions

Cap.(μF)	V(Code) Size code	6.3 (0J)		10 (1A)		16 (1C)		25 (1E)		35 (1V)	
		—	6	—	6	—	6	—	6	—	6
22	220									5 × 11	
27	270									5 × 11	
33	330							5 × 11		6.3 × 11	
39	390							5 × 11		6.3 × 11	
47	470					5 × 11		6.3 × 11		6.3 × 11	
56	560					5 × 11		6.3 × 11		6.3 × 11	
68	680			5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
82	820			5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
100	101	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15		8 × 11.5	
120	121	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15		8 × 15	10 × 12.5
150	151	6.3 × 11		6.3 × 11		6.3 × 15		8 × 11.5		8 × 15	10 × 12.5
180	181	6.3 × 11		6.3 × 11		6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 16
220	221	6.3 × 11		6.3 × 15		8 × 11.5		8 × 15	10 × 12.5	8 × 20	10 × 16
270	271	6.3 × 15		6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 16	10 × 20	12.5 × 15
330	331	6.3 × 15		8 × 11.5		8 × 15	10 × 12.5	8 × 20	10 × 16	10 × 20	12.5 × 15
390	391	8 × 11.5		8 × 15	10 × 12.5	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 25	12.5 × 15
470	471	8 × 15	10 × 12.5	8 × 15	10 × 12.5	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 31.5	16 × 15
560	561	8 × 15	10 × 12.5	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 25	12.5 × 15	12.5 × 20	16 × 15
680	681	8 × 20	10 × 16	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15
820	821	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 25	12.5 × 15	12.5 × 20	16 × 15	12.5 × 25	18 × 15
1000	102	10 × 20	12.5 × 15	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20
1200	122	10 × 20	12.5 × 15	10 × 25	12.5 × 15	12.5 × 20	16 × 15	12.5 × 25	18 × 15	12.5 × 35.5	16 × 25
1500	152	10 × 25	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20
1800	182	10 × 31.5	16 × 15	12.5 × 20	16 × 15	12.5 × 31.5	16 × 20	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25
2200	222	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5
2700	272	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25	16 × 40	18 × 35.5
3300	332	12.5 × 25	18 × 15	12.5 × 35.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5	18 × 40	
3900	392	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 31.5	18 × 25	16 × 40	18 × 35.5		
4700	472	12.5 × 35.5	18 × 20	16 × 31.5	18 × 25	16 × 35.5	18 × 31.5	18 × 40			
5600	562	12.5 × 40	18 × 20	16 × 35.5	18 × 25	16 × 40	18 × 35.5				
6800	682	16 × 31.5	18 × 25	16 × 35.5	18 × 31.5	18 × 35.5					
8200	822	16 × 35.5	18 × 31.5	16 × 40	18 × 35.5	18 × 40					
10000	103	16 × 40	18 × 31.5	18 × 40							
12000	123	18 × 35.5									
15000	153	18 × 40									

Cap.(μF)	V(Code) Size code	50 (1H)		63 (1J)		80 (1K)		100 (2A)	
		—	6	—	6	—	6	—	6
2.2	2R2	5 × 11						5 × 11	
3.3	3R3	5 × 11						5 × 11	
4.7	4R7	5 × 11			5 × 11			6.3 × 11	
6.8	6R8	5 × 11			5 × 11			6.3 × 11	
10	100	5 × 11		5 × 11		6.3 × 11		6.3 × 11	
12	120	5 × 11		5 × 11		6.3 × 11		6.3 × 11	
15	150	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
18	180	5 × 11		6.3 × 11		6.3 × 11		6.3 × 15	
22	220	6.3 × 11		6.3 × 11		6.3 × 15		8 × 11.5	
27	270	6.3 × 11		6.3 × 11		6.3 × 15		8 × 15	10 × 12.5
33	330	6.3 × 11		6.3 × 15		8 × 11.5		8 × 15	10 × 12.5
39	390	6.3 × 11		6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 16
47	470	6.3 × 15		8 × 11.5		8 × 15	10 × 12.5	10 × 20	12.5 × 15
56	560	6.3 × 15		8 × 15	10 × 12.5	8 × 20	10 × 16	10 × 20	12.5 × 15
68	680	8 × 11.5		8 × 15	10 × 12.5	10 × 20	12.5 × 15	10 × 25	12.5 × 15
82	820	8 × 15	10 × 12.5	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 31.5	16 × 15
100	101	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 25	12.5 × 15	10 × 31.5	16 × 15
120	121	8 × 20	10 × 16	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	16 × 15
150	151	10 × 20	12.5 × 15	10 × 25	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	18 × 15
180	181	10 × 20	12.5 × 15	10 × 31.5	16 × 15	12.5 × 25	16 × 15	12.5 × 31.5	16 × 20
220	221	10 × 25	12.5 × 15	12.5 × 20	16 × 15	12.5 × 31.5	18 × 15	12.5 × 35.5	16 × 25
270	271	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20
330	331	10 × 31.5	16 × 15	12.5 × 25	18 × 15	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25
390	391	12.5 × 25	16 × 15	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5
470	471	12.5 × 25	18 × 15	12.5 × 35.5	16 × 25	16 × 31.5	18 × 25	16 × 40	18 × 35.5
560	561	12.5 × 31.5	16 × 20	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5	18 × 35.5	
680	681	12.5 × 35.5	16 × 20	16 × 31.5	18 × 25	16 × 40	18 × 31.5	18 × 40	
820	821	12.5 × 40	18 × 20	16 × 35.5	18 × 31.5	18 × 35.5			
1000	102	16 × 31.5	18 × 25	16 × 40	18 × 35.5	18 × 40			
1200	122	16 × 35.5	18 × 31.5	18 × 40					
1500	152	16 × 40	18 × 31.5						
1800	182	18 × 35.5							
2200	222	18 × 40							

In case of low profile type, [6] will be put at 12th digit of type numbering system.

Dimension table for 160 to 450V products are shown in 218 page.

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

UPM

■ Dimensions

Cap.(μ F)	Code	Item	V(Code) Size code	6.3 (0J)									
				—				6					
				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mArms)		Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAarms)	
100	101	5 × 11	0.85		1.70	150	99	105°C / 100kHz to 200kHz		20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz
120	121	5 × 11	0.65	1.30	175	115							
150	151	6.3 × 11	0.49	0.98	225	155							
180	181	6.3 × 11	0.39	0.78	250	175							
220	221	6.3 × 11	0.30	0.60	285	205							
270	271	6.3 × 15	0.24	0.48	370	275							
330	331	6.3 × 15	0.20	0.40	405	310							
390	391	8 × 11.5	0.17	0.34	445	345							
470	471	8 × 15	0.14	0.28	550	440	10 × 12.5	0.14	0.28	635	505		
560	561	8 × 15	0.12	0.24	595	485	10 × 12.5	0.13	0.26	670	545		
680	681	8 × 20	0.10	0.20	730	605	10 × 16	0.11	0.22	825	685		
820	821	8 × 20	0.085	0.17	795	675	10 × 16	0.095	0.19	840	715		
1000	102	10 × 20	0.075	0.15	950	820	12.5 × 15	0.085	0.17	890	770		
1200	122	10 × 20	0.065	0.13	1060	930	12.5 × 15	0.075	0.15	950	835		
1500	152	10 × 25	0.055	0.11	1260	1130	12.5 × 15	0.065	0.13	1020	915		
1800	182	10 × 31.5	0.050	0.10	1370	1230	16 × 15	0.055	0.11	1270	1140		
2200	222	10 × 31.5	0.043	0.086	1470	1320	16 × 15	0.049	0.098	1340	1200		
2700	272	12.5 × 25	0.038	0.076	1700	1530	18 × 15	0.044	0.088	1500	1350		
3300	332	12.5 × 25	0.034	0.068	1710	1530	18 × 15	0.039	0.078	1600	1440		
3900	392	12.5 × 31.5	0.031	0.062	1980	1780	16 × 20	0.036	0.072	1770	1590		
4700	472	12.5 × 35.5	0.028	0.056	2230	2000	18 × 20	0.032	0.064	1920	1720		
5600	562	12.5 × 40	0.026	0.052	2460	2210	18 × 20	0.030	0.060	1980	1780		
6800	682	16 × 31.5	0.024	0.048	2510	2250	18 × 25	0.027	0.054	2350	2110		
8200	822	16 × 35.5	0.022	0.044	2770	2490	18 × 31.5	0.025	0.050	2600	2340		
10000	103	16 × 40	0.020	0.040	3110	2790	18 × 31.5	0.023	0.046	2720	2440		
12000	123	18 × 35.5	0.019	0.038	3050	2740							
15000	153	18 × 40	0.018	0.036	3300	2970							

Cap.(μ F)	Code	Item	V(Code) Size code	10 (1A)									
				—				6					
				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAarms)		Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAarms)	
68	680	5 × 11	0.80		1.60	155	97	105°C / 100kHz to 200kHz		20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz
82	820	5 × 11	0.65	1.30	175	110							
100	101	6.3 × 11	0.55	1.10	210	135							
120	121	6.3 × 11	0.44	0.88	235	160							
150	151	6.3 × 11	0.35	0.70	265	185							
180	181	6.3 × 11	0.29	0.58	290	205							
220	221	6.3 × 15	0.24	0.48	370	270							
270	271	6.3 × 15	0.20	0.40	405	300							
330	331	8 × 11.5	0.16	0.32	460	350							
390	391	8 × 15	0.14	0.28	550	430	10 × 12.5	0.15	0.30	635	490		
470	471	8 × 15	0.12	0.24	595	475	10 × 12.5	0.13	0.26	670	535		
560	561	8 × 20	0.10	0.20	730	595	10 × 16	0.11	0.22	700	570		
680	681	8 × 20	0.085	0.17	795	660	10 × 16	0.090	0.18	825	685		
820	821	10 × 20	0.070	0.14	985	835	12.5 × 15	0.080	0.16	920	780		
1000	102	10 × 20	0.060	0.12	1060	915	12.5 × 15	0.065	0.13	1040	900		
1200	122	10 × 25	0.050	0.10	1260	1120	12.5 × 15	0.060	0.12	1060	930		
1500	152	10 × 31.5	0.045	0.090	1450	1300	16 × 15	0.050	0.10	1330	1190		
1800	182	12.5 × 20	0.039	0.078	1470	1320	16 × 15	0.044	0.088	1420	1270		
2200	222	12.5 × 25	0.034	0.068	1710	1530	18 × 15	0.039	0.078	1600	1440		
2700	272	12.5 × 31.5	0.030	0.060	1980	1780	16 × 20	0.035	0.070	1740	1560		
3300	332	12.5 × 35.5	0.026	0.052	2230	2000	16 × 20	0.031	0.062	1850	1660		
3900	392	12.5 × 40	0.024	0.048	2460	2210	18 × 20	0.028	0.056	2050	1840		
4700	472	16 × 31.5	0.023	0.046	2420	2170	18 × 25	0.026	0.052	2350	2110		
5600	562	16 × 35.5	0.021	0.042	2610	2340	18 × 25	0.024	0.048	2440	2190		
6800	682	16 × 35.5	0.020	0.040	2770	2490	18 × 31.5	0.022	0.044	2720	2440		
8200	822	16 × 40	0.019	0.038	3110	2790	18 × 35.5	0.021	0.042	3050	2740		
10000	103	18 × 40	0.017	0.034	3300	2970							

In case of low profile type, [6] will be put at 12th digit of type numbering system.

UPM

■ Dimensions

Cap.(μ F)	Code	Item	Case size $\phi D \times L$ (mm)	16 (1C)						6							
				—				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAarms)		Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAarms)	
				20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz
47	470	5 × 11	0.80	1.60	155	92											
56	560	5 × 11	0.65	1.30	175	105											
68	680	6.3 × 11	0.50	1.00	220	135											
82	820	6.3 × 11	0.42	0.84	240	155											
100	101	6.3 × 11	0.35	0.70	265	175											
120	121	6.3 × 11	0.29	0.58	290	195											
150	151	6.3 × 15	0.23	0.46	375	260											
180	181	6.3 × 15	0.20	0.40	405	285											
220	221	8 × 11.5	0.16	0.32	460	335											
270	271	8 × 15	0.14	0.28	550	410	10 × 12.5	0.14	0.28	635	470						
330	331	8 × 15	0.12	0.24	595	455	10 × 12.5	0.12	0.24	670	510						
390	391	8 × 20	0.10	0.20	730	570	10 × 16	0.10	0.20	730	570						
470	471	8 × 20	0.090	0.18	770	615	10 × 16	0.090	0.18	825	660						
560	561	10 × 20	0.075	0.15	950	775	12.5 × 15	0.080	0.16	920	750						
680	681	10 × 20	0.065	0.13	1060	880	12.5 × 15	0.070	0.14	985	820						
820	821	10 × 25	0.055	0.11	1260	1070	12.5 × 15	0.060	0.12	1060	900						
1000	102	10 × 31.5	0.047	0.094	1410	1220	16 × 15	0.055	0.11	1270	1100						
1200	122	12.5 × 20	0.041	0.082	1430	1250	16 × 15	0.046	0.092	1390	1220						
1500	152	12.5 × 25	0.036	0.072	1700	1530	18 × 15	0.041	0.082	1560	1400						
1800	182	12.5 × 31.5	0.032	0.064	1880	1690	16 × 20	0.037	0.074	1700	1530						
2200	222	12.5 × 31.5	0.028	0.056	2010	1800	16 × 20	0.033	0.066	1800	1620						
2700	272	12.5 × 35.5	0.025	0.050	2230	2000	16 × 25	0.030	0.060	2190	1970						
3300	332	12.5 × 40	0.023	0.046	2460	2210	18 × 20	0.027	0.054	2090	1880						
3900	392	16 × 31.5	0.022	0.044	2510	2250	18 × 25	0.025	0.050	2350	2110						
4700	472	16 × 35.5	0.020	0.040	2770	2490	18 × 31.5	0.023	0.046	2720	2440						
5600	562	16 × 40	0.019	0.038	3110	2790	18 × 35.5	0.022	0.044	2620	2350						
6800	682	18 × 35.5	0.018	0.036	3050	2740											
8200	822	18 × 40	0.017	0.034	3300	2970											

Cap.(μ F)	Code	Item	Case size $\phi D \times L$ (mm)	25 (1E)						6							
				—				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAarms)		Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAarms)	
				20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz
33	330	5 × 11	0.80	1.60	155	88											
39	390	5 × 11	0.65	1.30	175	100											
47	470	6.3 × 11	0.55	1.10	210	125											
56	560	6.3 × 11	0.44	0.88	235	140											
68	680	6.3 × 11	0.36	0.72	260	160											
82	820	6.3 × 11	0.30	0.60	285	180											
100	101	6.3 × 15	0.24	0.48	370	245											
120	121	6.3 × 15	0.20	0.40	405	275											
150	151	8 × 11.5	0.16	0.32	460	320											
180	181	8 × 15	0.14	0.28	550	390	10 × 12.5	0.15	0.30	635	450						
220	221	8 × 15	0.11	0.22	625	455	10 × 12.5	0.13	0.26	670	485						
270	271	8 × 20	0.095	0.19	750	560	10 × 16	0.11	0.22	700	525						
330	331	8 × 20	0.085	0.17	795	610	10 × 16	0.095	0.19	825	630						
390	391	10 × 20	0.070	0.14	985	770	12.5 × 15	0.080	0.16	920	720						
470	471	10 × 20	0.065	0.13	1060	845	12.5 × 15	0.070	0.14	985	785						
560	561	10 × 25	0.055	0.11	1260	1030	12.5 × 15	0.060	0.12	1060	860						
680	681	10 × 31.5	0.046	0.092	1420	1180	16 × 15	0.055	0.11	1270	1050						
820	821	12.5 × 20	0.041	0.082	1440	1220	16 × 15	0.049	0.098	1340	1140						
1000	102	12.5 × 25	0.036	0.072	1700	1470	18 × 15	0.043	0.086	1520	1310						
1200	122	12.5 × 25	0.032	0.064	1760	1550	18 × 15	0.039	0.078	1600	1400						
1500	152	12.5 × 31.5	0.029	0.058	1980	1780	16 × 20	0.034	0.068	1770	1590						
1800	182	12.5 × 35.5	0.026	0.052	2230	2000	16 × 25	0.031	0.062	2190	1970						
2200	222	12.5 × 40	0.024	0.048	2460	2210	18 × 20	0.028	0.056	2050	1840						
2700	272	16 × 31.5	0.022	0.044	2510	2250	18 × 25	0.025	0.050	2350	2110						
3300	332	16 × 35.5	0.020	0.040	2770	2490	18 × 31.5	0.023	0.046	2720	2440						
3900	392	16 × 40	0.019	0.038	3110	2790	18 × 35.5	0.021	0.042	3050	2740						
4700	472	18 × 40	0.018	0.036	3300	2970											

In case of low profile type, [6] will be put at 12th digit of type numbering system.

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

UPM

Dimensions

Cap.(μ F)	Code	V(Code) Size code	Item	35 (1V)										
				—				6						
				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)		Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)		
22	220	5 x 11	0.75	1.50	160	85	20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz	20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz
27	270	5 x 11	0.60	1.20	180	99								
33	330	6.3 x 11	0.49	0.98	225	125								
39	390	6.3 x 11	0.41	0.82	245	140								
47	470	6.3 x 11	0.34	0.68	270	160								
56	560	6.3 x 11	0.28	0.56	295	180								
68	680	6.3 x 15	0.24	0.48	370	230								
82	820	6.3 x 15	0.19	0.38	415	265								
100	101	8 x 11.5	0.16	0.32	460	305								
120	121	8 x 15	0.14	0.28	550	370	10 x 12.5	0.15	0.30	635	425			
150	151	8 x 15	0.12	0.24	595	415	10 x 12.5	0.12	0.24	680	475			
180	181	8 x 20	0.10	0.20	730	520	10 x 16	0.11	0.22	700	500			
220	221	8 x 20	0.085	0.17	795	580	10 x 16	0.090	0.18	825	600			
270	271	10 x 20	0.070	0.14	985	735	12.5 x 15	0.080	0.16	920	690			
330	331	10 x 20	0.060	0.12	1060	810	12.5 x 15	0.065	0.13	1020	780			
390	391	10 x 25	0.055	0.11	1260	980	12.5 x 15	0.060	0.12	1060	825			
470	471	10 x 31.5	0.046	0.092	1450	1160	16 x 15	0.055	0.11	1270	1010			
560	561	12.5 x 20	0.041	0.082	1430	1170	16 x 15	0.048	0.096	1360	1110			
680	681	12.5 x 25	0.036	0.072	1700	1410	18 x 15	0.042	0.084	1540	1280			
820	821	12.5 x 25	0.032	0.064	1760	1490	18 x 15	0.038	0.076	1620	1380			
1000	102	12.5 x 31.5	0.029	0.058	1980	1710	16 x 20	0.034	0.068	1770	1530			
1200	122	12.5 x 35.5	0.026	0.052	2230	1960	16 x 25	0.031	0.062	2190	1920			
1500	152	12.5 x 40	0.024	0.048	2460	2210	18 x 20	0.028	0.056	2050	1840			
1800	182	16 x 31.5	0.022	0.044	2510	2250	18 x 25	0.025	0.050	2350	2110			
2200	222	16 x 35.5	0.020	0.040	2770	2490	18 x 31.5	0.023	0.046	2720	2440			
2700	272	16 x 40	0.018	0.036	3110	2790	18 x 35.5	0.021	0.042	3050	2740			
3300	332	18 x 40	0.017	0.034	3300	2970								

Cap.(μ F)	Code	V(Code) Size code	Item	50 (1H)										
				—				6						
				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)		Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)		
2.2	2R2	5 x 11	5.00	10.0	54	27	20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz	20°C / 100kHz	-10°C / 100kHz	105°C / 100kHz to 200kHz	105°C / 120Hz
3.3	3R3	5 x 11	3.30	6.60	66	33								
4.7	4R7	5 x 11	2.20	4.40	81	40								
6.8	6R8	5 x 11	1.80	3.60	91	45								
10	100	5 x 11	1.40	2.80	115	57								
12	120	5 x 11	1.20	2.40	125	62								
15	150	5 x 11	0.93	1.86	145	72								
18	180	5 x 11	0.80	1.60	165	79								
22	220	6.3 x 11	0.65	1.30	195	100								
27	270	6.3 x 11	0.53	1.06	215	115								
33	330	6.3 x 11	0.43	0.86	240	135								
39	390	6.3 x 11	0.36	0.72	260	150								
47	470	6.3 x 15	0.30	0.60	330	195								
56	560	6.3 x 15	0.25	0.50	360	220								
68	680	8 x 11.5	0.20	0.40	415	260								
82	820	8 x 15	0.17	0.34	505	320	10 x 12.5	0.18	0.36	530	340			
100	101	8 x 20	0.14	0.28	620	410	10 x 16	0.16	0.32	580	385			
120	121	8 x 20	0.12	0.24	755	510	10 x 16	0.13	0.26	755	510			
150	151	10 x 20	0.10	0.20	820	570	12.5 x 15	0.11	0.22	785	545			
180	181	10 x 20	0.085	0.17	945	670	12.5 x 15	0.095	0.19	845	605			
220	221	10 x 25	0.075	0.15	1150	840	12.5 x 15	0.080	0.16	920	670			
270	271	10 x 31.5	0.065	0.13	1200	900	16 x 15	0.070	0.14	1120	840			
330	331	10 x 31.5	0.055	0.11	1300	995	16 x 15	0.060	0.12	1210	925			
390	391	12.5 x 25	0.048	0.096	1440	1120	16 x 15	0.055	0.11	1270	990			
470	471	12.5 x 25	0.044	0.088	1500	1200	18 x 15	0.046	0.092	1470	1170			
560	561	12.5 x 31.5	0.040	0.080	1720	1410	16 x 20	0.044	0.088	1550	1270			
680	681	12.5 x 35.5	0.036	0.072	1900	1580	16 x 20	0.040	0.080	1630	1350			
820	821	12.5 x 40	0.033	0.066	2120	1800	18 x 20	0.036	0.072	1810	1540			
1000	102	16 x 31.5	0.030	0.060	2150	1860	18 x 25	0.033	0.066	2020	1750			
1200	122	16 x 35.5	0.028	0.056	2320	2040	18 x 31.5	0.031	0.062	2140	1880			
1500	152	16 x 40	0.026	0.052	2650	2380	18 x 31.5	0.029	0.058	2340	2100			
1800	182	18 x 35.5	0.025	0.050	2620	2350								
2200	222	18 x 40	0.024	0.048	2790	2510								

In case of low profile type, [6] will be put at 12th digit of type numbering system.

ALUMINUM ELECTROLYTIC CAPACITORS

nichicon

UPM

Dimensions

Cap.(μ F)	Code	Item	Case size $\phi D \times L$ (mm)	63 (1J)				6			
				—				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)
				20°C / 100kHz	-10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	-10°C / 100kHz	105°C / 10kHz to 200kHz
10	100	5 × 11	5 × 11	1.06	2.12	135	67				
12	120	5 × 11	5 × 11	0.93	1.86	145	72				
15	150	6.3 × 11	6.3 × 11	0.73	1.46	185	92				
18	180	6.3 × 11	6.3 × 11	0.63	1.26	195	100				
22	220	6.3 × 11	6.3 × 11	0.52	1.04	215	110				
27	270	6.3 × 11	6.3 × 11	0.43	0.86	240	130				
33	330	6.3 × 15	6.3 × 15	0.35	0.70	305	170				
39	390	6.3 × 15	6.3 × 15	0.30	0.60	330	190				
47	470	8 × 11.5	8 × 11.5	0.25	0.50	365	215				
56	560	8 × 15	8 × 15	0.21	0.42	450	275	10 × 12.5	0.23	0.46	450
68	680	8 × 15	8 × 15	0.17	0.34	500	315	10 × 12.5	0.19	0.38	495
82	820	8 × 20	8 × 20	0.15	0.30	600	385	10 × 16	0.16	0.32	580
100	101	10 × 20	10 × 20	0.12	0.24	750	495	12.5 × 15	0.14	0.28	695
120	121	10 × 20	10 × 20	0.10	0.20	820	555	12.5 × 15	0.12	0.24	750
150	151	10 × 25	10 × 25	0.090	0.18	950	665	12.5 × 15	0.095	0.19	845
180	181	10 × 31.5	10 × 31.5	0.075	0.15	1110	790	16 × 15	0.080	0.16	1050
220	221	12.5 × 20	12.5 × 20	0.065	0.13	1140	835	16 × 15	0.070	0.14	1120
270	271	12.5 × 25	12.5 × 25	0.055	0.11	1340	1000	18 × 15	0.060	0.12	1290
330	331	12.5 × 25	12.5 × 25	0.049	0.098	1420	1090	18 × 15	0.050	0.10	1410
390	391	12.5 × 31.5	12.5 × 31.5	0.043	0.086	1620	1260	16 × 20	0.047	0.094	1500
470	471	12.5 × 35.5	12.5 × 35.5	0.039	0.078	1780	1420	16 × 25	0.042	0.084	1700
560	561	12.5 × 40	12.5 × 40	0.035	0.070	1950	1590	18 × 20	0.039	0.078	1730
680	681	16 × 31.5	16 × 31.5	0.032	0.064	2050	1700	18 × 25	0.035	0.070	1940
820	821	16 × 35.5	16 × 35.5	0.029	0.058	2220	1890	18 × 31.5	0.032	0.064	2110
1000	102	16 × 40	16 × 40	0.027	0.054	2370	2050	18 × 35.5	0.029	0.058	2280
1200	122	18 × 40	18 × 40	0.025	0.050	2510	2210				1970

Cap.(μ F)	Code	Item	Case size $\phi D \times L$ (mm)	80 (1K)				6			
				—				Case size $\phi D \times L$ (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)
				20°C / 100kHz	-10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	-10°C / 100kHz	105°C / 10kHz to 200kHz
4.7	4R7	5 × 11	5 × 11	4.20	11.00	53	26				
6.8	6R8	5 × 11	5 × 11	2.60	7.00	68	34				
10	100	6.3 × 11	6.3 × 11	1.70	4.60	87	43				
12	120	6.3 × 11	6.3 × 11	1.40	3.80	96	48				
15	150	6.3 × 11	6.3 × 11	1.20	3.20	104	52				
18	180	6.3 × 11	6.3 × 11	1.00	2.70	150	78				
22	220	6.3 × 15	6.3 × 15	0.77	2.10	180	95				
27	270	6.3 × 15	6.3 × 15	0.63	1.70	220	115				
33	330	8 × 11.5	8 × 11.5	0.53	1.40	275	150				
39	390	8 × 15	8 × 15	0.46	1.20	300	170	10 × 12.5	0.49	1.30	380
47	470	8 × 15	8 × 15	0.39	1.10	360	215	10 × 12.5	0.42	1.10	410
56	560	8 × 20	8 × 20	0.34	0.92	490	295	10 × 16	0.36	0.97	500
68	680	10 × 20	10 × 20	0.28	0.76	570	355	12.5 × 15	0.31	0.84	520
82	820	10 × 20	10 × 20	0.25	0.68	620	395	12.5 × 15	0.27	0.73	560
100	101	10 × 25	10 × 25	0.21	0.57	795	525	12.5 × 15	0.23	0.62	605
120	121	10 × 31.5	10 × 31.5	0.18	0.49	870	585	16 × 15	0.20	0.54	663
150	151	10 × 31.5	10 × 31.5	0.15	0.41	955	665	16 × 15	0.18	0.47	699
180	181	12.5 × 25	12.5 × 25	0.13	0.35	1040	735	16 × 15	0.15	0.41	766
220	221	12.5 × 31.5	12.5 × 31.5	0.12	0.32	1160	845	18 × 15	0.13	0.35	881
270	271	12.5 × 31.5	12.5 × 31.5	0.10	0.27	1270	945	16 × 20	0.11	0.30	1240
330	331	12.5 × 35.5	12.5 × 35.5	0.088	0.24	1450	1100	16 × 25	0.099	0.27	1440
390	391	12.5 × 40	12.5 × 40	0.078	0.21	1610	1250	18 × 20	0.089	0.24	1450
470	471	16 × 31.5	16 × 31.5	0.069	0.19	1790	1430	18 × 25	0.080	0.22	1650
560	561	16 × 35.5	16 × 35.5	0.062	0.17	2000	1640	18 × 31.5	0.072	0.19	1750
680	681	16 × 40	16 × 40	0.055	0.15	2200	1830	18 × 31.5	0.065	0.18	1850
820	821	18 × 35.5	18 × 35.5	0.049	0.13	2250	1910				1540
1000	102	18 × 40	18 × 40	0.044	0.12	2370	2050				

In case of low profile type, [6] will be put at 12th digit of type numbering system.

UPM

■ Dimensions

Cap.(μF)	Code	V(Code) Size code	100 (2A)										
			—				6						
			Item	Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)		Case size φD × L (mm)	Impedance (Ω) MAX.		Rated ripple (mAmps)	
2.2	2R2	5 × 11	6.60	18.0	43	21	105°C / 10kHz to 200kHz	105°C / 120Hz		20°C / 100kHz	-10°C / 100kHz	105°C / 10kHz to 200kHz	105°C / 120Hz
3.3	3R3	5 × 11	4.10	11.0	54	27							
4.7	4R7	6.3 × 11	2.80	7.60	68	34							
6.8	6R8	6.3 × 11	1.90	5.10	83	41							
10	100	6.3 × 11	1.20	3.20	104	52							
12	120	6.3 × 11	1.00	2.70	150	75							
15	150	6.3 × 15	0.81	2.20	180	90							
18	180	6.3 × 15	0.67	1.80	220	110							
22	220	8 × 11.5	0.55	1.50	275	145							
27	270	8 × 15	0.47	1.30	300	160	10 × 12.5	0.50	1.40	380	205		
33	330	8 × 15	0.38	1.00	360	200	10 × 12.5	0.42	1.10	410	230		
39	390	8 × 20	0.33	0.89	490	280	10 × 16	0.36	0.97	500	285		
47	470	10 × 20	0.28	0.76	570	340	12.5 × 15	0.31	0.84	520	310		
56	560	10 × 20	0.24	0.65	620	375	12.5 × 15	0.27	0.73	560	340		
68	680	10 × 25	0.21	0.57	795	500	12.5 × 15	0.23	0.62	605	380		
82	820	10 × 31.5	0.18	0.49	870	555	16 × 15	0.19	0.51	681	435		
100	101	10 × 31.5	0.15	0.41	955	635	16 × 15	0.17	0.46	719	475		
120	121	12.5 × 25	0.13	0.35	1040	700	16 × 15	0.14	0.38	793	535		
150	151	12.5 × 25	0.11	0.30	1120	780	18 × 15	0.12	0.32	917	640		
180	181	12.5 × 31.5	0.098	0.26	1270	900	16 × 20	0.11	0.30	1240	880		
220	221	12.5 × 35.5	0.087	0.23	1450	1050	16 × 25	0.093	0.25	1440	1050		
270	271	12.5 × 40	0.072	0.19	1610	1200	18 × 20	0.080	0.22	1450	1080		
330	331	16 × 31.5	0.062	0.17	1790	1370	18 × 25	0.070	0.19	1650	1260		
390	391	16 × 35.5	0.053	0.14	2000	1550	18 × 31.5	0.062	0.17	1850	1430		
470	471	16 × 40	0.047	0.13	2200	1760	18 × 35.5	0.056	0.15	1970	1570		
560	561	18 × 35.5	0.041	0.11	2250	1840							
680	681	18 × 40	0.036	0.097	2300	1910							

In case of low profile type, [6] will be put at 12th digit of type numbering system.

Cap.(μF)	Code	160		200		250		315		350		400		450	
		2C	2D	2E	2F	2V	2G	2W							
1	010	8 × 11.5	19	8 × 11.5	19	8 × 11.5	19	8 × 11.5	19	10 × 12.5	21	10 × 12.5	17	10 × 16	17
2.2	2R2	8 × 11.5	30	8 × 11.5	30	10 × 12.5	32	10 × 12.5	32	10 × 16	34	10 × 16	28	10 × 20	28
3.3	3R3	10 × 12.5	50	10 × 12.5	50	10 × 16	52	10 × 16	52	10 × 20	54	10 × 20	47	12.5 × 20	48
4.7	4R7	10 × 12.5	57	10 × 16	60	10 × 16	60	10 × 20	65	10 × 20	65	12.5 × 20	55	12.5 × 25	55
10	100	10 × 16	90	10 × 20	95	12.5 × 20	98	12.5 × 20	98	12.5 × 25	100	12.5 × 25	85	16 × 25	90
22	220	12.5 × 20	140	12.5 × 25	145	16 × 25	150	16 × 25	150	16 × 25	150	16 × 31.5	130	16 × 35.5	135
33	330	12.5 × 25	175	16 × 25	180	16 × 25	180	16 × 31.5	185	16 × 35.5	190	18 × 35.5	170	18 × 40	170
47	470	16 × 25	220	16 × 25	220	16 × 31.5	225	18 × 35.5	235	18 × 40	240			Case size φD × L (mm)	※1
100	101	16 × 35.5	330	18 × 40	345	18 × 40	345								

※1 Rated ripple current (mAmps) at 105°C 120Hz



电子元器件线上授权代理开拓者
原厂授权 · 正品现货 · 一件即发

单击下面可查看定价，库存，交付和生命周期等信息

[>>Nichicon\(尼吉康\)](#)