



インターフェース (端子型号)  
WF20006-01201 (ATOM)

No.	PIN配列
1	24V
2	GND
3	NC
4	CLK
5	FG
6	NC

Note. 1: M3部3箇所のネジ侵入深さは6mmMaxとする。  
M3部的3処螺釘最大可深度的値為6mm。  
The screw invasion depth of M3 part is 6mm Max.

REV	ISSUE	ECO No.	APPROVED	DESIGNED	APPROVED	CHECKED	DESIGNED	DRAWN	No.	PART No.	PART NAME	NOTE	Q'ty	UNIT	MARKS/MTL
	0						A. WANG	2022-07-27							
							A. WANG	2022-07-26							
TOLERANCE UNLESS OTHERWISE SPECIFIED										TREAT.				MTL.	
LINEAR										FINISH				MODEL	42F704R590
0~30 : ±0.5													PARTS	DCブラシレスモータ	
30~ : ±0.8													DWG.	DC Brushless Motor	
~ : ±										UNIT	SCALE 1/1	A3	DWG.	外形図	
ANGULAR : ±1°														Out-line Drawing	
CORNER															
OUTSIDE : C															
INSIDE : R															
										DWG. No.	K980938400				

单击下面可查看定价，库存，交付和生命周期等信息

[>>Nidec\(尼得科\)](#)