

# NU8015Q: Integrated Power Stage for High-Integration and High-Efficiency Medium-Power Wireless Power Transmitter

## 1 Features

- Wide Input Voltage: 4V to 21V
- Integrated 7A rating high-efficiency full-bridge FETs
- Integrated FET Driver Optimized for Low EMI
- Integrated 5V DC/DC for IC power supply
- Integrated 3.3V (2.5V configurable) LDO to Bias External Circuit and Provide Reference Voltage
- High-Accuracy, Lossless Current Measurement for FOD and In-Band Communication
- Integrated Lossless Q Factor Detection
- Integrated Low-Error-Rate Digital Demodulation
- Input UVLO and OVP
- Over-Current Protection
- Thermal Shutdown
- I<sup>2</sup>C Interface
- AEC-Q100 Grade 2 qualified
- 4mm×4mm QFN Package

## 2 Applications

- Wireless Power Transmitter Compliant with WPC V1.2.4 Extended Power Profile (EPP)
- Wireless Power Transmitter for Automotive Applications
- Motor Drivers

## 3 Descriptions

NU8015Q is a family of highly integrated full-bridge power stage IC optimized for wireless power transmitter solutions. The device integrates all critical functions, such as high-efficiency power FETs, low-EMI FET drivers, bootstrap circuit, 5V integrated DC/DC power supply, 3.3V (2.5V configurable) LDO and lossless current measurement. The proprietary current-measurement circuit provides the accurate current reading used for the FOD (Foreign Object Detection) power measurement, in-band communication, Q factor detection, and digital demodulation.

The IC also includes protection functions such as input under-voltage lockout, over-voltage protection, over current protection, and thermal shutdown. These provisions further enhance the reliability of the total system solution.

I<sup>2</sup>C interface is used for communication with the controller and can easily be extended to multi-coil solutions. The device is housed in a thermally enhanced 4mm×4mm QFN package.

This document contains confidential and proprietary information of NuVolta. Any information in this document is prohibited from being used, reproduced or disseminated to any third party in any form and/or through any means without the prior written consent of NuVolta. **ALL RIGHTS RESERVED.**

## 10 Package Information

Orderable Device	Status	Package Type	Package Drawing	Pins	Package Quantity
NU8015QQCFB	MP	QFN	QCF	34	3000
Orderable Device	Eco Plan	Lead/Ball Finish	MSL Peak Temp	OpTemp/°C	Device Marking
NU8015QQCFB	Green (RoHS & no Sb/Br)	Tin	Level-2	-40 to 125	NU8015Q

单击下面可查看定价，库存，交付和生命周期等信息

[>>NuVolta](#)