


6 mm Square Dustproof Ceramic Trimmer Potentiometers (Cermet, Radial Taping)

Discontinued

Type: **EVMAAS/EVMAES**
(Radial Taping)
EVMAAG/EVMAEG/EVMAHG/EVMAJG/EVMASG
(Bulk)



Features

- High reliability due to cermet element
- Excellent automatic insertion due to strong lead terminals
- Available for automatic adjustment due to slot & taper shape suitable for screwdriver
- Dustproof type with electrically activated wiper enclosed in an insulated rotor cap
- Conforms to JIS C5260-1:1999
- RoHS compliant

Recommended Applications

- Audio/visual, office, and communication equipment
- General electronic equipment

Explanation of Part Numbers

1	2	3	4	5	6	7	8	9	10	11	12									
E	V	M	A	A	S	A	0	0	B	5	2									
Product Code			Type/Structure (AA, AE, AH, AJ, AS)				Taper & Resistance Example : B52=500 Ω													
Symbol		Packaging																		
SA00		Radial taping height 20 mm																		
SA01		Radial taping height 21 mm																		
GA00		Bulk Standard																		

Specifications

	EVMAA□/EVMAHG/EVMAJG/EVMASG	EVMAE□ (Low Resistor Value)
Total Resistance Value	100 Ω to 1 MΩ	10 Ω to 500 Ω
Resistance Tolerance	±25 %	
Power Rating	0.3 W	0.5 W
Limiting Element Voltage	100 V	$\sqrt{P \cdot R}$
Rotation Torque	2 to 30 mN·m	
Stopper Strength	50 mN·m min.	
Temperature Coefficient of Resistance	±200 × 10 ⁻⁶ /°C	· 10 Ω ≤ R ≤ 20 Ω ±200 × 10 ⁻⁶ /°C · 20 Ω < R ≤ 200 Ω ±150 × 10 ⁻⁶ /°C · 200 Ω < R ≤ 500 Ω ±100 × 10 ⁻⁶ /°C

Minimum Quantity/Packing Unit



Part Number	Radial taping		Bulk	
	Quantity per Box	Packaging quantity	Quantity per pack	Packaging quantity
EVMAAS EVMAES	1,000	10,000	—	—
EVMAAG EVMAHG EVMAJG EVMASG	—	—	200	2,000
EVMAEG	—	—	600	3,000

Dimensions in mm (not to scale)

● Radial tapering

● 3-terminal, Top-adjust, Cross Slots EVMAAS/EVMAES

No. 1




Mass (Weight) : 420 mg/pc.

● Bulk

● 3-terminal, Top-adjust, Cross Slots EVMAAG/EVMAEG

No. 2




Mass (Weight) : 420 mg/pc.

Panasonic Ceramic Substrate Trimmer Potentiometers


Dimensions in mm (not to scale)

● Bulk


● 3-terminal, Top-adjust, Cross Slots EVMAHG



● 3-terminal, Top-adjust, Cross Slots EVMAJG



● 3-terminal, Top-adjust, Cross Slots EVMASG



单击下面可查看定价，库存，交付和生命周期等信息

[>>Panasonic\(松下\)](#)