



DY2M5Z0C0L1

For bidirectional ESD protection and transient voltage suppressor

■ Features

- IEC 61000-4-2 (ESD) ±15 kV (Contact and Air)
- IEC 61000-4-5 (Lightning) 1.9 A (8/20 μs)
- Low leak current
- Halogen-free / RoHS compliant
(EU RoHS / UL-94 V-0 / MSL: Level 1 compliant)

■ Marking Symbol:

■ Packaging

Embossed type (Thermo-compression sealing) : 20 000 pcs / reel (standard)

■ Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Total Power Dissipation ^{*1, 2}	PT	-	150	mW
Electrostatic Discharge ^{*1, 3}	ESD	-	±15	kV
Peak Pulse Power ^{*1, 4}	Ppp	-	20	W
Peak Pulse Current ^{*1, 4}	Ipp	-	1.9	A
Operating Junction Temperature ^{*5}	Tj	-	150	°C
Ambient Temperature	Ta	-40	150	°C
Storage Temperature	Tstg	-55	150	°C

Note) *1: Ta = Tj = 25°C



*2: Device mounted on a FR4 PCB (25.4mm×25.4mm , 1mm thick), copper wiring (27.6mm² area , 36μm thick).

*3: Test method: IEC61000-4-2


(C = 150 pF , R = 330 Ω , Contact and Air discharge: 10 times)

*4: Test method: IEC61000-4-5 (Tp = 8/20 μs , Unrepeated)


*5: Power derating is necessary so that Tj < 150°C .




(IEC61000-4-2 Pulse)



(IEC61000-4-5 Pulse)




(TLP Pulse)




■ Electrical Characteristics Ta = 25°C ± 3°C

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reverse Stand-off Voltage	VRWM	-			5.0	V
Reverse Breakdown Voltage *1	VBR	IT = 0.1 mA	7.0	7.5	8.0	V
Reverse Breakdown Voltage *1	VBR	IT = 5 mA	7.0	7.6	8.0	V
Reverse Leakage Current	IR	VR = 5 V			50	nA
Clamping Voltage *2	Vc	Ipp = 1.9 A, Tp = 8/20 μs		10.6	12.7	V
Clamping Voltage *3	Vc-TLP	Ipp = 8 A		12.0		V
Clamping Voltage *3	Vc-TLP	Ipp = 16 A		16.0		V
Terminal Capacitance	Ct	VR = 0 V, f = 1 MHz		6.0		pF

- Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7031 measuring methods for diodes.
 2. Absolute frequency of input and output is 5 MHz.
 3. *1: VBR guaranteed 20 ms after current flow.
 *2: conditions : 8/20 μs Pulse Waveform
 *3: conditions : TLP parameter Z = 50 Ω, Tp = 100 ns, tr = 0.2ns, average window t1 = 54.4ns, t2 = 94.4ns



(Magnified figure)




Symbol	Parameter
Ipp	Peak Pulse Current
Vc	Clamping Voltage @ Ipp
IR	Reverse Leakage Current @ VRWM
VRWM	Reverse Stand-off Voltage
IT	Test Current
VBR	Breakdown Voltage @ IT




Typical Characteristics at Ta = 25°C, unless otherwise specified


Reverse Breakdown Voltage



Reverse Leakage Current




Terminal Capacitance *1



Note) *1: Test Condition : f = 1 MHz


Typical Characteristics at Ta = 25°C, unless otherwise specified

ESD Clamping (Positive Pulse)^{*1}




Note) *1: Input Pulse :
IEC61000-4-2 / Contact / + 8 kV

ESD Clamping (Negative Pulse)^{*2}




Note) *2: Input Pulse :
IEC61000-4-2 / Contact / - 8 kV

ESD Clamping (Positive Pulse)^{*3}



Note) *3: Input Pulse :
IEC61000-4-2 / Contact / + 15 kV


ESD Clamping (Negative Pulse)^{*4}



Note) *4: Input Pulse :
IEC61000-4-2 / Contact / - 15 kV


Typical Characteristics at Ta = 25°C, unless otherwise specified

Clamping Voltage ^{*1}




Note) *1: Input : 8/20 μs pulse waveform

TLP Characteristic ^{*2}



Note) *2: Input Pulse : Tp = 100ns , tr = 0.2ns , average window t1 = 54.4ns , t2 = 94.4ns
Extraction of Rd using least squares fit of TLP characteristic between Ipp = 10 A and Ipp = 25 A .
Rd : Dynamic resistance

Total Power Dissipation




(Evaluation Board Condition ³)

	PCB Size PCB Thickness	Copper Wiring	
		Thickness	Area
(1)	25.4 mm ×25.4 mm 1 mm thick	36 μm thick	27.6 mm ²
(2)			50.7 mm ²
(3)			108.0 mm ²


Note) *3: FR4 PCB

(Evaluation Board Outline)




DCSP0402010-N2

Unit: mm



■ Land Pattern (Reference) (Unit: mm)



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.
- (3) The products described in this book are intended to be used for general applications (such as office equipment, communications equipment, measuring instruments and household appliances), or for specific applications as expressly stated in this book.
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automotive equipment, traffic signaling equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.It is to be understood that our company shall not be held responsible for any damage incurred as a result of or in connection with your using the products described in this book for any special application, unless our company agrees to your using the products in this book for any special application.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.

No.020210

单击下面可查看定价，库存，交付和生命周期等信息

[>>Panasonic\(松下\)](#)