



# BAV16W

## SURFACE MOUNT SWITCHING DIODES

**Voltage**

**100 V**

**Power**

**350 mW**

**SOD-123**



Unit : inch(mm)

### Features

- Fast Switching Speed
- Electrically Identical to Standard JEDEC
- High Conductance
- Surface Mount Package Ideally Suited for Automatic Insertion
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

### Mechanical Data

- Case: SOD-123 plastic case
- Terminals: Solderable per MIL-STD-750, Method 2026
- Standard packaging: 8mm tape
- Approx. Weight: 0.00037 ounces, 0.0104 grams
- Marking: A6



### Maximum Ratings ( $T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	VALUE	UNIT
Reverse voltage	$V_R$	75	V
Peak reverse voltage	$V_{RM}$	100	V
RMS voltage	$V_{RMS}$	50	V
Maximum DC blocking voltage	$V_{DC}$	75	V
Maximum average forward current at $T_A = 25^\circ\text{C}$	$I_{AV}$	150	mA
Peak forward surge current : 1 $\mu\text{s}$	$I_{FSM}$	4	A
Power dissipation derate above 25 $^\circ\text{C}$	$P_{TOT}$	350	mW
Maximum forward voltage	$V_F$	0.855 / 0.01A	V
Maximum dc reverse current at rated dc blocking voltage $T_J = 25^\circ\text{C}$	$I_R$	1@75V	$\mu\text{A}$
Junction capacitance (Notes 1)	$C_J$	2	pF
Maximum reverse recovery (Notes 2)	$T_{RR}$	6	ns
Typical thermal resistance	$R_{\theta JA}$	450	$^\circ\text{C/W}$
Operating junction temperature range	$T_J$	-55 to +150	$^\circ\text{C}$

Note : 1.  $C_J$  at  $V_R=0, f=1\text{MHz}$

2. From  $I_F=10\text{mA}$  to  $I_R=1\text{mA}$ ,  $V_R=6\text{V}$ ,  $R_L=100\Omega$



# BAV16W




FIG. 1-TYPICAL FORWARD CHARACTERISTIC




FIG. 2-TYPICAL REVERSE CHARACTERISTICS





FIG. 3 POWER DERATING CURVE



# BAV16W

## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information  
T/R – 10K per 13" plastic Reel  
T/R – 3K per 7" plastic Reel



# BAV16W


**Part No\_packing code\_Version**

BAV16W\_R1\_00001

BAV16W\_R2\_00001

For example :

RB500V-40\_R2\_00001



Packing Code <b>XX</b>				Version Code <b>XXXXXX</b>		
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HF or RoHS	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



## BAV16W

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Panjit\(强茂\)](#)