

## COMPLIMENTARY PAIR ENHANCEMENT MODE MOSFETS

This space-efficient device contains an electrically-isolated complimentary pair of enhancement-mode MOSFETs (one N-channel and one P-channel). It comes in a very small SOT-363 package. This device is ideal for portable applications where board space is at a premium.


### FEATURES

- Complimentary Pairs
- Low On-Resistance
- Low Gate Threshold Voltage
- Fast Switching
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

### APPLICATIONS

- Switching Power Supplies
- Hand-Held Computers, PDAs

MARKING CODE: S82



**MAXIMUM RATINGS - TOTAL DEVICE**  $T_J = 25^\circ\text{C}$  Unless otherwise noted

Rating	Symbol	Value	Units
Total Power Dissipation (Note 1)	$P_D$	200	mW
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 to +150	$^\circ\text{C}$

**MAXIMUM RATINGS N - CHANNEL -  $Q_1$ , 2N7002**  $T_J = 25^\circ\text{C}$  Unless otherwise noted

Rating	Symbol	Value	Units
Drain-Source Voltage	$V_{DSS}$	60	V
Drain-Gate Voltage $R_{GS} < 1.0\text{Mohm}$	$V_{DGR}$	60	V
Gate-Source Voltage - Continuous	$V_{GSS}$	$\pm 20$	V
Drain Current - Continuous (Note 1)	$I_D$	115	mA

**MAXIMUM RATINGS P - CHANNEL -  $Q_2$ , BSS84**  $T_J = 25^\circ\text{C}$  Unless otherwise noted

Rating	Symbol	Value	Units
Drain-Source Voltage	$V_{DSS}$	-50	V
Drain-Gate Voltage $R_{GS} < 20\text{Kohm}$	$V_{DGR}$	-50	V
Gate-Source Voltage - Continuous	$V_{GSS}$	$\pm 20$	V
Drain Current - Continuous (Note 1)	$I_D$	130	mA

### THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Units
Thermal Resistance, Junction to Ambient (Note 1)	$R_{thja}$	625	$^\circ\text{C/W}$

Note 1. FR-5 board 1.0 x 0.75 x 0.062 inch with minimum recommended pad layout

**Electrical Characteristics - N-CHANNEL - Q<sub>1</sub> , 2N7002**  $T_J = 25^\circ\text{C}$  Unless otherwise noted

**OFF CHARACTERISTICS (Note 2)**

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$BV_{DSS}$	$I_D = 10\mu\text{A}, V_{GS} = 0\text{V}$	60	80	-	V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 60\text{V}, V_{GS} = 0$ $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$	-	-	1.0	$\mu\text{A}$
Gate-Body Leakage	$I_{GSS}$	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$	-	-	$\pm 10$	nA

**ON CHARACTERISTICS (Note 2)**

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	1.0	1.6	2.5	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = 5\text{V}, I_D = 0.05\text{A}$ $V_{GS} = 10\text{V}, I_D = 0.5\text{A}$	-	1.8	4.5	Ohms
On-State Drain Current	$I_{D(ON)}$	$V_{GS} = 10\text{V}, V_{DS} = 7.5\text{V}$	0.5	1.65	-	A
Forward Transconductance	$g_{FS}$	$V_{DS} = 10\text{V}, I_D = 0.2\text{A}$	0.08	-	-	S

**DYNAMIC CHARACTERISTICS**

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Input Capacitance	$C_{iss}$	$V_{DS} = 25\text{V},$ $V_{GS} = 0\text{V},$ $f = 1.0\text{MHz}$	-	-	50	pF
Output Capacitance	$C_{oss}$		-	-	25	pF
Reverse Transfer Capacitance	$C_{rss}$		-	-	5.0	pF

**SWITCHING CHARACTERISTICS**

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Turn-On Delay Time	$t_{D(ON)}$	$V_{DD} = 30\text{V}, I_D = 0.2\text{A}, R_L = 150\text{ohm}$ $R_{GEN} = 25\text{ohm}, V_{GEN} = 10\text{V}$	-	-	20	ns
Turn-Off Delay Time	$t_{D(OFF)}$		-	-	20	ns

Note 2. Short duration test pulse used to minimize self-heating

**Electrical Characteristics - P-CHANNEL - Q<sub>2</sub>, BSS84**  $T_J = 25^\circ\text{C}$  Unless otherwise noted

**OFF CHARACTERISTICS (Note 3)**

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$BV_{DSS}$	$I_D = -250\mu\text{A}, V_{GS} = 0\text{V}$	-50	-	-	V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = -50\text{V}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$	-	-	-15	$\mu\text{A}$
		$V_{DS} = -50\text{V}, V_{GS} = 0\text{V}, T_J = 125^\circ\text{C}$	-	-	-60	
		$V_{DS} = -25\text{V}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$	-	-	-0.1	
Gate-Body Leakage	$I_{GSS}$	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$	-	-	$\pm 10$	nA

**ON CHARACTERISTICS (Note 3)**

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -1\text{mA}$	-0.8	1.44	-2.0	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS} = -5\text{V}, I_D = -0.1\text{A}$	-	3.8	10	Ohms
Forward Transconductance	$g_{FS}$	$V_{DS} = -25\text{V}, I_D = -0.1\text{A}$	0.05	-	-	S

**DYNAMIC CHARACTERISTICS**







Parameter	Symbol	Conditions	Min	Typ	Max	Units
Input Capacitance	$C_{iss}$	$V_{DS} = -25\text{V}, V_{GS} = 0\text{V}, f = 1.0\text{MHz}$	-	-	45	pF
Output Capacitance	$C_{oss}$		-	-	25	pF
Reverse Transfer Capacitance	$C_{rss}$		-	-	12	pF

**SWITCHING CHARACTERISTICS**







Parameter	Symbol	Conditions	Min	Typ	Max	Units
Turn-On Delay Time	$t_{D(ON)}$	$V_{DD} = -30\text{V}, I_D = -0.27\text{A}, R_{GEN} = 50\text{ohm}, V_{GS} = -10\text{V}$	-	7.5	-	ns
Turn-Off Delay Time	$t_{D(OFF)}$		-	25	-	ns

Note 3. Short duration test pulse used to minimize self-heating

**Typical Characteristics Curves - N-Channel - Q<sub>1</sub>, 2N7002**  $T_J = 25^\circ\text{C}$  Unless otherwise noted




**Electrical Characteristic Curves - P-Channel -  $Q_2$ , BSS84**  $T_J = 25^\circ\text{C}$  Unless otherwise noted



## PACKAGE LAYOUT AND SUGGESTED PAD DIMENSIONS


### SOT-363

Unit : inch(mm)



### SOT-363

Unit : inch(mm)



## ORDERING INFORMATION

BSS8402DW T/R7: 7 inch reel, 3K units per reel, Pin 1 towards tape sprocket holes

BSS8402DW T/R7-R: 7 inch reel, 3K units per reel, Pin 1 away from tape sprocket holes

BSS8402DW T/R13: 13 inch reel, 10K units per reel, Pin 1 towards tape sprocket holes

BSS8402DW T/R13-R: 13 inch reel, 10K units per reel, Pin 1 away from tape sprocket holes



# BSS8402DW


## Part No\_packing code\_Version

BSS8402DW\_R1\_00001

BSS8402DW\_R2\_00001

For example :

**RB500V-40\_R2\_00001**



Packing Code <b>XX</b>				Version Code <b>XXXXX</b>		
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HF or RoHS	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



## BSS8402DW

---

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.



单击下面可查看定价，库存，交付和生命周期等信息

[>>Panjit\(强茂\)](#)