



ER1AAFC ~ ER1JAFC Series

Surface Mount Super Fast Recovery Rectifier

Voltage

50~600 V

Current

1 A



Features

- For surface mounted applications in order to optimize board space
- High temperature metallurgically bonded-no compression contacts as found in other diode-constructed rectifiers
- Glass passivated junction
- Easy pick and place
- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : Molded plastic, SMAF-C
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0012 ounces, 0.034 grams

SMAF-C



Maximum Ratings and Thermal Characteristics (T_A = 25°C unless otherwise noted)

PARAMETER	SYMBOL	ER1AAFC	ER1BAFC	ER1CAFC	ER1DAFC	ER1EAFC	ER1GAFC	ER1JAFC	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	150	200	300	400	600	V
Maximum RMS Voltage	V _{RMS}	35	70	105	140	210	280	420	V
Maximum DC Blocking Voltage	V _R	50	100	150	200	300	400	600	V
Maximum Average Forward Rectified Current	I _{F(AV)}	1							A
Peak Forward Surge Current : 8.3 ms Single Half Sine-Wave Superimposed On Rated Load	I _{FSM}	30							A
Instantaneous Forward Voltage at 1A	V _F	0.95			1.25		1.7		V
Reverse Current	I _R	1							uA
Typical Junction Capacitance Measured at 1 MHz And Applied V _R = 4V	C _J	15							pF
Reverse Recovery Time ^(Note 1)	T _{RR}	35							ns
Typical Thermal Resistance	^(Note 2) R _{θJL}	24							°C/W
	^(Note 3) R _{θJA}	150							
Operating Junction Temperature Range	T _J	-55 to +150							°C
Storage Temperature Range	T _{STG}	-55 to +150							°C

NOTES:

1. Reverse Recovery Test Conditions: I_F=0.5A, I_R=1A, Recover to 0.25A
2. Mounted on a FR4 PCB, single-sided copper, with 48cm² copper pad area
3. Mounted on a FR4 PCB, single-sided copper, standard footprint



ER1AAFC ~ ER1JAFC Series

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Reverse Characteristics




Fig.5 Typical Reverse Characteristics




Fig.6 Typical Forward Characteristics



ER1AAFC ~ ER1JAFC Series

TYPICAL CHARACTERISTIC CURVES




Fig.7 Typical Forward Characteristics




Fig.8 Typical Forward Characteristics





ER1AAFC ~ ER1JAFC Series

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
ER1AAFC	SMAF-C	3K pcs / 7" reel	ER1A
ER1BAFC	SMAF-C	3K pcs / 7" reel	ER1B
ER1CAFC	SMAF-C	3K pcs / 7" reel	ER1C
ER1DAFC	SMAF-C	3K pcs / 7" reel	ER1D
ER1EAFC	SMAF-C	3K pcs / 7" reel	ER1E
ER1GAFC	SMAF-C	3K pcs / 7" reel	ER1G
ER1JAFC	SMAF-C	3K pcs / 7" reel	ER1J

Packaging Information & Mounting Pad Layout





ER1AAFC ~ ER1JAFC Series

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Panjit\(强茂\)](#)