



UF3010GP

ULTRAFAST PLASTIC RECTIFIER

Voltage

1000 V

Current

3 A


Features

- Glass passivated chip junction
- Ultrafast reverse recovery time
- Low forward voltage drop
- Low switching losses, high efficiency
- High forward surge capability
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: DO-201AD Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.037 ounces, 1.057 grams

DO-201AD



Maximum Ratings and Thermal Characteristics (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	1000	V
Maximum Rms Voltage	V _{RMS}	700	V
Maximum Dc Blocking Voltage	V _{DC}	1000	V
Maximum Average Forward Current	I _{F(AV)}	3	A
Peak Forward Surge Current: 8.3 ms Single Half Sine-Wave Superimposed On Rated Load	I _{FSM}	150	A
Typical Junction Capacitance Measured at 1 MHz And Applied V _R = 4 V	C _J	28	pF
Typical Thermal Resistance	R _{θJA} ⁽¹⁾	38	°C/W
	R _{θJC} ⁽²⁾	11	
Operating Junction Temperature Range	T _J	-55~150	°C
Storage Temperature Range	T _{STG}	-55~150	°C



UF3010GP

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Forward Voltage	V_F	$I_F = 3\text{ A}, T_J = 25^\circ\text{C}$	-	-	1.7	V
Reverse Current	I_R	$V_R = 1000\text{ V}, T_J = 25^\circ\text{C}$	-	-	1	uA
		$V_R = 1000\text{ V}, T_J = 100^\circ\text{C}$	-	-	100	
Reverse Recovery Time	$T_{RR}^{(3)}$	$I_F = 0.5\text{ A}, I_R = 1\text{ A},$ $I_{RR} = 0.25\text{ A}, T_J = 25^\circ\text{C}$	-	-	75	ns

NOTES:

1. The testing condition of the thermal resistance (junction to ambient) is based on 10mm lead length between mini copper pads
2. The testing condition of the thermal resistance (junction to lead) is based on 10mm lead length between two 10cm x 10cm copper pads
3. Reverse Recovery Time $I_F = 0.5\text{ A}, I_R = 1\text{ A}, I_{RR} = 0.25\text{ A}, T_J = 25^\circ\text{C}$



UF3010GP

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics




UF3010GP

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
UF3010GP_AY_00001	DO-201AD	1250pcs / Ammo	UF3010GP	Halogen free
UF3010GP_B0_00001	DO-201AD	500pcs / Box	UF3010GP	Halogen free
UF3010GP_R2_00001	DO-201AD	1250pcs / 13" reel	UF3010GP	Halogen free

Packaging Information & Mounting Pad Layout





UF3010GP

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Panjit\(强茂\)](#)