



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

200V N-Channel Enhancement Mode MOSFET

Voltage

200 V

Current


18 A

Features

- $R_{DS(ON)}$, $V_{GS}@10V, I_D@9A < 160m\Omega$
- High switching speed
- Improved dv/dt capability
- Low Gate Charge
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : TO-251AA, TO-252AA, TO-220AB, ITO-220AB-F Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- TO-251AA Approx. Weight : 0.0104 ounces, 0.297grams
- TO-252AA Approx. Weight : 0.0105 ounces, 0.297grams
- TO-220AB Approx. Weight : 0.067 ounces, 1.89 grams
- ITO-220AB-F Approx. Weight : 0.068 ounces, 2 grams



Maximum Ratings and Thermal Characteristics ($T_A=25^\circ C$ unless otherwise noted)

PARAMETER	SYMBOL	TO-251AA TO-252AA	TO-220AB	ITO-220AB-F	UNITS	
Drain-Source Voltage	V_{DS}	200			V	
Gate-Source Voltage	V_{GS}	± 20				
Continuous Drain Current	I_D	$T_C=25^\circ C$	18		A	
		$T_C=100^\circ C$	11			
Pulsed Drain Current (Note 1)	I_{DM}	72				
Power Dissipation	P_D	$T_C=25^\circ C$	83	89	50	W
		$T_C=100^\circ C$	33	35.6	20	
Single Pulse Avalanche Energy (Note 6)	E_{AS}	72			mJ	
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55~150			$^\circ C$	
Typical Thermal Resistance (Note 4,5)						
- Junction to Case	$R_{\theta JC}$	1.5	1.4	2.5	$^\circ C/W$	
- Junction to Ambient	$R_{\theta JA}$	110	62.5	120		

- Limited only By Maximum Junction Temperature



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	200	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1	1.83	3	
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=9A$	-	126	160	m Ω
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=200V, V_{GS}=0V$	-	-	1.0	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	± 100	nA
Dynamic (Note 7)						
Total Gate Charge	Q_g	$V_{DS}=160V, I_D=18A,$ $V_{GS}=10V$ (Note 2,3)	-	24	-	nC
Gate-Source Charge	Q_{gs}		-	3.7	-	
Gate-Drain Charge	Q_{gd}		-	6.1	-	
Input Capacitance	C_{iss}	$V_{DS}=25V, V_{GS}=0V,$ $f=1.0\text{MHz}$	-	1017	-	pF
Output Capacitance	C_{oss}		-	148	-	
Reverse Transfer Capacitance	C_{rss}		-	36	-	
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=100V, I_D=18A,$ $V_{GS}=10V, R_G=25\Omega$ (Note 2,3)	-	15	-	ns
Turn-On Rise Time	t_r		-	61	-	
Turn-Off Delay Time	$t_{d(off)}$		-	104	-	
Turn-Off Fall Time	t_f		-	99	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_S	---	-	-	18	A
Maximum Pulsed Drain-Source Diode Forward Current	I_{SM}	---	-	-	72	
Diode Forward Voltage	V_{SD}	$I_S=1A, V_{GS}=0V$	-	0.73	1.0	V

NOTES :

1. Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$
2. Essentially independent of operating temperature typical characteristics.
3. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}=150^\circ\text{C}$. Ratings are based on low frequency and duty cycles to keep initial $T_J=25^\circ\text{C}$.
4. The maximum current rating is package limited.
5. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch² with 2oz. square pad of copper.
6. The test condition is $L=1\text{mH}$, $I_{AS}=12A$, $V_{DD}=50V$, $R_G=25\text{ohm}$, Starting $T_J=25^\circ\text{C}$
7. Guaranteed by design, not subject to production testing.



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with VGS




Fig.6 Source-Drain Diode Forward Voltage



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Capacitance vs. Drain-Source Voltage




Fig.11 PJU/PJD Maximum Safe Operating Area




Fig.12 PJP18N20 Maximum Safe Operating Area



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

TYPICAL CHARACTERISTIC CURVES




Fig.13 PJF18N20 Maximum Safe Operating Area




Fig.14 PJU/D Normalized Transient Thermal Impedance




Fig.15 PJP Normalized Transient Thermal Impedance








Fig.16 PJF Normalized Transient Thermal Impedance



PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

Packaging Information






PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
PJU18N20_T0_00001	TO-251AA	80pcs / Tube	U18N20	Halogen free
PJD18N20_L2_00001	TO-252AA	3,000pcs / 13" reel	D18N20	Halogen free
PJP18N20_T0_00001	TO-220AB	50pcs / Tube	P18N20	Halogen free
PJF18N20_T0_00001	ITO-220AB-F	50pcs / Tube	F18N20	Halogen free

Mounting Pad Layout





PJU18N20 / PJD18N20 / PJP18N20 / PJF18N20

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Panjit\(强茂\)](#)