



BI-DIRECTIONAL ESD PROTECTION DIODE


This bi-directional TVS has been designed to protect sensitive equipment against ESD and to prevent Latch-Up events in CMOS circuitry operating at 3.3Vdc and below. This offers an integrated solution to protect a single data line where the board space is a premium.


SPECIFICATION FEATURES

- 40W Power Dissipation (8/20µs Waveform)
- Low Leakage Current, Maximum of 2.5 μA@3.3Vdc
- · Very low Clamping voltage
- IEC 61000-4-2 ESD 30kV air, 30kV Contact Compliance
- Lead free in compliance with EU RoHS2.0 (2011/65/EU & 2015/865/EU directive)
- Green molding compound as per IEC61249 Std. . (Halogen Free)
- Terminals : Solderable per MIL-STD-750, Method 2026
- · Case: DFN 2L, Plastic
- · Marking : BS

APPLICATIONS

- Video I/O ports protection
- Set Top Boxes
- · Portable Instrumentation





MAXIMUM RATINGS

Rating	Symbol	Value	Units
Peak Pulse Power (8/20 μs Waveform)	Ppp	40	W
Peak Pulse Current (8/20 μs Waveform)	I ррм	6	Α
Operating Junction and Storage Temperature Range	ТJ,Тsтg	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (T_J=25°C)

Parameter	Symbol	Conditions	Min.	Тур.	Max.	Units
Reverse Stand-Off Voltage	Vwrm		-	-	3.3	V
Reverse Breakdown Voltage	VBR	IBR=1mA	5.4	-	7.0	V
Reverse Leakage Current	IR	VR=3.3V	-	-	2.5	μА
Clamping Voltage (8/20μs)	Vc	IPP=6A	-	-	10	V
Off State Junction Capacitance	Cı	0 Vdc Bias f=1MHz	-	-	25	pF

PAN JIT RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE

May 9,2017-REV.01 PAGE . 1





TYPICAL CHARACTERISTICS




FIG. 1-TYPICAL PEAK CLAMPING VOLTAGE




FIG. 3- Typical Junction Capacitance





FIG. 2-TYPICAL REVERSE CHARACTERISTICS





MOUNTING PAD LAYOUT



ORDER INFORMATION

· Packing information

T/R - 8K per 7" plastic Reel






Part No_packing code_Version

PJSD03LCFN2_R1_00001

For example:



Packing Code XX				Version Code XXXXX			
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code	
Tape and Ammunition Box (T/B)	Α	N/A	0	HF	0	serial number	
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number	
Bulk Packing (B/P)	В	13"	2				
Tube Packing (T/P)	Т	26mm	X				
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y				
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U				
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D				





Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties
 of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation.
 Customers are responsible in comprehending the suitable use in particular applications.
 Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

单击下面可查看定价,库存,交付和生命周期等信息

>>Panjit(强茂)