



# ED302S~ED306S

## SUPERFAST RECOVERY RECTIFIERS

**Voltage**

**200~600 V**

**Current**

**3 A**


### Features

- Plastic package has Underwriters Laboratories Flammability Classification 94V-O utilizing Flame Retardant Epoxy Molding Compound
- Superfast recovery times-epitaxial construction.
- Low forward voltage, high current capability.
- Exceeds environmental standards of MIL-S-19500/228.
- Hermetically sealed.
- Low leakage.
- High surge capability.
- Lead free in compliance with EU RoHS 2011/65/EU directive.
- Green molding compound as per IEC61249 Std..(Halogen Free)

### Mechanical Data

- Case: TO-252 Molded plastic
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: As marking
- Approx. Weight: 0.0104 ounces, 0.297 grams
- Marking: Part number

**TO-252** Unit : inch(mm)



### Maximum Ratings ( $T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	ED302S	ED303S	ED304S	ED306S	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	200	300	400	600	V
Maximum rms voltage	$V_{RMS}$	140	210	280	420	V
Maximum dc blocking voltage	$V_R$	200	300	400	600	V
Maximum average forward rectified current	$I_{F(AV)}$	3				A
Peak forward surge current : 8.3ms single half sine-wave superimposed on rated load	$I_{FSM}$	75				A
Maximum forward voltage at 3A	$V_F$	0.95	1.25		1.7	V
Maximum dc reverse current at rated dc blocking voltage	$I_R$	1				$\mu\text{A}$
		300				
Maximum reverse recovery time	$T_{RR}$	35				nS
Typical junction capacitance	$C_J$	45				pF
Typical thermal resistance	$R_{\theta JA}$	25				$^\circ\text{C/W}$
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +150				$^\circ\text{C}$



# ED302S~ED306S

## RATING AND CHARACTERISTIC CURVES




Fig. 1-FORWARD CURRENT DERATING CURVE




Fig.2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC




Fig.3-TYPICAL REVERSE CHARACTERISTICS




Fig.4-MAXIMUM NON-REPETITIVE SURGE CURRENT





Fig.5-TYPICAL JUNCTION CAPACITANCE



## ED302S~ED306S

### MOUNTING PAD LAYOUT



### ORDER INFORMATION

- Packing information  
T/R – 3K per 13" plastic Reel



## ED302S~ED306S


Part No\_packing code\_Version

ED302S\_L2\_00001

ED302S\_S2\_00001

For example :

RB500V-40\_R2\_00001



Packing Code <b>XX</b>				Version Code <b>XXXXX</b>		
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HF or RoHS	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			



## ED302S~ED306S

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Panjit\(强茂\)](#)