



#### **BI-DIRECTIONAL ESD PROTECTION DIODE**

This Penta has been designed to Protect Sensitive Equipment against ESD and to prevent Latch-Up events in CMOS circuitry operating at 5Vdc and below. This offers an integrated solution to protect up to data line where the board space is a premium.

#### **SPECIFICATION FEATURES**

- 25W Power Dippsipation (8/20µs Waveform)
- Low Leakage Current, Maximum of 1μA@5Vdc
- Very low Clamping voltage
- IEC 61000-4-2 ESD 15kV air, 8kV Contact Compliance
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)
- · Acquire quality system certificate: TS16949
- Manufactured in accordance with AECQ101

#### **APPLICATIONS**

- Video I/O ports protection
- Set Top Boxes
- Portable Instrumentation

#### **MECHANICAL DATA**

• Case : SOD-923, Plastic

• Terminals : Solderable per MIL-STD-750, Method 2026

• Approx. Weight: 0.00002 ounces, 0.0005 grams.

• Marking : X



Fig.138(TOP VIEW)

# 0.034(0.85) 0.029(0.75) 0.021(0.55) 0.007(0.18) 0.003(0.08) 1 0.042(1.05) 0.037(0.95)

#### **MAXIMUM RATINGS**

Rating	Symbol	Value	Units
Peak Pulse Power (8/20 μs Waveform)	Ppp	25	W
Peak Pulse Current (8/20 μs Waveform)	I PP	2	А
ESD Voltage (HBM)	V <sub>ESD</sub>	>25	kV
Operating Junction and Storage Temperature Range	Тл,Твтс	-55 to +150	°C


#### ELECTRICAL CHARACTERISTICS (TA=25°C)


Parameter	Symbol	Conditions	Min.	Тур.	Max.	Units
Reverse Stand-Off Voltage	Vwrm		-	-	5.0	V
Reverse Breakdown Voltage	VBR	I BR=1mA	5.78	-	7.82	V
Reverse Leakage Current	I R	V <sub>R</sub> =5V	-	-	1.0	μΑ
Clamping Voltage (8/20μs)	Vc	I PP=2A	-	-	12.5	V
Off State Junction Capacitance	Cı	0 Vdc Bias f=1MHz	-	-	15	pF






#### TYPICAL CHARACTERISTICS












#### **MOUNTING PAD LAYOUT**



#### **ORDER INFORMATION**

• Packing information

T/R - 8K per 7" plastic Reel





#### Part No\_packing code\_Version

PJSD05LCTM-AU\_R1\_000A1

# For example : RB500V-40\_R2\_00001 Part No. Serial number Version code means HF Packing size code means 13" Packing type means T/R

Packing Code XX			Version Code XXXXX			
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HF or RoHS	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	Α	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	В	13"	2			
Tube Packing (T/P)	Т	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			





#### **Disclaimer**

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties
  of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation.
   Customers are responsible in comprehending the suitable use in particular applications.
   Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

单击下面可查看定价,库存,交付和生命周期等信息

>>Panjit(强茂)