

## PCB terminal block - ZFKKDSA 1,5-5,08- 2 - 1891522

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current: 12 A, Nom. voltage: 400 V, Pitch: 5.08 mm, Number of positions: 2, Connection method: Spring-cage connection, Mounting: Soldering, Conductor/PCB connection direction: 45 °, Color: green

### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 6.4 GRM  |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|                |            |
|----------------|------------|
| Length         | 24 mm      |
| Pitch          | 5.08 mm    |
| Dimension a    | 5.08 mm    |
| Pin dimensions | 0,7 x 1 mm |
| Hole diameter  | 1.3 mm     |

#### General

|                                         |                     |
|-----------------------------------------|---------------------|
| Range of articles                       | ZFKKDS(A) 1,5       |
| Insulating material group               | I                   |
| Rated surge voltage (III/3)             | 4 kV                |
| Rated surge voltage (III/2)             | 4 kV                |
| Rated surge voltage (II/2)              | 4 kV                |
| Rated voltage (III/3)                   | 250 V               |
| Rated voltage (III/2)                   | 400 V               |
| Rated voltage (II/2)                    | 630 V               |
| Connection in acc. with standard        | EN-VDE              |
| Nominal current $I_N$                   | 12 A                |
| Nominal cross section                   | 1.5 mm <sup>2</sup> |
| Maximum load current                    | 12 A                |
| Insulating material                     | PA                  |
| Solder pin surface                      | Sn                  |
| Inflammability class according to UL 94 | V0                  |

## PCB terminal block - ZFKKDSA 1,5-5,08- 2 - 1891522

### Technical data

#### General

|                           |        |
|---------------------------|--------|
| Internal cylindrical gage | A1     |
| Stripping length          | 7.5 mm |
| Number of positions       | 2      |

#### Connection data

|                                        |    |
|----------------------------------------|----|
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max  | 14 |
| Minimum AWG according to UL/CUL        | 26 |
| Maximum AWG according to UL/CUL        | 12 |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141109 |
| eCl@ss 4.1 | 27141109 |
| eCl@ss 5.0 | 27141190 |
| eCl@ss 5.1 | 27141190 |
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440401 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11     | 39121432 |
| UNSPSC 12.01  | 39121432 |
| UNSPSC 13.2   | 39121432 |

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)