

Housing - HC-HPR-B10-BFH-EMR-BK - 1411083

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON B10 panel mounting base, HPR series, for screw locking, for increased environmental and EMC requirements

Why buy this product

- Vibration and shock: IEC 61373/EN 50155, category 1, class 1B



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	160.0 g
Custom tariff number	85389099
Country of origin	China

Technical data

Dimensions

Height	20 mm
Width	58 mm
Length	145 mm
Length of the assembly cutout	48 mm
Width of the assembly cutout	35 mm

Ambient conditions

Degree of protection of housing (IP)	IP68 (0.5 bar / 24 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 125 °C

General

Housing - HC-HPR-B10-BFH-EMR-BK - 1411083


Technical data

General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Size	B10
Housing type	Panel mounting base
Locking type	for M6 screws
Torque	4 Nm (Locking screw)
Screw connection	none
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, black
Seal material	NBR
Material lock	Stainless steel
Material of locking screw	Stainless steel


Drawings

Dimensional drawing



Dimensional drawing

Dimensional drawing



Panel cutout

Classifications

eCl@ss

eCl@ss 5.1	27143424
eCl@ss 6.0	27261203
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

ETIM

ETIM 4.0	EC000437
ETIM 5.0	EC000437

Housing - HC-HPR-B10-BFH-EMR-BK - 1411083

Approvals

Approvals

Approvals

EAC / GL

Ex Approvals

Approvals submitted

Approval details

EAC

GL

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)