

# FLK 50/2FLK20/EZ-DR/ 400/DV

Order No.: 2304924



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2304924>

Assembled circular cable, with two 20-pos. and one 50-pos. socket strip (for Emerson Delta V). The cable is suitable for coupling 32-channel modules. Length of cable: 4 m

## Commercial data

|                |                                                                                                        |
|----------------|--------------------------------------------------------------------------------------------------------|
| GTIN (EAN)     | <br>4 046356 011730 |
| Note           | Made-to-order                                                                                          |
| sales group    | I680                                                                                                   |
| Pack           | 1 pcs.                                                                                                 |
| Customs tariff | 85444290                                                                                               |

## Product notes

WEEE/RoHS-compliant since:  
05/02/2005



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General

|                                         |           |
|-----------------------------------------|-----------|
| Nominal voltage $U_N$                   | < 50 V AC |
|                                         | 60 V DC   |
| Max. current carrying capacity per path | 1 A       |

|                                         |                                                     |
|-----------------------------------------|-----------------------------------------------------|
| Max. conductor resistance               | 0.16 $\Omega$ /m                                    |
| Ambient temperature (operation)         | -20 °C ... 50 °C                                    |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C                                    |
| Number of positions, control side       | 20                                                  |
| Number of connectors, control side      | 2                                                   |
| Number of positions, module side        | 50                                                  |
| Number of connectors, modul side        | 1                                                   |
| Fixed cable length                      | 4 m                                                 |
| Single wire, cross section              | 0.14 mm <sup>2</sup>                                |
| AWG                                     | 26                                                  |
| Single wire, material                   | Cu tin-plated                                       |
| External diameter                       | 10.5 mm                                             |
| Cable, preassembly                      | Insulation displacement, IEC 60352-4/DIN EN 60352-4 |
| Shielding                               | no                                                  |

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)