

Door position switch - PLD E 400-DS-3,0/FS/0,6 - 2702336

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Door position switch with 3 m cable with open cable end and 0.6 m cable with M8 socket (Snap-in), including mounting accessories

Product Description

This door position switch is used to automatically switch the class 400 PLD enclosure lights on or off when opening or closing the control cabinet door. If the enclosure lights are connected in series, this door position switch is to be used before the first light.

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	200.000 g
Custom tariff number	85365080
Country of origin	Germany

Technical data

Dimensions

Width	31 mm
Height	30.5 mm
Depth	98.3 mm
Note on dimensions	Without connected cables

Ambient conditions

Ambient temperature (operation)	-30 °C ... 80 °C
Degree of protection	IP54

General

Net weight	197.1 g
Mechanical service life	10 x 10 ⁶ cycles

Power supply for module electronics

Door position switch - PLD E 400-DS-3,0/FS/0,6 - 2702336

Technical data

Power supply for module electronics

Rated voltage	24 V DC
Rated current	3 A

Standards and Regulations


Protection class	II
------------------	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Circuit diagram



Classifications

eCl@ss

eCl@ss 8.0	27119220
eCl@ss 9.0	27119290

ETIM

ETIM 5.0	EC002557
----------	----------

Approvals

Approvals

Approvals


UL Listed / cUL Listed / cULus Listed


Ex Approvals


Door position switch - PLD E 400-DS-3,0/FS/0,6 - 2702336

Approvals

Approval details

UL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 140324

cUL Listed  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 140324

cULus Listed 

Accessories

Accessories

Sensor/Actuator cable - SAC-3P-M 8MS/ 0,6-PUR/M 8SIFS - 1417699



Sensor/Actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, on Socket straight M8 Snap-in, Cable length: 0.6 m

Sensor/Actuator cable - SAC-3P-M 8MS/ 1,0-PUR/M 8SIFS - 1417700



Sensor/Actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, on Socket straight M8 Snap-in, Cable length: 1 m

Sensor/Actuator cable - SAC-3P-M 8MS/ 3,0-PUR/M 8SIFS - 1417701



Sensor/Actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug straight M8, on Socket straight M8 Snap-in, Cable length: 3 m

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact \(菲尼克斯\)](#)