


## Bus system cable - SAC-5P- 2,0-924/M12FR - 1405983

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Bus system cable, CANopen®, DeviceNet™, 5-position, PVC, gray, shielded, free cable end, on Socket angled M12, coding: A, cable length: 2 m, Connector unshielded



DeviceNet CANopen



### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 1 pc                                                                                                    |
| Minimum order quantity | 50 pc                                                                                                   |
| GTIN                   | <br>4 046356 800457 |
| GTIN                   | 4046356800457                                                                                           |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 2 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
|                                 | -25 °C ... 90 °C (Plug / socket) |
| Degree of protection            | IP65                             |
|                                 | IP67                             |
|                                 | IP68                             |

#### General

|                       |              |
|-----------------------|--------------|
| Rated current at 40°C | 4 A          |
| Rated voltage         | 48 V AC      |
|                       | 60 V DC      |
| Number of positions   | 5            |
| Insulation resistance | ≥ 100 MΩ     |
| Coding                | A - standard |
| Signal type/category  | CANopen®     |

# Bus system cable - SAC-5P- 2,0-924/M12FR - 1405983

## Technical data

### General

|                      |                        |
|----------------------|------------------------|
|                      | DeviceNet™             |
| Status display       | No                     |
| Overvoltage category | II                     |
| Degree of pollution  | 3                      |
| Tightening torque    | 0.4 Nm (M12 connector) |

### Material

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Material, knurls                       | Zinc die-cast, nickel-plated                |
| Sealing material                       | NBR                                         |

### Cable

|                                               |                                                                             |
|-----------------------------------------------|-----------------------------------------------------------------------------|
| Cable type                                    | CANopen®/DeviceNet™, PVC, gray                                              |
| Cable type (abbreviation)                     | 924                                                                         |
| UL AWM style                                  | 2464 (80°C/300 V)                                                           |
| Cable structure                               | 2xAWG22 (Signal) + 2xAWG22 (Power)                                          |
| Conductor cross section                       | 2x 0.34 mm² (Signal line)                                                   |
|                                               | 2x 0.34 mm² (Power supply)                                                  |
| AWG signal line                               | 22                                                                          |
| AWG power supply                              | 22                                                                          |
| Conductor structure signal line               | 19x 0.15 mm                                                                 |
| Conductor structure, voltage supply           | 19x 0.15 mm                                                                 |
| Core diameter including insulation            | 1.27 mm ±0.05 mm (Signal line)                                              |
|                                               | 2.24 mm ±0.13 mm (Power supply)                                             |
| Wire colors                                   | red-black, blue-white                                                       |
| Twisted pairs                                 | 2 cores to the pair                                                         |
| Type of pair shielding                        | Plastic-coated aluminum foil, aluminum side inside                          |
| Overall twist                                 | 2 pairs around a drain wire in the center to the core                       |
| Shielding                                     | Plastic-coated aluminum foil with a filler litz wire, aluminum side outside |
| External cable diameter D                     | 6.9 mm ±0.13 mm                                                             |
| Minimum bending radius, flexible installation | 15 x D                                                                      |
| Cable weight                                  | 64.51 kg/km                                                                 |
| External sheath, color                        | gray                                                                        |
| Outer sheath, material                        | PVC                                                                         |
| Material conductor insulation                 | Foamed PE (Signal line)                                                     |
|                                               | PVC (Power supply)                                                          |
| Conductor material                            | Bare Cu litz wires                                                          |
| Insulation resistance                         | ≥ 59.38 Ω*m (Signal line)                                                   |

Bus system cable - SAC-5P- 2,0-924/M12FR - 1405983

Technical data

Cable


|                                 |                                              |
|---------------------------------|----------------------------------------------|
|                                 | ≥ 57.41 GΩ*km (Power supply)                 |
| Working capacitance             | nom. 78.74 pF (per meter)                    |
| Wave impedance                  | 120 Ω ±12 Ω                                  |
| Signal runtime                  | 4.46 ns/m                                    |
| Shield attenuation              | 0.95 dB (f = 125 kHz)                        |
|                                 | 1.64 dB (f = 500 kHz)                        |
|                                 | 2.3 dB (f = 1 MHz)                           |
| Special properties              | UL standards PLTC and ITC                    |
| Other resistance                | UV resistant                                 |
| Flame resistance                | FT4                                          |
| Resistance to oil               | yes                                          |
| Ambient temperature (operation) | -30 °C ... 75 °C (cable, fixed installation) |

Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |


Drawings

Dimensional drawing




M12 x 1 socket, angled

Circuit diagram



Contact assignment of the M12 socket


Schematic diagram



Pin assignment M12 socket, 5-pos., A-coded, socket side view

## Bus system cable - SAC-5P- 2,0-924/M12FR - 1405983

Cable cross section



CANopen<sup>®</sup>/DeviceNet<sup>™</sup>, PVC, gray [924]

### Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27060308 |
| eCl@ss 11.0   | 27060307 |
| eCl@ss 4.0    | 27060300 |
| eCl@ss 4.1    | 27060300 |
| eCl@ss 5.0    | 27060300 |
| eCl@ss 5.1    | 27060300 |
| eCl@ss 6.0    | 27279200 |
| eCl@ss 7.0    | 27279218 |
| eCl@ss 9.0    | 27060308 |

## Bus system cable - SAC-5P- 2,0-924/M12FR - 1405983

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000830 |
| ETIM 4.0 | EC001855 |
| ETIM 6.0 | EC001855 |
| ETIM 7.0 | EC001855 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 26121616 |
| UNSPSC 7.0901 | 26121616 |
| UNSPSC 11     | 26121604 |
| UNSPSC 12.01  | 26121616 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 18.0   | 26121604 |
| UNSPSC 19.0   | 26121604 |
| UNSPSC 20.0   | 26121604 |
| UNSPSC 21.0   | 26121600 |

### Approvals

#### Approvals

#### Approvals

UL Listed / cUL Listed / EAC-RoHS / EAC / cULus Listed

#### Ex Approvals

#### Approval details

|                    |                                                                                     |                                                                                                                                                       |               |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Listed          |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 221474 |
| Nominal voltage UN | 125 V                                                                               |                                                                                                                                                       |               |
| Nominal current IN | 4 A                                                                                 |                                                                                                                                                       |               |

|                    |                                                                                     |                                                                                                                                                       |               |
|--------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| cUL Listed         |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 221474 |
| Nominal voltage UN | 125 V                                                                               |                                                                                                                                                       |               |
| Nominal current IN | 4 A                                                                                 |                                                                                                                                                       |               |

## Bus system cable - SAC-5P- 2,0-924/M12FR - 1405983

### Approvals

|              |                                                                                   |                          |
|--------------|-----------------------------------------------------------------------------------|--------------------------|
| EAC-RoHS     |  | RU D-<br>DE.HB35.B.00387 |
| EAC          |  | RU C-<br>DE.BL08.B.00286 |
| cULus Listed |  |                          |

Phoenix Contact 2022 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)