

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sensor/actuator box, application: Standard, connection method: M8 socket Metal, number of slots: 8, number of positions: 3, coding: A - standard, slot assignment: single, status display: yes, pnp; master cable connection: M16 plug connection 90°, shielding: no

Your advantages

- Safety in the field, thanks to molded housing and high degree of protection
- Convenient: increased machine availability thanks to quick and easy diagnostics

Commercial Data

Item number	1166980
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	B08
Product Key	BF3BCB
GTIN	4063151184087
Weight per Piece (including packing)	145.7 g
Weight per Piece (excluding packing)	140 g
Customs tariff number	85444290
Country of origin	DE

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Technical Data

Notes

Assembly instruction:	NOTE: Observe the permissible bending radii when laying conductors, since the degree of protection may be put in jeopardy if the bending forces are too high. Alleviate mechanical loads upstream of the connector, e.g. by using cable ties.
Note on application	Unused slots are to be sealed off prior to commissioning. Suitable sealing elements are to be found under "Accessories".

Product properties

Product type	Distributor boxes with M8 to M12 slots
Number of positions	3
Application	Standard
Number of slots	8
Coding	A - standard

Material specifications

Color	black
Material of threaded sleeve	Cu alloy
Material of threaded sleeve surface	Nickel-plated
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	PBT
Material of contact, master cable side	CU alloy
O-ring material	FKM
Material of the moulding mass	PUR
Housing material	PBT

Dimensions

Dimensional drawing	
Width	30 mm
Height	27 mm
Length	134.4 mm

Connection data

Pin assignment	1 / 4 (A) = P
----------------	---------------

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Slot/position = Wire color or connection	2 / 4 (A) = J
	3 / 4 (A) = T
	4 / 4 (A) = S
	5 / 4 (A) = G
	6 / 4 (A) = R
	7 / 4 (A) = E
	8 / 4 (A) = O
	1-8 / 1 (+ 24 V) = A+M
	1-8 / 3 (0 V) = L+U

LED signaling

Status display present	yes
------------------------	-----

Electrical properties

Max. operating voltage U_{\max}	30 V DC
Local diagnostics	Supply voltage per module Green LED
	Status display I/O Yellow LED
Nominal voltage U_N	24 V DC
Rated current, total	6 A
Max. current carrying capacity per path	2 A
Current carrying capacity per slot	2 A

Cable / line

Sensor/actuator connection system	M8 socket
Connection method	M16 plug connection
Tightening torque - master cable - plug connection	1.5 Nm
Tightening torque of mounting screw for fixing the housing	0.8 Nm
Tightening torque slot sensor/actuator cable	0.2 Nm

Standards and regulations

Standards/specifications	IEC 61076-2-104
--------------------------	-----------------

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-20 °C ... 80 °C

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD




1166980

<https://www.phoenixcontact.com/us/products/1166980>

Drawings

Schematic diagram




M16 plug connection pin, 14-pos.

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD


1166980

<https://www.phoenixcontact.com/us/products/1166980>

Dimensional drawing



Circuit diagram




Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Schematic diagram



M8 slot, socket, 3-pos.

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Approvals



cUL Recognized

Approval ID: E238705



UL Recognized

Approval ID: E238705

cULus Recognized

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Classifications

ECLASS

ECLASS-9.0	27440108
ECLASS-11.0	27440111
ECLASS-10.0.1	27440111

ETIM

ETIM 8.0	EC003558
----------	----------

UNSPSC

UNSPSC 21.0	31251500
-------------	----------

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Accessories

Master cable

Master cable - SAC-12P- 5,0-PUR/M16FR - 1693720

<https://www.phoenixcontact.com/us/products/1693720>



Master cable, application: Sensor/actuator box, connection method: M8 socket Metal, number of slots: 8, number of positions: 12, slot assignment: single, status display: No; master cable connection: M16 plug connection, PUR/PVC, cable length: 5 m, shielding: no

Master cable

Master cable - SAC-12P-10,0-PUR/M16FR - 1693733

<https://www.phoenixcontact.com/us/products/1693733>



Master cable, application: Sensor/actuator box, connection method: M8 socket, number of slots: 8, number of positions: 12, slot assignment: single, status display: No; master cable connection: M16 plug connection, PUR/PVC, cable length: 10 m, shielding: no

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Connector

Connector - SACC-M16FS-14CON-M - 1500554

<https://www.phoenixcontact.com/us/products/1500554>



M16 socket, 14-pos., with solder connection, freely configurable, straight, for a 6.0 mm conductor diameter ... 8.0 mm

Connector

Connector - SACC-M16FR-14CON-M - 1500253

<https://www.phoenixcontact.com/us/products/1500253>



M16 socket, 14-pos., with solder connection, freely configurable, angled, for a 6.0 mm conductor diameter ... 8.0 mm

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Screw plug

Screw plug - PROT-M8 - 1682540

<https://www.phoenixcontact.com/us/products/1682540>



An M8 screw plug for the unoccupied M8 sockets of the sensor/actuator cable, boxes and flush-type connectors

Torque screwdriver

Torque screwdriver - TSD 02 SAC - 1208487

<https://www.phoenixcontact.com/us/products/1208487>



Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Tool

Tool - SAC BIT M8-D10 - 1208461

<https://www.phoenixcontact.com/us/products/1208461>



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 10 mm, for 4 mm hexagonal drive

Tool

Tool - SACC BIT M8-D12 - 1208474

<https://www.phoenixcontact.com/us/products/1208474>



Nut for assembling M8 connectors with longitudinal knurl and a knurl diameter of 12 mm, for 4 mm hexagonal drive

Sensor/actuator box - SACB- 8/3-L-M16-M8 HD



1166980

<https://www.phoenixcontact.com/us/products/1166980>

Marker for terminal blocks

Marker for terminal blocks - UCT1U-TM 5 - 0803204

<https://www.phoenixcontact.com/us/products/0803204>

UniCard materials for thermal transfer printers, for marking terminal blocks from Weidmüller, Conta Clip, and Klemsan, 72-section, offset foot, can be marked with THERMOMARK CARD and BLUEMARK, color: white



Marker for terminal blocks

Marker for terminal blocks - UCT1U-TM 5 CUS - 8191012

<https://www.phoenixcontact.com/us/products/8191012>

Markers for terminal blocks, for marking terminal blocks from Weidmüller, Conta Clip, and Klemsan, 72-section, offset foot, can be ordered in sheet form, marked according to customer specifications, color: white



Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

info@phoenixcon.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)