

Electronic housing - ME MAX 12,5 G 3-3 TBUS KMGY - 2279017

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Electronics housing

Product Features

- Plug-in connection with screw, spring-cage or fast connection technology
- ☑ DIN rail bus connector as an option
- ☑ Large front surface for high-pos. plugs or operating and setting elements

- Fixed or plug-in connection technology can be combined on up to three connection levels, with different pitches
- Functional earth ground contact as an option

Key commercial data

Packing unit	11
Minimum order quantity	10 1
Weight per Piece (excluding packing)	39.6 GRM
Custom tariff number	85472000
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	Polyamide
Color	light gray

Dimensions

Constructional height	114.5 mm
Width	12.5 mm

11.11.2013 Page 1/3



Electronic housing - ME MAX 12,5 G 3-3 TBUS KMGY - 2279017

Technical data

Technical data

Inflammability class according to UL 94	V0
Power dissipation at 20°C in the horizontal mounting position	4.3 W 7.1 W

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

11.11.2013 Page 2 / 3



Electronic housing - ME MAX 12,5 G 3-3 TBUS KMGY - 2279017

Approvals	
Approvals submitted	
Approval details	
UL Recognized \$\)	

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com

单击下面可查看定价,库存,交付和生命周期等信息

>>Phoenix Contact(菲尼克斯)