

## Fork-type cable lug - C-FCI 2,5/M5 - 3240040

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fork-type cable lug, blue, 1.5 - 2.5 mm², M5

### Product Features

- ✓ The fork-type cable lugs without plastic sleeve feature a hard-soldered neck. In conjunction with the CRIMPFOX-RC ... and CRIMPFOX-RCI ... pliers they can be used to achieve maximum conductor pull-out forces
- ✓ The insulated versions are halogen-free and feature "EASY ENTRY" technology



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 0.8 g    |
| Custom tariff number                 | 85369010 |
| Country of origin                    | China    |

### Technical data

#### Dimensions

|                                              |         |
|----------------------------------------------|---------|
| Length (b)                                   | 22.5 mm |
| Width (a)                                    | 8 mm    |
| Maximum stripping length                     | 8 mm    |
| Length of insulation sleeve (c)              | 11 mm   |
| Inner dimension of the insulating collar (d) | 4.5 mm  |
| Inner diameter (f)                           | 5.3 mm  |
| Material thickness (g)                       | 0.8 mm  |

#### General

|                  |      |
|------------------|------|
| Color            | blue |
| Stripping length | 8 mm |

## Fork-type cable lug - C-FCI 2,5/M5 - 3240040

### Technical data

#### General

|                                        |              |
|----------------------------------------|--------------|
| Components                             | Halogen-free |
| Flammability rating according to UL 94 | V2           |

#### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V2 |
|----------------------------------------|----|

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400204 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC001052 |
| ETIM 5.0 | EC001052 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 27113201 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

### Approvals

#### Approvals

#### Approvals

#### EAC / EAC

## Fork-type cable lug - C-FCI 2,5/M5 - 3240040

### Approvals

Ex Approvals

---

Approvals submitted


### Approval details

|     |
|-----|
| EAC |
|-----|

|     |
|-----|
| EAC |
|-----|

### Drawings

Dimensional drawing



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)