

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)





Product Features

- ✓ Versions with bipolar defect indicator
- ▼ Test contacts on both sides of the fuse
- ☑ Can be used for overload/short-circuit protection



Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	6.58 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Note	Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block.
Color	black
Insulating material	PA
Inflammability class according to UL 94	V0
Fuse	G / 6,3 x 32
Nominal current I _N	0.86 mA
Nominal voltage U _N	60 V (if used as fuse terminal block)
	500 V (if used as disconnect terminal block)

Dimensions

11/26/13 Page 1 / 4



Technical data

Dimensions

Width	8.2 mm
Length	40 mm

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

CSA

Ex Approvals



Approvals


Approvals submitted

Approval details

CSA (I)	
Nominal current IN	10 A
Nominal voltage UN	60 V

Drawings


Application drawing



Fuse terminal blocks in interconnected arrangement, block consisting of 5 fuse terminal blocks



Application drawing



Fuse terminal block in single arrangement, block consisting of one fuse terminal block and 4 feed-through terminal blocks

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com

单击下面可查看定价,库存,交付和生命周期等信息

>>Phoenix Contact(菲尼克斯)