

Surge protection base element - PT-IQ-3-EX-BE-UT - 2905496

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Base element for protective plug PLUGTRAB PT-IQ-1X2-EX

The figure shows the PT-IQ-PTB-BE-UT version.

Product Features



Key commercial data

Packing unit	1 pc
Custom tariff number	85363010
Country of origin	Germany

Technical data

Dimensions

Height	90 mm
Width	17.7 mm
Depth	51.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

General

Housing material	PA 6.6
Inflammability class according to UL 94	V-0
Color	blue
Mounting type	DIN rail: 35 mm

Protective circuit

Nominal current I_N	350 mA
Resistance in series	1.2 Ω $\pm$ 5 %

Surge protection base element - PT-IQ-3-EX-BE-UT - 2905496

Technical data

Connection data

Connection method	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12

Classifications

eCl@ss

eCl@ss 5.1	27130801
eCl@ss 6.0	27130807
eCl@ss 8.0	27130807

ETIM

ETIM 4.0	EC000943
ETIM 5.0	EC000943

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)