

Short-circuit connector - SAC-5P-M12MS BK BR 1-2-4 - 1054366

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Termination plug for PSR-CT series RFID transponder switches, M12 male, 5-pos., closes the circuit at the last Y distributor in a series connection

Product Description


Blind plugs for each sensor circuit from the PSR-CT safety circuits.

Your advantages

- ✓ Easy installation with M12 connection
- ✓ Eliminates wiring errors



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 698007
GTIN	4055626698007

Technical data

Dimensions

Width	14.8 mm
Height	14.8 mm
Length	56.3 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 90 °C (Plug)
	-25 °C ... 90 °C (Plug)
Degree of protection	IP65
	IP67

General

Number of positions	5
Color handle area	black

Short-circuit connector - SAC-5P-M12MS BK BR 1-2-4 - 1054366

Technical data

General

Coding	A - standard
Overvoltage category	II
Degree of pollution	3
Insertion/withdrawal cycles	≥ 100

Material


Flammability rating according to UL 94	HB
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values


Drawings

Schematic diagram



Pin assignment M12 male connector, 5-pos., A-coded, male side

Dimensional drawing



Plug, M12 x 1, straight, shielded

Classifications

eCl@ss

eCl@ss 10.0.1	27060311
eCl@ss 11.0	27060311
eCl@ss 6.0	27279200
eCl@ss 7.0	27279218
eCl@ss 9.0	27060311

ETIM

ETIM 6.0	EC001855
ETIM 7.0	EC001855

UNSPSC

UNSPSC 19.0	31251501
UNSPSC 20.0	31251501
UNSPSC 21.0	26121600

Short-circuit connector - SAC-5P-M12MS BK BR 1-2-4 - 1054366

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E221474
Nominal voltage UN		125 V	
Nominal current IN		4 A	

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E221474
Nominal voltage UN		125 V	
Nominal current IN		4 A	

cULus Recognized			
------------------	--	--	--

Phoenix Contact 2022 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact \(菲尼克斯\)](#)