

# Screwdriver - SZS 1,2X8,0 - 1205082

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Screwdriver, bladed, VDE insulated, size: 1.2 x 8.0 x 175 mm, 2-component grip, with non-slip grip

The illustration shows version SZG 0,6 x 3,5

## Why buy this product

- The tools feature ergonomic two-component safety handles
- Large contact surface of blades inside screw head
- Individually tested safety screwdrivers according to DIN EN 60900 (VDE 0682-201)
- For working on or in the vicinity of live parts up to 1000 V AC or 1500 V DC

## Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 283 (CL2-2011)
GTIN	 4 017918 019129
Custom tariff number	82054000
Country of origin	CZECH REPUBLIC

## Technical data

### General

Length (b)	287 mm
Width (a)	40 mm
Design	Phillips
Blade thickness	1.2 mm
Blade width	8 mm
Blade height	175 mm
Weight	140 g
Test standard	DIN/ISO 2380-1 IEC 60900:2004

## Classifications

### eclass

eCl@ss 4.0	21040401
------------	----------

# Screwdriver - SZS 1,2X8,0 - 1205082

## Classifications

### eclass

eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040401
eCl@ss 6.0	21040401
eCl@ss 7.0	21040409

### etim

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158

### unspsc

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

## Approvals

### Approvals

---

#### Approvals

VDE approval of drawings / GOST / VDE approval of drawings

---

#### Ex Approvals


---

#### Approvals submitted

---

### Approval details

VDE approval of drawings 

GOST 

# Screwdriver - SZS 1,2X8,0 - 1205082

## Approvals


VDE approval of drawings

## Drawings

Pictogram



Dimensioned drawing



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)