

Slave protocol chip - IBS SUPI 4 QFN - 2746744

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Slave protocol chip, for INTERBUS



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	250 pc
Custom tariff number	85423290
Country of origin	Japan

Technical data

Dimensions

Width	8 mm
Height	0.9 mm
Depth	8 mm
Length	8 mm

Ambient conditions

Ambient temperature (storage/transport)	-65 °C ... 150 °C (at max. 60 %)
Ambient temperature (operation)	-40 °C ... 85 °C (at max. 75% humidity during operation)

Module

IC power supply voltage	3.3 V DC $\pm$ 10 % (DC)
Typical current consumption	20 mA
Connection method	Remote bus, local bus or installation remote bus
Interface	INTERBUS
Internal data length	64 bytes IN/64 bytes OUT
User interface	MFP interface, digital I/O (16 IN/16 OUT, 32 IN, 32 OUT), parallel and serial port for microprocessors

General

Type	QFN 52 (with copper block)
------	----------------------------

Slave protocol chip - IBS SUPI 4 QFN - 2746744

Classifications

eCl@ss

eCl@ss 4.0	27250201
eCl@ss 4.1	27250201
eCl@ss 5.0	27250203
eCl@ss 5.1	27249201
eCl@ss 6.0	27242605
eCl@ss 7.0	27242605
eCl@ss 8.0	27242608

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC001601
ETIM 5.0	EC001604

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)