

**UK 10,3-HESILED N 72**

Order No.: 3048661

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=3048661>

Lever-type fuse terminal block

**Commercial data**

|                |                                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------|
| GTIN (EAN)     | <br>4 046356 138642 |
| Note           | Made-to-order                                                                                        |
| sales group    | A040                                                                                                 |
| Pack           | 10 pcs.                                                                                              |
| Customs tariff | 85363030                                                                                             |

**Product notes**WEEE/RoHS-compliant since:  
04/03/2008

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Certificates / Approvals**

Certification

CSA, CUL, UL

## Accessories

| Item            | Designation                 | Description                                                                                                                                                                    |
|-----------------|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Assembly</b> |                             |                                                                                                                                                                                |
| 3022218         | CLIPFIX 35                  | Snap-on end bracket, for 35 mm NS 35/7.5 or NS 35/15 DIN rail, can be fitted with Zack strip ZB 8 and ZB 8/27, terminal strip marker KLM 2 and KLM, width: 9.5 mm, color: gray |
| 0801762         | NS 35/ 7,5 CU UNPERF 2000MM | DIN rail, material: Copper, unperforated, height 7.5 mm, width 35 mm, length: 2 m                                                                                              |
| 0801733         | NS 35/ 7,5 PERF 2000MM      | DIN rail, material: Steel, galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 2 m                                                   |
| 0801681         | NS 35/ 7,5 UNPERF 2000MM    | DIN rail, material: Steel, unperforated, height 7.5 mm, width 35 mm, length: 2 m                                                                                               |
| 1201756         | NS 35/15 AL UNPERF 2000MM   | DIN rail, deep-drawn, high profile, unperforated, 1.5 mm thick, material: Aluminum, height 15 mm, width 35 mm, length 2 m                                                      |
| 1201895         | NS 35/15 CU UNPERF 2000MM   | DIN rail, material: Copper, unperforated, 1.5 mm thick, height 15 mm, width 35 mm, length: 2 m                                                                                 |
| 1201730         | NS 35/15 PERF 2000MM        | DIN rail, material: Steel, perforated, height 15 mm, width 35 mm, length: 2 m                                                                                                  |
| 1201714         | NS 35/15 UNPERF 2000MM      | DIN rail, material: Steel, unperforated, height 15 mm, width 35 mm, length: 2 m                                                                                                |
| 1201798         | NS 35/15-2,3 UNPERF 2000MM  | DIN rail, material: Steel, unperforated, 2.3 mm thick, height 15 mm, width 35 mm, length: 2 m                                                                                  |
| <b>Bridges</b>  |                             |                                                                                                                                                                                |
| 3009299         | EB 56-18                    | Insertion bridge, Number of positions: 56, Color: gray                                                                                                                         |
| 3009367         | EB 56-18/L1-L2-L3           | Insertion bridge, Number of positions: 56, Color: gray                                                                                                                         |
| <b>General</b>  |                             |                                                                                                                                                                                |
| 3048409         | VS-UK 10,3-HESI N 3POL      | Fuse modular terminal block, Color: black                                                                                                                                      |
| <b>Marking</b>  |                             |                                                                                                                                                                                |
| 0809984         | ZBF10:SO/CMS                | Zack marker strip, flat, in 10 mm pitch, labeled according to customer specifications, 10-section, divisible, color: White                                                     |
| 0809997         | ZBF10:UNBEDRUCKT            | Zack marker strip, flat, in 10 mm pitch, unprinted, 10-section, for individual labeling with M-PEN 0,8, X-PEN, or CMS-P1-PLOTTER                                               |
| <b>Tools</b>    |                             |                                                                                                                                                                                |
| 1205066         | SZS 1,0X4,0 VDE             | Screwdriver, bladed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip                                                                             |

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)