

## Antenna cable - PSI-CAB-GSM/UMTS-10M - 2900981

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

GSM/UMTS antenna cable, 10 m long; SMA (male) -> SMA (female), 50 Ohm impedance



### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	520.0 g
Custom tariff number	85442000
Country of origin	Poland

### Technical data

#### Dimensions

Fixed cable length	10 m
External diameter	5.50 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

#### General

Connection 1	Connector connection
Connection method	SMA (male)
Connection 2	Connector connection
Connection method	SMA (female)
Outer sheath, material	LSFH
Minimum bending radius	82.00 mm
Frequency range	850 MHz
	900 MHz
	1800 MHz
	1900 MHz
	2100 MHz

# Antenna cable - PSI-CAB-GSM/UMTS-10M - 2900981

## Technical data

### General

Impedance	50 Ω
-----------	------

### Attenuation

Cable, attenuation	Approx. 0.23 dB/m at 850 MHz
	Approximately 0.24 dB/m at 900 MHz
	Approximately 0.35 dB/m at 1.8 GHz
	Approximately 0.39 dB/m at 2.1 GHz

## Classifications

### eCl@ss

eCl@ss 4.0	27240490
eCl@ss 4.1	27240490
eCl@ss 5.0	27242208
eCl@ss 5.1	27242208
eCl@ss 6.0	19070490
eCl@ss 7.0	19070490
eCl@ss 8.0	27061802

### ETIM

ETIM 3.0	EC000310
ETIM 4.0	EC001682
ETIM 5.0	EC001682

### UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	43223108
UNSPSC 11	39121008
UNSPSC 12.01	43223108
UNSPSC 13.2	43223108

## Approvals

### Approvals

---

Approvals

EAC

---

## Antenna cable - PSI-CAB-GSM/UMTS-10M - 2900981

### Approvals

Ex Approvals

---

Approvals submitted

---

### Approval details

EAC
-----

---

Phoenix Contact 2015 © - all rights reserved  
<http://www.phoenixcontact.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact \(菲尼克斯\)](#)