

## Screw flange - UT 4-TWIN/ 1P-F - 3060322

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Screw flange, for screwing COMBI plugs, with the same structure and pitch as the relevant COMBI terminal blocks



### Product Features

- ✓ Same shape and pitch as the basic terminal blocks

### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 10.0 g   |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Germany  |

### Technical data

#### General

|                                        |      |
|----------------------------------------|------|
| Number of levels                       | 1    |
| Number of connections                  | 3    |
| Color                                  | gray |
| Insulating material                    | PA   |
| Flammability rating according to UL 94 | V0   |

#### Dimensions

|                  |         |
|------------------|---------|
| Width            | 6.2 mm  |
| End cover width  | 2.2 mm  |
| Length           | 56.7 mm |
| Height           | 46.9 mm |
| Height NS 35/7,5 | 47.5 mm |
| Height NS 35/15  | 55 mm   |

#### Connection data

|                   |                  |
|-------------------|------------------|
| Connection method | Screw connection |
|-------------------|------------------|

## Screw flange - UT 4-TWIN/ 1P-F - 3060322

### Technical data

#### Connection data

|                        |        |
|------------------------|--------|
| Screw thread           | M2,5   |
| Tightening torque, min | 0.4 Nm |
| Tightening torque max  | 0.5 Nm |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141117 |
| eCl@ss 4.1 | 27141117 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |
| eCl@ss 8.0 | 27141135 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC001041 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

Approvals

EAC / EAC

---

Ex Approvals

---



# Screw flange - UT 4-TWIN/ 1P-F - 3060322

## Approvals

Approvals submitted

---

### Approval details

|     |
|-----|
| EAC |
|-----|

|     |
|-----|
| EAC |
|-----|

单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)