

Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Set, consisting of COMBICON headers and PCB terminal blocks for 6 x 4-pos. (24-pos.), color: green



Key commercial data

Packing unit	1 1
Weight per Piece (excluding packing)	38.3 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Product type	Printed circuit board housing
Approval	CSA
	VDE report with production monitoring
	IECEE CB Scheme
	GOST
	UL Recognized
	cUL Recognized
	CCA
	cULus Recognized
Rated voltage (IEC)	320
Rated current (IEC)	12
Mounting type	Soldering
Number of positions	4
Pitch	5 mm
Levels	Single-level
Type of locking	Without

Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC002638
ETIM 5.0	EC002638

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

CSA / VDE Gutachten mit Fertigungsüberwachung / IECEx CB Scheme / UL Recognized / cUL Recognized / CCA / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961

Approvals

CSA 		
	B	D
mm ² /AWG/kcmil	28-12	28-12
Nominal current I _N	10 A	10 A
Nominal voltage U _N	300 V	300 V

VDE Gutachten mit Fertigungsüberwachung 	
Nominal current I _N	8 A
Nominal voltage U _N	250 V

IECEE CB Scheme 	
Nominal current I _N	8 A
Nominal voltage U _N	250 V

UL Recognized 		
	B	D
mm ² /AWG/kcmil	30-12	30-12
Nominal current I _N	15 A	10 A
Nominal voltage U _N	300 V	300 V

cUL Recognized 		
	B	D
mm ² /AWG/kcmil	30-12	30-12
Nominal current I _N	15 A	10 A
Nominal voltage U _N	300 V	300 V

Printed-circuit board connector - MSTBO 2,5/ 4-4 ST SET - 2707961

Approvals

CCA	
Nominal current I _N	8 A
Nominal voltage U _N	250 V

cULus Recognized  US

Accessories

Accessories

Coding element

Coding section - CR MSTBO-G1 - 2199618

Coding section



单击下面可查看定价，库存，交付和生命周期等信息

[>>Phoenix Contact\(菲尼克斯\)](#)